

KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS -- NITROGEN A800500-10 -- 4920-00-870-0582

===== Product Identification =====

Product ID:NITROGEN A800500-10

MSDS Date:05/20/1986

FSC:4920

NIIN:00-870-0582

MSDS Number: BJDTH

=== Responsible Party ===

Company Name:KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS

Address:2500 AIRPORT DRIVE

City:WILSON

State:NC

ZIP:27893-9604

Country:US

Info Phone Num:307-744-5487

Emergency Phone Num:919-237-7004

CAGE:61423

=== Contractor Identification ===

Company Name:KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS

Address:2500 AIRPORT DRIVE

Box:City:WILSON

State:NC

ZIP:27893-9604

Country:US

Phone:252-237-7004

CAGE:61423

===== Composition/Information on Ingredients =====

Ingred Name:NITROGEN

CAS:7727-37-9

RTECS #:QW9700000

Fraction by Wt: 100%

ACGIH TLV:ASPHYXIAN; 9192

===== Hazards Identification =====

LD50 LC50 Mixtur

e:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CHRONIC:N/A.

INHALE:HEADACHE,DROWSINESS,DIZZINESS,EXCITATION, EXCESS SALIVATION,
VOMITING AND UNCONSCIOUSNESS. LIQUID CONTACT MAY CAUSE FROSTBITE.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SEE HEALTH HAZARDS
Medical Cond Aggravated by Exposure:THE TOXICOLOGY, PHYSICAL AND
CHEMICAL PROPE
RTIES OF THE MATERIAL DO NOT SUGGEST THAT
OVEREXPOSURE IS LIKELY TO AGGRAVATE EXISTING MEDICAL CONDITIONS.

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR,GET MD. GIVE ART. RESP. IF NECESSARY OR
OXYGEN. FLUSH EYES W/WATER AT LEAST 15 MIN. FOR EXPOSURE TO LIQUID,
WARM FROSTBITE AREA WITH WATER (NOT TO EXCEED 105F). IN CASE OF
MASSIVE EXPOSURE, REMOVE CLOTHES AND SHOWER W/WARM WATER. NOTE:
THERE IS NO SPECIFIC ANTIDOTE. DIR.
TREATMENT AT CNTRL OF SYMPTOM.

===== Fire Fighting Measures =====

Extinguishing Media:NITROGEN CANNOT CATCH FIRE
Fire Fighting Procedures:USE MEDIA APPROPRIATE FOR SURROUNDING
FIRE.EVACUATE PERSONNEL FROM DANGER AREA.DELUGE CONTAINER W/WATER
SPRAY FROM MAX.DISTANCE TIL COOL.MOVE CONTAINERS AWAY.
Unusual Fire/Explosion Hazard:GAS CANNOT CATCH FIRE.CONT.MAY RUPTURE
DUE TO HEAT OR FIRE.NO PART OF A CONT.SHOULD BE >52C.MOST
CONTAINERS WILL VENT CON
TENTS WHEN EXPOSED TO HIGH TEMPS.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE PERSONNEL. USE SCBA WHERE NEEDED.
VENTILATE AREA WHERE LEAK OCCURED. TEST AREA FOR SUFFICIENT OXYGEN
PRIOR TO PERMITTING RE-ENTRY OF PERSONNEL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE & USE W/ADEQUATE VENTILATIONS.
MIXING TWO OR M

ORE GASES OR LIQUIDIFIED GASES MAY COMBINE TO CREATE
UNEXPECTED HAZARD.OBTAIN SAFETY INFORMATION.

Other Precautions:NEVER WORK ON A PRESSURIZED SYSTEM. IF THERE IS A
LEAK,CLOSE THE CYLINDER VALVE,BLOW DOWN THE SYSTEM BY VENTING TO A
SAFE PLACE, THEN REPAIR THE LEAK.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PER OSHA 29 CFR 1910.134 - ACCEPTABLE TO MSHA
AND NIOSH

Ventilation:LOCAL EXHAUST PREFERRED, MECHANICAL ACCEPTABLE

Protectiv

e Gloves:USE FOR HANDLING CYLINDERS & 1910.132.

Eye Protection:I/A/W OSHA CFR 1910.133

Other Protective Equipment:METATORSAL SHOES FOR CYLINDER HANDLING, IAW
OSHA 29 CFR 1910.132

Work Hygienic Practices:GOOD HYGIENE PRACTICE AS WITH ANY INDUSTRIAL
CHEMICAL

Supplemental Safety and Health

THIS IS PART "B" OF A TWO PART PRODUCT, WHICH IS NOT A KIT.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:-320F,-195C

Melt/Freeze Pt:M.P/F.P Text:-346F,-210C

Vapor Pres:@ 20C GAS

Vapor Density:0.967

Spec Gravity:1.2506G/L @ 0C

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS,ODORLESS GAS AT AMBIENT TEMP AND PRESSURE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

UNDER CERTAIN CONDITIONS NITROGEN CAN REACT VIOLENTLY
W/LITHIUM,NEODYMIUM,TITANIUM OR OZONE.

Stability Condition to Avoid:CAUTION HIGH PRESSURE GAS

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

=

===== Disposal Considerations =====

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE. DISCARD ANY PRODUCT, RESIDUE DISPOSABLE CONTAINERS OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER I/A/W FED, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.