

WILLIAM F. NYE, INC. -- LUBRICATING GREASE/NYE RHEOLUBE,SEE SUPDATA -- 9150-00-140-4434

=====
Product Identification
=====

Product ID:LUBRICATING GREASE/NYE RHEOLUBE,SEE SUPDATA

MSDS Date:03/11/1988

FSC:9150

NIIN:00-140-4434

MSDS Number: BJFMS

=== Responsible Party ===

Company Name:WILLIAM F. NYE, INC.

Address:12 HOWLAND ROAD

City:FAIRHAVEN

State:MA

ZIP:02719

Country:US

Info Phone Num:508-996-672

1

Preparer's Name:PAUL A. BESSETTTE

CAGE:DO759

=== Contractor Identification ===

Company Name:AMPEX CORP

Address:401 BROADWAY

Box:City:REDWOOD CITY

State:CA

ZIP:94063-3126

Country:US

CAGE:92739

Company Name:NYE LUBRICANTS INC

Address:12 HOWLAND RD

Box:City:FAIR HAVEN

State:MA

ZIP:02719

Country:US

Phone:508-996-6721

CAGE:98354

Company Name:WILLIAM F. NYE, INC.

Address:12 HOWLAND ROAD

City:FAIRHAVEN

State:MA

ZIP:02719

Phone:704-628-1711

CAGE:DO759

=====
Composition/Information on Ingredi

ents =====

Ingred Name:SYNTHETIC HYDROCARBON
CAS:68037-01-4

Ingred Name:PHENOLIC ANTIOXIDANT
CAS:118-82-1

Ingred Name:STEARYL ANHYDRIDE
CAS:58239-72-8

Ingred Name:POLYBUTENE POLYMER
CAS:9003-29-6
RTECS #:EM9032000

Ingred Name:LITHIUM HYDROXYSTEARATE
CAS:7620-77-1

Ingred Name:OIL MIST
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IA
RC:NO OSHA:NO

Health Hazards Acute and Chronic:POSSIBLE SKIN AND EYE IRRITATION.
POSSIBLE RESPIRATORY PASSAGE IRRITATION AT HIGH TEMPERATURES.

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE: WASH THOROUGHLY, CONTACT PHYSICIAN IF IRRITATION
PERSISTS. SKIN: WASH W/ SOAP AND WATER. INH: MOVE TO FRESH
AIR AND
REFER TO A PHYSICIAN FOR TREATMENT. INGEST: CALL MD IMMEDIATELY .

===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:435F,224C

Lower Limits:UNDEFINED

Upper Limits:UNDEFINED

Extinguishing Media:CO*2, FOAM, DRY CHEMICAL, WATER SPRAY

Fire Fighting Procedures:AVOID SMOKE INHALATION. WATER OR FOAM MAY
CAUSE FROTHING. USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE
EQUIP .

Unusual Fire/Explosion Hazard:NONE.

=====

Accidental Release Measures =====

Spill Release Procedures:WIPE OR SCRAPE UP SPILLAGE AND PLACE IT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACES THOROUGHLY W/ DETERGENT AND WATER TO REDUCE SLIPPING HAZARD.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.

Other Precautions:WASH HANDS THOROUGHLY BEFORE SMOKING. USERS SHOULD BE ALER

T TO THE POSSIBILITY THAT VERY SMALL PERCENTAGES OF THE POPULATION MAY DISPLAY UNEXPECTED ALLERGIC SKIN REACTIONS TO OTHERWISE INNOCUOUS INDUST RIAL CHEMICALS AND RAW MATERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR: NOT REQUIRED UNLESS MISTS, SMOKE, OR VAPORS ARE PRODUCED AT HIGH TEMPERATURES.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:REC:AVOID PROLONG/REPEATED SKIN CONTACT

Eye Protection:SAFETY GOG

GLSES RECOMMENDED.

Other Protective Equipment:NONE REQUIRED UNLESS MISTS, SMOKE, OR VAPORS ARE PRODUCED AT HIGH TEMPERATURES.

Work Hygienic Practices:EXERCISE ORDINARY MEASURES OF PERSONAL HYGIENE. AVOID CONTAMINATION OF CIGARETTES OR OTHER TOBACCO PRODUCTS.

Supplemental Safety and Health

NO COMPONENTS ARE KNOWN TO BE HAZARDOUS UNDER NORMAL USAGE.

MANUFACTURERS PART NO./TRADE NAME: AMPEX PN-087-828 IDLER ROLLER LUBE

===== Physical/Chemical Properties =====

=====

Boiling Pt:B.P. Text:NOT VOLAT

Vapor Pres:NEGLIGIBLE

Vapor Density:> AIR

Spec Gravity:.96 @ 77 F

Evaporation Rate & Reference:< DIETHYL ETHER

Solubility in Water:INSOLUBLE

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS.

Stability Condition to Avoid:PYROLYSIS.

Hazardous Decomposition Products:BURNING MAY PRODUCE CA

RBON MONOXIDE AS
WELL AS SMALL AMOUNTS OF OTHER TOXIC FUMES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL PROCEDURES: MANY STATES CLASSIFY WASTE LUBRICANTS AS HAZARDOUS, WHICH MEANS DISPOSAL ONLY BY A LICENSED FIRM. CONSULT LOCAL, STATE, AND FED REGS APPLICABLE IN YOUR AREA.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.