Product ID:1230432 KODAK EKTACOLOR RA DEV/REPL, ALT 1 MSDS Date:06/14/1987 FSC:6750 NIIN:01-354-1029 MSDS Number: BJHRQ === Responsible Party === Company Name: EASTMAN KODAK CO Address:343 STATE ST **City:ROCHESTER** State:NY ZIP:14650 Info Phone Num:(716) 722-5151 Emergency Phone Num:(716) 722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:WATER, H2O CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 60-65%

Ingred Name:LITHIUM SULFATE Fraction by Wt: 5-10%

Ingred Name:POTASSIUM SULFITE CAS:10117-38-1 RTECS #:WT353000 0 Fraction by Wt: 1-5%

Ingred

Name:4-(N-ETHYL-N-2-METHANESULFONYLAMINOETHYL)-2-METHYLPHENYLENEDIA MINE SESQUISULFATE MONOHYDRATE RTECS #:PB4310000 Fraction by Wt: 15-20%

Ingred Name:SULFUR DIOXIDE (SARA III) CAS:7446-09-5 RTECS #:WS4550000 Other REC Limits:2 PPM OSHA PEL:5 PPM/5 STEL ACGIH TLV:2 PPM/5 STEL; 9293

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OS HA:NO Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: IRRITATION & ALLERGIC REACTION. INHALATION: UPPER RESPIRATORY TRACT IRRITATION. INGESTION: HARMFUL. Explanation of Carcinogenicity:NONE Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION & ALLERGIC REACTION. INHALATION: UPPER RESPIRATORY TRACT IRRITATION. INGESTION: HARMFUL. Medical Cond Aggravated by Exposure:ALLERGIC REACTION

First Aid:IN

HALATION: REMOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MED ATT. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. GET MED ATT. SKIN: FLUSH W/PLENTY OF WATER & WASH W/NON-ALKALINE ACID TYPE OF C LEANSER. GET MED ATT. INGESTION: IF CONSCIOUS, RINSE MOUTH/INDUCE VOMITING BY GIVING 1 OR 2 GLASSES OF WATER/SYRUP OF IPECAC. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON. CALL PHYSICIAN.

Flash Point:

NONE Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CO2, FOAM Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard: FIRE & EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS. Spill Release Procedures: FLUSH TO SEWER W/LARGE AMOUNTS OF WATER. NEUTRALIZE W/BAKING SODA, SODIUM BICARBONATE. Neutralizing Agent: BAKING SODA, SODIUM BI CARBONATE Handling and Storage Precautions: KEEP FROM CONTACT W/OXIDIZING MATERIALS. KEEP CONTAINER TIGHTLY CLOSED. AVOID BREATHING & CONTACT W/EYES/SKIN/CLOTHING. USE W/ADEQUATE VENTILATION. Other Precautions: THE DIRECT INSTANTANEOUS DISCHARGE TO RECEIVING BODY OF WATER OF AN AMOUNT OF THIS FORMULATION WHICH WILL RAPIDLY PRODUCE, BY DILUTION, A FINAL CONCENTRATION OF 0.15 MG/L OR LESS. ISN'T EXPECTED TO CA USE AN ADVERSE ENVIRONMENTAL EFFECT.

Respiratory Protection: A NIOSH-APPROVED ACID GAS RESPIRATOR SHOULD BE WORN IF NEEDED.

Ventilation:MECHANICAL: TYPICALLY 10 ROOM VOLUMES PER HOUR IS CONSIDERED GOOD GENERAL VENTILATION. LOCAL EXHAUST: TO KEEP