

TURCO-PUREX INDUSTRIAL CORP SUB OF PENNWALT CORP -- FLURO-CHEK,P60H(M)  
PENETRANT,PART A -- 6850-01-266-4550

===== Product Identification =====

Product ID:FLURO-CHEK,P60H(M) PENETRANT,PART A

MSDS Date:01/08/1987

FSC:6850

NIIN:01-266-4550

Kit Part:Y

MSDS Number: BJJMJ

=== Responsible Party ===

Company Name:TURCO-PUREX INDUSTRIAL CORP SUB OF PENNWALT CORP

Address:7300 BOLSA AVENUE

City:WESTMINISTER

State:CA

ZIP:92684-3600

Country:US

Info Phone Num:714-890-3647

Emergency Phone Num:614-387-6200

CAGE:KO898

=== Contractor Identification ===

Company Name:TURCO PUREX INDUSTRIES SUB OF PENNWALT CORP

Address:7300 BOLSA AVENUE

Box:City:WESTMINISTER

State:CA

ZIP:92683-5211

Country:US

Phone:614-387-6200

CAGE:1JD46

Company Name:TURCO-PUREX INDUSTRIAL CORP SUB OF PENNWALT CORP

Address:7300 BOLSA AVENUE

Box:City:WESTMINISTER

State:CA

ZIP:92684-3600

Country:US

Phone:714-890-3600

CAGE:KO898

=====

Composition/Information on Ingredients =====

Ingred Name:ISOCYLDIPHENYLPHOSPHATE

CAS:29761-21-5

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM(T); 400 PPM

ACGIH TLV:400 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO

IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: EYES:SEVERE IRRITATION.

SKIN:SEVERE IRRITATION, DRYING, DEFATTING; ABSORBED IN TOXIC AMOUNTS. INHALATION:IRRITATION,DIZZINESS, HEADACHE.

INGESTION:SEVERE IRRITATION, NAUSEA

Effects of Overexposure:VAPORS MAY CAUSE DIZZINESS, HEADACHE, NAUSEA.

EYES/SKIN: IRRITATION. INGESTION: NAUSEA

Medical Cond Aggravated by Exposure:NONE REPORTED BY MANUFACTURER

===== First Aid Measures =====

First

Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER.

GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION.

EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

FI

Flash Point Method:TCC

Flash Point:>200F,>93C

Autoignition Temp:Autoignition Temp Text:UNKNOW

Extinguishing Media:CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:USE SELF-CONTAINED RESPIRATORY PROTECTION

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE  
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:MINOR: ABSORB MATERIAL WITH CLAY, VERMICULITE,  
OR SIMILAR ABSORBENT  
MATERIAL. PLACE IN DISPOSAL CONTAINERS.  
ELIMINATE SOURCES OF IGNITION. WEAR APPROPRIATE PROTECTIVE  
CLOTHING. KEEP RINSES FROM ENTERING SEWERS/WATERWAYS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY PROTECTED AREA AWAY FROM  
FROM STRONG OXIDIZERS.

Other Precautions:CLEAN CONTAMINATED EQUIPMENT BY SOLVENT FLUSHING AND  
COLLECT RINSES FOR DISPOSAL. BE CAREFUL TO AVOID SPLATTERING.

===== Exposure Controls

/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR. AIR-SUPPLIED  
OR FILTERING TYPE WITH ORGANIC VAPOR CARTRIDGES ARE RECOMMENDED.  
SCBA MAY BE NEEDED IN HIGH CONCENTRATION.

Ventilation:MAINTAIN SUFFICIENT MECHANICAL VENTILATION TO KEEP  
CONCENTRATION BELOW TLV.

Protective Gloves:NEOPRENE

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER, BOOTS AND  
APRONS

Work Hygienic Practices:

DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.

WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK  
AREA.

Supplemental Safety and Health

KEY1:N1. DISCARD CONTAMINATED SHOES, LAUNDRER CLOTHING AT WORK SITE.  
PART A OF A TWO-PART KIT; PART B LISTED AS PART B UNDER THIS NSN.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>500F,>260C

Vapor Pres:1

Spec Gravity:0.977

Evaporation Rate & Reference: