

SPAULDING COMPOSITES CO INC -- GREY VULCANIZED FIBRE -- 6115-00-700-8035

===== Product Identification =====

Product ID:GREY VULCANIZED FIBRE

MSDS Date:07/01/1989

FSC:6115

NIIN:00-700-8035

Kit Part:Y

MSDS Number: BJKPN

=== Responsible Party ===

Company Name:SPAULDING COMPOSITES CO INC

Address:310 WHEELER STREET

City:TONAWANDA

State:NY

ZIP:14151-5101

Country:US

Info Phone Num:716-692-2000

Emergency

Phone Num:716-692-2000

CAGE:56137

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO

Address:3135 EASTON TURNPIKE

Box:City:FAIRFIELD

State:CT

ZIP:06431

Country:US

Phone:800-626-2000/800-626-2004 (CHRIS)

CAGE:24446

Company Name:LELAND ELECTROSYSTEMS INC

Address:1200 LAWERENCE PKWY

Box:City:ERIE

State:PA

ZIP:16531

Country:US

Phone:814-875-2916

CAGE:0F796

Company Name:SPAULDING COMPOSITES CO INC

Address:310 WHEELER ST

Box:City:TONAWANDA

State:NY

ZIP:14151-5101

Country:US

Phone:716-

692-2000
CAGE:56137

=====
Composition/Information on Ingredients
=====

Ingred Name:VULCANIZED FIBER CONSISTING OF PARTIALLY REGENERATED
CELLULOSE (C*6H*100*5)
Other REC Limits:NOT KNOWN

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:THIS PRODUCT MAY YIELD A NUI
SANCE DUST
WHEN MACHINED OR SANDED.
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:DUST MAY CAUSE MINOR IRRITATION TO EYES.
Medical Cond Aggravated by Exposure:INHALATION OF DUST MAY AGGRAVATE
PRE-EXISTING RESPIRATORY DISORDERS.

=====
First Aid Measures
=====

First Aid:DUST IN EYES, FLUSH WITH WATER.

=====
Fire Fighting Measures
=====

Extinguishing Media:WATER, CARBON DIOXIDE (CO*2) OR FOAM.
Fire Fighting Procedures:USE CONVENTIONAL FIRE FIGHTING PROCEDURES USED
FOR WOOD. SELF-CONTAINED NIOSH/MSHA APPROVED BREATHING APPARATUS
SHOULD BE WORN WHEN ENTERING A BURNING AREA.
Unusual Fire/Explosion Hazard:SMOKE AND TOXIC FUMES MAY BE RELEASED
WHILE BURNING.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SPECIAL: NIOSH/MSHA APPROVED DUST RESPIRATOR.
OTHER: AIR FILTERED WORK BOOTHS.
Ventilation:LOCAL EXHAUST PREFERRED. IF GENERAL

EXHAUST IS USED, ENSURE
ADEQUATE VENTILATION.

Protective Gloves:DESIRABLE TO PREVENT CUTS & ABRASIONS

Eye Protection:SFTY GLASSES WITH FACESHIELD, OR GOGGLES

Work Hygienic Practices:WASH HANDS BEFORE HANDLING FOOD. DO NOT SMOKE,
DRINK, OR EAT IN DUSTY ATMOSPHERE. DO NOT TAKE INTERNALLY.

Supplemental Safety and Health

THIS IS ONE OF THREE HAZARDOUS COMPONENTS OF A MULTI-PART (60 PARTS
TOTAL) KIT.

===== Physical/Chemical Properties =====

Decomp Temp:Decom

p Text:NOT KNOWN

Spec Gravity:1.05-1.55H*2O=1

Appearance and Odor:COLOR - AS ORDERED. NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:CARBON DIOXIDE (CO*2), CARBON MONOXIDE
(CO).

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL OR INCINERATE IN ACCORDANCE WITH
APPLICABLE FEDERAL, STATE, AND LOCAL LAWS.

Di

sclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.