

KOP-COAT INC -- MIL-P-24441/7C COMP A (156 RED) -- 8010-01-302-3607

=====
Product Identification
=====

Product ID:MIL-P-24441/7C COMP A (156 RED)

MSDS Date:03/01/1990

FSC:8010

NIIN:01-302-3607

Kit Part:Y

MSDS Number: BJKVT

=== Responsible Party ===

Company Name:KOP-COAT INC

Address:436 7TH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

Info Phone Num:800-556-7737, 412-227-2155

Emergenc

y Phone Num:800-553-5631, CHEMTREC 800-424-9300

Preparer's Name:C.A. HOPE, OHPSD

CAGE:00297

=== Contractor Identification ===

Company Name:KOP-COAT INC

Address:436 7TH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

Phone:800-553-5631, CHEMTREC 800-424-9300

CAGE:00297

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 20-25%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:

5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 1-5%
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7400000
Fraction by Wt: 25-30%
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 5-10%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:POLYAMIDE RESIN
Fraction by Wt: 1-5%

Ingred Name:VOC 3.6 LBS/GAL
RTECS #:9999999VO

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN:PROLONG/REPEATED CONTACT MAY
CAUSE DEFATT. MAY BE ABSORBED RESULTING SYST EFFECTS, SENSITIZ
REACTION IN CERTAIN PERSONS. INHALED:HIGH CONCENTRATE MAY CAUSE
RSPRTRY TRACT IRRIT & CENTR NERV SYST D EPRESS, MAY LEAD TO LUN
G
CHANGES. POSSIBLE METAL FUME FEVER(FLU LIKE SYMPT).ASPIRAT MAY
CAUSE CHEM PNEUMON, CAN BE FATAL
Explanation of Carcinogenicity:NO KNOWN INGREDIENTS WHICH OCCUR AT
GREATER THAN 0.1% ARE LISTED AS A CARCINOGEN.
Effects of Overexposure:EYES: DIRECT CONTACT MAY IRRIT. SKIN: MAY CAUSE
REDNESS, CRACKING, BLISTERING, IRRIT & DERMATITIS. INHALED:RSPRTRY
TRACT IRRIT, HEADACHE, WEAKNESS, DIZZ, INCOORD, POSSIBLE COLLAPSE.
METAL FUME FEVER:H EADACHE, DIZZ, METALLIC TASTE, GENERAL F

LU-LIKE

SYMPT. INGEST:NAUSEA, VOMIT, DIARRHEA & EFFECTS SIMILAR TO INHALED.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING DISEASE
IN OR HISTORY OF AILMENTS INVOLVING SKIN, EYE, RESPIRATORY TRACT,
LIVER, KIDNEY, CENTRAL NERVOUS SYSTEM ARE AT GREATER THAN NORMAL
RISK OF DEVELOPING ADVERSE EFFECTS.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH W/LG AMTS OF H2O 15 MINS. SEEK MED AID. SKIN:WASH
WELL W/SOAP & H2O, IF SYM
PT DEVELOP/PERSIST, SEEK MED.
INHALED:REMOVE FROM EXPOSURE. IF BREATH STOPPED OR DIFF, ADMIN CPR
OR OXYGEN AS NEED ED, SEEK MED AID. INGEST:DO NOT VOMIT. GIVE 1
GLASS OF MILK OR 1 TO 2 OZ(30 TO 60G)ACTIVATED CHARCOAL IN H2O TO
VICTIM AS TOLERATED. SEEK MED AID.(DO NOT ATTEMPT TO GIVE ANYTHING
BY MOUTH IF UNCONSC)

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:99 F/38 C
Extinguishing Media:WATER MAY BE INEFFECTIVE. USE
CO2, DRY CHEM, FOAM,
WATER SPRAY, ALCOHOL OR UNIVERSAL TYPE FOAMS PER MFR
RECOMMENDATIONS
Fire Fighting Procedures:WEAR COMPLETE FIRE SERVICE PROTECTIVE
EQUIPMENT, FULL-FACE MSHA/NIOSH APPROVED SCBA. USE WATER TO COOL
FIRE-EXPOSED CONTAINERS/STRUCTURES/PROTECT PERSONNEL.
Unusual Fire/Explosion Hazard:VAPORS FORM FLAMM/EXPLOS MIX.VAPOR
HEAVY,MAY TRAVEL TO IGNITE SOURCES.CLOSED CONTAIN MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT(FIRE)MAY EMIT IRRIT/TOXIC GAS/FUME

=====
===== Accidental Release Measures =====

Spill Release Procedures:STOP SPILL/LEAK IF NO RISK. AVOID BREATHING
VAPORS. ELIM IGNITE SOURCES. VENT AREA. AVOID CONTACT W/HOT
LIQ/FUMES. TAKE UP CAREFULLY TO AVOID HEAT/SPARKS. USE INERT ABSORB
TO COMPLETE CLEAN-UP. MATERI AL REACTS W/OXIDIZERS,IF RELEASED INTO
ENVIRON **
Neutralizing Agent:N/K.**REPORT TO NRC 1-800-424-8802. SPILL/LEAK
REPORTABLE AMT IS 100 LBS OR MORE

=====
===== Handling and Storage =

=====

Handling and Storage Precautions:STORE AREAS/BLDG DESIGNED TO COMPLY W/OSHA 1910.106. KEEP IN CLOSED,LABELED CONTAIN W/IN A COOL,WELL SHADED,DRY-VENTED AREA. PROTECT FROM PHYSICAL ***

Other Precautions:***DAMAGE. KEEP CONTAIN CLOSED WHEN NOT IN USE. GROUND/BOND DRUMS. DO NOT USE PRESSURE TO EMPTY DRUMS. DO NOT WEAR CONTAM CLOTHES. DISCARD CONTAM FOOTWEAR. KEEP AWAY FROM HEAT & OPEN FLAME. DO NOT USE WITHOUT FULLY UNDERSTANDING. SEE FILE.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENT DOESN'T MAINTAIN EXPOSURE BELOW PEL(TLV)USE MSHA/NIOSH APPROVED UNITS AS PER CURRENT 29CFR1910.134, INSTRUCTIONS/WARNINGS & NIOSH-RSPRTR DECISION LOGIC-PUB.#87.108. IF WITHIN OSHA PROTECTION FACTOR, AIR PURIFYING OV/FILTER UNITS OK.

Ventilation:GEN/LOCAL EXHAUST VENT IN PATTERN/VOLUME TO CONTROL INHALE EXPOSURE BELOW LIMITS & AREAS BELOW FLAMM VAPOR CONCENTRATE

Protective Gloves:INDUST RESIST FLEX-TY(NEOPRENE OR EQUAL)

Eye Protection:INDUST SAFETY GLASSES, MIN. CHEMICAL ****

Other Protective Equipment:****GOGGLES W/SIDE OR FACE SHIELDS. WEAR INDUST-TY WORK CLOTHES & SAFETY FOOTWEAR. DEPENDS ON WORK CONDITION. SEE FILE.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES & RECOMMENDED PROCEDURES. MAINTAIN GOOD HOUSEKEEPING. OBSERVE ALL PRECAUTIONS.

Supplemental Safety and Health

NOTE TO PHYSICIAN: THERE IS NO SPECIFIC ANTIDOTE FOR EFFECTS FROM OVEREXPOSU

RE TO THIS MATERIAL. TREATMENT SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS & THE CLINICAL CONDITIONS. (SEE FILE FOR ADDITIONAL INFORMATION)

===== Physical/Chemical Properties =====

HCC:F3

Vapor Density:>1

Spec Gravity:12.3-12.8 LB/GL

Viscosity:73-90

Solubility in Water:NEGLIGIBLE

Appearance and Odor:RED VISCOUS LIQUID WITH A TYPICAL SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:Y

ES

AVOID OXIDIZING AGENTS, HEAT, SPARKS AND OPEN FLAMES.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE UPON THERMAL DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods: THIS PRODUCT IS US EPA DEFINED IGNITABLE HAZARDOUS WASTE. DISPOSE OF AS AN IGNITABLE HAZARDOUS WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This informat

ion is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.