

BAKER SEALANTS AND COATINGS CO. -- PETTMAN CEMENT, FORMULA X-767A --
8030-00-245-7032

===== Product Identification =====

Product ID:PETTMAN CEMENT, FORMULA X-767A
MSDS Date:06/12/1985
FSC:8030
NIIN:00-245-7032
MSDS Number: BJLDT
=== Responsible Party ===
Company Name:BAKER SEALANTS AND COATINGS CO.
Address:234 SUYDAM AVE
City:JERSEY CITY
State:NJ
ZIP:07304-3306
Country:US
Info Phone Num:201-333-6
986
Emergency Phone Num:201-333-6986
CAGE:34094
=== Contractor Identification ===
Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:City:JERSEY CITY
State:NJ
ZIP:07304-3306
Country:US
Phone:201-333-6986
CAGE:34094
Company Name:STEVEN INDUSTRIES
Address:39 AVENUE C
Box:8
City:BAYONNE
State:NJ
ZIP:07002-3417
Country:US
Phone:201-437-6501
CAGE:33150

===== Composition/Information on Ingredients =====

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7400000
Frac

tion by Wt: 48%
Other REC Limits:NONE SPECIFIED
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 22%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

Ingred Name:TERPENIC TYPE OILS
Fraction by Wt: 14%
Other REC Limits:NONE SPECIFIED

Ingred Name:SHELLAC
Fraction by Wt: 16%
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes o
f Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:EYES: IRRITATION, CAN DAMAGE EYE
TISSUE. SKIN: IRRITATION.
Effects of Overexposure:EYES: IRRITATION, CAN DAMAGE EYE TISSUE. SKIN:
IRRITATION.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH SOAP AND WATER. IF
OVERCOME BY VAPORS, REMOVE TO FRESH AIR. "OBJECT IS TO GET MEDICAL
ATTENTION IMMEDIATELY".

=====
Fire F
ighting Measures
=====

Flash Point Method:CC
Flash Point:59 F/15 C
Lower Limits:2.5
Extinguishing Media:DRY CHEMICAL OR FOAM TYPE.
Fire Fighting Procedures:USE WATER SPRAY TO COOL EXPOSED SURFACES & TO
PROTECT PERSONNEL.

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. DIKE AREA.
ABSORB WITH SAND OR EARTH OR SUITABLE ABSORBANT.

=====
Handling and Storage
=====

=

Handling and Storage Precautions:KEEP AWAY FROM HEAT. ADEQUATE VENTILATION REQUIRED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR SUPPLIED RESPIRATOR
Ventilation:LOCAL & MECHANICAL, EXPLOSION PROOF EQUIPMENT.
Protective Gloves:CHEMICAL RESISTANT
Eye Protection:CHEMICAL SPLASH GOGGLES
Other Protective Equipment:USUALLY NOT NEEDED
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling
Pt:B.P. Text:179F/81.5C
Melt/Freeze Pt:M.P/F.P Text:-129F,-90C
Vapor Pres:31.20
Spec Gravity:.787
Evaporation Rate & Reference:1.70 (BUTYL ACETATE=1)
Solubility in Water:100%
Appearance and Odor:N/K. "ALL PHYSICAL DATA GIVEN IS ON ALCOHOL"

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:NONE

=====
===== Disposal Considerations =====

Waste Disposal Methods:"AS PER LOCAL, STATE OR FEDERAL REGULATIONS"

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and as

some responsibility for the suitability of this information to their particular situation.