

PRATT & LAMBERT INC., INDUSTRIAL COATING DIVISION -- ENAMEL ALKYD GLOSS GREEN 14064  
ID 742412 -- 8010-00-298-2295

=====  
Product Identification  
=====

Product ID:ENAMEL ALKYD GLOSS GREEN 14064 ID 742412  
MSDS Date:08/23/1990  
FSC:8010  
NIIN:00-298-2295  
MSDS Number: BJLGJ  
=== Responsible Party ===  
Company Name:PRATT & LAMBERT INC., INDUSTRIAL COATING DIVISION  
Address:16116 E. 13TH ST.  
Box:2153  
City:WICH  
ITA  
State:KS  
ZIP:67201  
Country:US  
Info Phone Num:316-733-1361  
Emergency Phone Num:316-733-1361  
Preparer's Name:W.A. ELLISON  
CAGE:PRATT  
=== Contractor Identification ===  
Company Name:PRATT & LAMBERT  
Address:250 PETTIT AVE  
Box:2153  
City:BELLMORE  
State:NY  
ZIP:11710  
Country:US  
Phone:800-647-2253  
CAGE:PRATT  
Company Name:PRATT AND LAMBERT INC  
Address:Box:6027  
City:CLEVELAND  
State:OH  
ZIP:44101-1027  
Country:US  
Phone:216-566-2902  
CAGE:61196

=====  
Composition/Information on Ingredients  
=====

=====

Ingred Name:MINERAL SPIRITS (VP 2 MMHG @ 20C)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 50%

Other REC Limits:LFL 1.0 UFL 7.0

OSHA PEL:100 PPM/525 MG/UC.M.

ACGIH TLV:100 PPM/525 MG/CU.M.

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 102 F/>39 C

Extinguishing Media:USE NFPA CLASS B FIRE EXTINGUISHERS DESIGNED FOR FLAMMABLE LIQUID FIRES. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures:USE WATER TO COOL EXPOSED CONTAINERS TO PREVE

NT PRESSURE BUILD-UP/AUTO-IGNITE/EXPLOSION FROM EXTREME HEAT.

IF WATER USED, FOG NOZZLES ARE PREFERRABLE.

Unusual Fire/Explosion Hazard:OVEREXPOS TO DECOMP PRODUCTS MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY BE DELAYED, OBTAIN MED. KEEP CONTAIN TIGHTLY CLOSED. CONTAINER MAY EXPLODE FROM EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIM IGNITE SOURCES.

DIKE & CONTAIN W/MATERIAL(E.G. SAND,ETC)TRANSFER

LIQ TO COVERED

METAL CONTAIN FOR RECOVERY/DISPOSAL. REMOVE W/INERT ABSORB. USE ONLY NON-SPARK TOOLS. PREVENT CONTAM OF SEWERS,GROUNDWATERS W/MATERIAL/ABSORB

Neutralizing Agent:N/K.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 95F. STORE LARGE AMOUNTS IN COMPLIANCE W/OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.

Other Precautions:EMPTY CONTAINERS MUST NOT BE WASHED & RE-U

SED FOR ANY

PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPT Y. DRUM IS NOT A PRESSURE VESSEL.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WELL VENTED AREA MAY NOT REQUIRE USE OF RSPRTR. RESTRICTED VENT:CHEM CARTRIDGE RSPRTR MAYBE REQUIRED. SPRAY:USE MECH PREFILTER. CONFINED AREA:USE AIR SUPPLIED RSPRTR. IF TLV EXCEED USE PROPE

RPLY FITTED RSPRTR W/PROTECTION FACTOR

Ventilation:GEN DILUTE/LOCAL EXHAUST IN VOL/PATTERN TO KEEP CONCENTRATE OF HAZARD INGRED BELOW LOWEST LIMITS. REMOVE DECOMP PRODUCTS

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING.

Supplemental Safety and Health

THIS PRODUCT, IF DISCARDED DIRECTLY, WOULD BE CLASSIFIED AS HAZARDOU S

WASTE BASED ON ITS IGNITABILITY CHARACTERISTIC, I.E. HAS A FLASH POINT OF 140 DEG. F. OR LESS. THE PROPER RCRA CLASSIFICATION WOULD BE D001.

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:302 TO 390F

Vapor Density:> THAN AIR

Spec Gravity:1.0

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:62

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STR

ONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING/CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS, FLAME.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL LAWS. INCINERATE ONLY

EPA PERMITTED FACILITY. DO NOT

INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF  
FLAMMABLE MATERIALS. CONTAMINATED ADSORBENT MAY BE DISPOSED IN HAZARD  
WASTE LANDFILL

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for

its use. Any person utilizing this

document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.