

SHERWIN INC -- ER83A EMULSIFIER (HYDROPHILIC) -- 6850-01-263-8227

===== Product Identification =====

Product ID:ER83A EMULSIFIER (HYDROPHILIC)

MSDS Date:01/01/1987

FSC:6850

NIIN:01-263-8227

Kit Part:Y

MSDS Number: BJLMK

=== Responsible Party ===

Company Name:SHERWIN INC

Address:5530 BORWICK AVE

City:SOUTH GATE

State:CA

ZIP:90280-7402

Country:US

Info Phone Num:213-861-6324

Emergency Phone Num:213-8

61-6324

CAGE:21405

=== Contractor Identification ===

Company Name:SHERWIN INC.

Address:5530 BORWICK AVE.

City:SOUTH GATE

State:CA

ZIP:90280-7402

Country:US

Phone:562-861-6324/FAX 923-8370

CAGE:21405

===== Composition/Information on Ingredients =====

Ingred Name:NONIONIC SURFACTANTS

Fraction by Wt: 30 - 60%

Other REC Limits:NONE SPECIFIED

Ingred Name:GLYCOLS

Fraction by Wt: 30 - 60%

Other REC Limits:NONE SPECIFIED

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by

Wt: 0.5 - 4%  
Other REC Limits:NONE SPECIFIED

Ingred Name:DYESTUFF  
Fraction by Wt: 200F,>93C  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER  
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE  
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====

Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL FLAMES. CONTAIN SPILLED  
MATERIAL. SOAK UP WITH ABSORBENT MATERIAL AND PLACE INTO LEAK PROOF  
CONTAINERS FOR DISPOSAL.  
Neutralizing Agent:NONE SPECIFIED.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED  
AREA AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED WHEN NOT  
IN USE. PROTECT FROM PHYSICAL DAM  
AGE.  
Other Precautions:NONE SPECIFIED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. IF VAPORS OR MISTS ARE  
GENERATED, USE A NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29  
CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH-RESPIRATOR SELECTION  
TO PREVENT OVEREXPOSURE.  
Ventilation:PROVIDE SUFFICIENT VENTILATION TO MINIMIZE EXPOSURE. LOCAL  
EXHAUST RECOMMENDED BY MANUFACTURER.  
Protective Gloves:NEOPRENE, BUTYL  
Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES  
Other Protective Equipment:SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE  
WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED  
CONTACT.  
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE  
EATING OR DRINKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:T6  
Boiling Pt:B.P. Text:390F,199C  
Evaporation Rate &

Reference:0.1 (BUTYL ACETATE = 1)  
Solubility in Water:APPRECIABLE  
Appearance and Odor:PINK LIQUID, DETERGENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES  
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OTHER  
INCOMPLETELY BURNED CARBON PRODUCTS.

===== Disposal Considerations =====  
=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE  
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent profes  
sional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.