

SHELL OIL COMPANY -- ETHYLENE GLYCOL -- 9150-00-224-8729

=====
Product Identification
=====

Product ID:ETHYLENE GLYCOL

MSDS Date:07/01/1979

FSC:9150

NIIN:00-224-8729

MSDS Number: BJMBS

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Address:HEALTH, SAFETY AND ENVIRONMENT

Box:4320

City:HOUSTON

State:TX

ZIP:77210

Country:US

Info Phone Num:713-241-4819

Emergency Phone Num:713-473-9461

CAGE:

54527

=== Contractor Identification ===

Company Name:SHELL OIL COMPANY

Box:2463

City:HOUSTON

State:TX

ZIP:77210

Country:US

Phone:800-231-6950

CAGE:54527

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 94%

Other REC Limits:NONE SPECIFIED

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TRIETHANOLAMINE PHOSPHATE

CAS:10017-56-8

Fraction by Wt:

2.5%

Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM 2-MERCAPTOBENZOTHIAZOLE

CAS:2492-26-4

Fraction by Wt: 0.25%

Other REC Limits:NONE SPECIFIED

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 2.5%

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ACUTE ORAL LD50 (HUMAN) IS 1500 MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Haz

ards Acute and Chronic:ACUTE: INGESTION:ABDOMINAL DISCOMFORT

OR PAIN, NAUSEA, CENTRAL NERVOUS SYSTEM DEPRESSION. SEVERE KIDNEY AND LIVER DAMAGE FROM LARGE AMOUNTS; MAY BE FATAL.

INHALATION:IRRITATION OF THE NOSE AND THROAT. EYE:DISCOMFORT WITH TRANSIENT CONJUNCTIVITIS. CHRONIC: INHALATION OF MIST MAY PRODUCE SIGNS OF CNS DISTURBANCES.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexpos

ure:MAY CAUSE DIZZINESS, MALAISE, LUMBAR PAIN,

UREMIA, AND CENTRAL NERVOUS SYSTEM DEPRESSION. MAY CAUSE EYE, SKIN & RESPIRATORY TRACT IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF KIDNEY OR LIVER DISORDERS MAYBE AT INCREASED RISK FROM EXPOSURE.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. CALL A PHYSICIAN IF

DISCOMFORT PERSISTS. EYE: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR

15 MINUTES. CALL A PHYSICIAN. SKIN: WASH WITH PLENTY OF SOAP & WATER. REMOVE CONTAMINATED CLOTHING/SHOES. INGESTION: IF CONSCIOUS, GIVE 2 GLASSES OF WATER TO DRINK AND INDUCE VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. CALL A PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:250F,121C
Autoignition Temp:Autoignition Temp Text:UNKNOWN
Lower Limits:3.2
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, ALCOHOL FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: WIPE/SOAK UP WITH PAPER TOWEL OR INERT ABSORBENT. PUT IN DISPOSAL CONTAINER. FLUSH RESIDUE WITH WATER. LARGE SPILL: VENTILATE AREA. IF POSSIBLE, STOP LEAK. DIKE TO RETAIN RUN OFF. VACUUM UP FREE LIQUID. FLUSH RESIDUE WITH WATER.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. WATER DILUTION RECOMMENDED.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.
Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. FOR INDUSTRIAL USE ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE AND DUST/MIST PRE-FILTER

RESPIRATORS AS PER CURRENT 29

CFR 1910.134, INSTRUCTIONS/ WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS ADEQUATE IF USE IS ENCLOSED. LOCAL EXHAUST IS NEEDED IF VENTED INTO WORK AREA.

Protective Gloves:NEOPRENE, NITRILE, PVC OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practic

es:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND

RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

DO NOT TAKE INTERNALLY. DO NOT GET ON SKIN OR IN EYES. AVOID PROLONGED

OR REPEATED BREATHING OF VAPOR. DO NOT BREATHE MISTS. WASH

THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING OR SMOKING

OR USING REST ROOM.

===== Physical/Chemical Properties =====

HCC:V5

Boiling Pt:B.P. Text:387F,197C

Vapor

Pres:0.06 @68F

Vapor Density:2.1 AIR=1

Spec Gravity:1.118

Evaporation Rate & Reference: