

DOW CORNING CORP -- MOLYKOTE(R) 44 GREASE-ALL GRADES -- 9150-01-014-3512

===== Product Identification =====

Product ID:MOLYKOTE(R) 44 GREASE-ALL GRADES

MSDS Date:01/19/1981

FSC:9150

NIIN:01-014-3512

Kit Part:Y

MSDS Number: BJMGT

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emer

gency Phone Num:517-496-5900

Preparer's Name:L.C. VANVOLKINBURG

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:NOT HAZARDOUS INGRED

IENTS  
Fraction by Wt: 100%  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT AVAILABLE  
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Health Hazards Acute and Chronic:ACUTE-EYES:MAY CAUSE TEMPORARY  
DISCOMFORT.CHRONIC-NONE SPECIFIED BY MANUFACTURER.  
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.  
Effects of Overexposure:MAY CAUSE TEMPORARY DISCOMFORT TO EYES.  
Medical Cond Aggrav  
ated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION  
PERSISTS, CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:OC  
Flash Point:>250F,>121C  
Extinguishing Media:CARBON DIOXIDE OR FOAM  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING C  
HEMICAL FIRE. USE WATER  
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.  
Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORNING.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS GREASE. USE ABSORBENT MATERIAL  
TO COLLECT THE REST AND CONTAIN FOR SALVAGE OR DISPOSAL.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN

A COOL, DRY PLACE WITH  
ADEQUATE VENTILATION. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN  
USE. KEEP AWAY FROM OPEN FLAMES & HIGH TEMPERATURES.  
Other Precautions:MINIMIZE SKIN CONTACT. WASH WITH SOAP & WATER BEFORE  
EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDER  
CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF  
CONTAMINATED LEATHER ARTICLES (SHOES) THAT CAN NOT BE  
DECONTAMINATED.

===== Exposure Controls/Personal Protection =====

Respi  
ratory Protection:RESPIRATORY PROTECTION NOT ORDINARILY REQUIRED.  
Ventilation:MECHANICAL  
Protective Gloves:NEOPRENE RUBBER AS REQUIRED.  
Eye Protection:SAFETY GLASSES RECOMMENDED.  
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.  
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.  
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND  
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR  
FOOTWEAR.  
Supplemental Safety and Health  
KIT CONSISTS OF PART NO  
S. 39479-P8,39479-P9,39479-P15, AND  
39479-P16.ACTION INITIATED TO CANCEL SUBJECT NSN. NO FURTHER BUYS  
SHOULD BE MADE.MANUFACTURER HAS DISCONTINUED MARKETING ITEMS AS A  
KIT.

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>300F,>149C  
Vapor Pres: