

CHEMICAL SPECIALISTS & DEVELOPMENT -- THINNER, PAINT TYPE III-ODORLESS --  
8010-01-021-3320

===== Product Identification =====

Product ID:THINNER, PAINT TYPE III-ODORLESS

MSDS Date:09/01/1990

FSC:8010

NIIN:01-021-3320

MSDS Number: BJMGX

=== Responsible Party ===

Company Name:CHEMICAL SPECIALISTS & DEVELOPMENT

Address:#5 HACKBERRY LANE

City:CUT & SHOOT

State:TX

ZIP:77303

Country:US

Info Phone Num:40

9-756-1065

Emergency Phone Num:800-424-9300

Preparer's Name:DAVID SHIPP

CAGE:CHEMS

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS INC

Address:149 WEST TRIGG AVE

City:HARRISBURG

State:NC

ZIP:28075

Country:US

Phone:704-522-0825

CAGE:CHEMS

Company Name:CSD INC. (PRE 1985 NAME: MATHEWS, INC)

Address:420 SEABOARD DRIVE

Box:City:MATTHEWS

State:NC

ZIP:28105-5073

Country:US

Phone:704-821-9822

CAGE:5W216

===== Composition/Information on Ingredients =====

Ingred Na

me:STODDARD SOLVENT  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 100%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM; 9293

=====  
===== Hazards Identification =====  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Health Hazards Acute and Chronic:ASPIRATION OF MATERIAL INTO THE LUNGS  
CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.  
Effects of Overexposure:EYES:MAY CAUSE IRRIT, REDNESS, TEARING.  
SKIN:PROLONGED/REPEATED CONTACT C  
AN CAUSE MOD IRRIT, DEFATTING,  
DERMATITIS. EXCESSIVE INHALE:NASAL & RESPIRATORY IRRIT, CENTRAL  
NERVOUS SYST EFFECTS, DIZZI, WEA K, FATIGUE, NAUSEA, HEADACHES &  
POSSIBLE UNCONSC & EVEN DEATH. SWALLOW:GASTROINTESTINAL IRRIT,  
NAUSEA, VOMIT & DIARRHEA

=====  
===== First Aid Measures =====  
=====

First Aid:SKIN:THORO WASH AREA W/SOAP & WTR. REMOVE CONTAM CLOTHES.  
LAUNDER CLOTHES BEFORE RE-USE. DISCARD SATURATED SHOES. EYES:FLUSH  
W/LG AMNTS OF WTR, LIF  
TING LIDS, GET MED ATTN. SWALLOWED:DO NOT  
INDUCE VOMIT, KEEP PERSON WARM/QUIET, GET MED ATTN. ASPIRATION  
INTO LUNG DUE TO VOMITING CAN CAUSE CHEM PNEUMONITIS, CAN BE FATAL.  
INHALE:REMOVE TO FRESH AIR, ADMIN CPR/OXYGEN AS NEEDED, KEEP  
WARM/QUIET, GET MED

=====  
===== Fire Fighting Measures =====  
=====

Flash Point Method:TCC  
Flash Point:140 F/60 C  
Lower Limits:1.0  
Upper Limits:6.0  
Extinguishing Media:REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL  
Fire Fighti

ng Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES.

Unusual Fire/Explosion Hazard:VAPOR > THAN AIR & MAY TRAVEL ALONG GROUND/MOVED BY VENT & IGNITED BY HEAT, PILOT LIGHT, OTHER IGNITE SOURCES AT DISTANT LOCATIONS. EMPTY CONTAINER CAN EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SM:ABSORB LIQ ON PAPER,VERMICUL,FLOOR

ABSORB,TRANSFER TO HOOD.LG:ELIM IGNITE SOURCES.REMOVE PERSONS NOT WEAR PROTECTIVE EQUIP.STOP SPILL AT SOURCE.DIKE AREA, PREVENT SPREAD, PUMP LIQ TO SALVAGE TANK, TAKE UP REMAIN W/SAND, ETC.SHOVEL TO CONTAINERS\*

Neutralizing Agent:N/K. \*PREVENT RUN-OFF TO SEWERS OR ANY BODIES OF WTR. NOTIFY AUTHORITY IF ENTERS

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS OF MATERIAL MAY BE HAZARDOUS WHEN EMPTIED SINCE EMPTY RETAINS RESIDUES(VAPOR, LIQ, SOLID)ALL HAZARD PRECAUTIONS GIVEN MUST BE OBSERVED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE LIMIT/COMPONENT IS EXCEEDED:NIOSH/MSHA APPROVED AIR SUPPLIED RSPRTR, IF NO ENVIRON CONTROL. OSHA REGS PERMIT OTHER NIOSH/MSHA RSPRTR(NEG PRESS TYPE)UNDER SPECIFIED CONDITIONS(SEE SAFETY EQ UIP SUPPLIER & ENGINEER/ADMIN CONTROLS)

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL &/OR LOCAL EXHAUST) VENT TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:RESISTANT GLOVES SUCH AS NITRILE RUBBER

Eye Protection:CHEM SPLASH GOGGLES OR SAFETY GLASSES

Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN CONTACT WEAR IMPERVIOUS CLOTHING AND BOOTS.

Supplemental Safety and Health

SEE FILE FOR ADDITIONAL INFORMATION.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:360 F/182 C

Melt/Freeze Pt:M.P/F.P Text:-20F,-29C

Vapor Pres:0.05

MMHG

Vapor Density:5.17

Spec Gravity:0.740

Evaporation Rate & Reference:.03 (ETNYL ETHER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, LITTLE IF ANY COLOR; SLIGHT OIL ODOR.

Percent Volatiles by Volume:100

Corrosion Rate:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS, CARBON  
DIOXIDE AND CARBON MONOXIDE,  
VARIOUS HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:SM:ALLOW VOLATILE PORTION TO EVAPORATE IN  
HOOD.ALLOW VAPOR TO COMPLETELY CLEAR HOOD DUCT.DISPOSE REMAINING  
MATERIAL IN ACCORD W/APPLICABLE REGS.LG:DESTROY BY LIQ  
INCINERATE.CONTAM ABSORB MAY BE DEPOSITED IN LANDFILL IN ACCORD  
W/LOCAL,STATE& FED REGS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use

by elements of the Department

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.