

EXXON CO USA, A DIV OF EXXON CORP. -- TERESSTIC N150 -- 9150-01-234-7440

=====  
Product Identification  
=====

Product ID:TERESSTIC N150

MSDS Date:01/01/1987

FSC:9150

NIIN:01-234-7440

MSDS Number: BJNRY

=== Responsible Party ===

Company Name:EXXON CO USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info Phone Num:713-656-3424

Emergency Phone Num:7

13-870-6000

CAGE:29700

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM HYDROCARBONS

Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC



===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL (TLV), USE NIOSH/MSHA APPROVED RESPIRATOR AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation:MECHANICAL (GENERAL) VENTILATION IS USUALLY ADEQUATE.

Protective Gloves:RUBBER GLOVES OR OTHER OIL RESISTANT.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:S

SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE

WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

DISCARD OIL SOAKED SHOES. USE AIR-SUPPLIED RESPIRATORY EQUIPMENT IF EXPOSED TO HOT FUMES.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:755F,402C

Vapor

Pres:0.01

Vapor Density:18

Spec Gravity:0.89

Evaporation Rate & Reference:0.01 NO REFERENCE GIVEN

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT REDDISH LIQUID, VERY SLIGHT HYDROCARBON ODOR

Percent Volatiles by Volume:NEGL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN, OR SODIUM OR CALCIUM HYPOCHLORITE.

Stability Condition to Avoid:HIGH TEMP

ERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE, ALDEHYDES AND KETONES, AND OTHER COMBUSTION PRODUCTS OF NITROGEN AND SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Depa

rtment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.