View NSN Online: https://aerobasegroup.de/nsn/6810-00-234-8366

Product ID: POTASSIUM HYDROXIDE MSDS Date:04/06/1989 FSC:6810 NIIN:00-234-8366 MSDS Number: BJNVJ === Responsible Party === Company Name:MALLINCKRODT INC Address:675 MCDONNELL BLVD Box:5840 **City:SAINT LOUIS** State:MO ZIP:63134 Country:US Info Phone Num:314-539-1600 Emergency Phone Num:314-539-1600 CAGE:379 40 === Contractor Identification === Company Name:MALLINCKRODT INC Address:675 MCDONNELL BLVD Box:5840 City:ST. LOUIS State:MO ZIP:63134 Country:US Phone:314-539-1600 CAGE:37940 **Company Name: SANCHEZ & ASSOCIATES** Address:476 WEST FOGG STREET Box:1649 City:COLTON (MAY BE OUT OF BUSINESS !) State:CA ZIP:92324 Country:US Phone:714-370-3921/FAX824-0341 ALL WRONG# CAGE:0HF19 Company Name: SPECTRUM LABORATORY PRODUCTS INC Address:14422 S SAN PEDRO ST Box:City:GARDENA State:CA ZIP:90248-2027 Country:US

Phone:310-516-8000/FAX: 310-516-9843 CAGE:63415 Company Name:VENUS LABORATORIES INC Address:15571 COMMERCE LANE Box:City:HUNTINGTON BEACH State:CA ZIP:92649 Country:US Phone:714-881-3100 CAGE:0N140

Ingred Name:POTASSIUM HYDROXIDE (SARA III) CAS:1310-58-3 RTECS #:TT2100000 Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED OSHA PEL:C, 2 MG/M3 ACGIH TLV:C 2 MG/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 365 MG/KG (SOLUTION) Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:CORROSIVE LIQUID WILL BURN EYES/SKIN/ RESPIRATORY TRACT. CAN CAUSE BLINDNESS. CAUSES DESTRUCTIVE TISSUE DAMAGE AND SCARRING. MAY LEAD TO SKIN DERMATITIS. INGESTION OF LIQUID OR MIST WILL CAUSE SEVERE BURNING AND IRRITATION TO MUC OUS MEMBRANES, MOUTH, THROAT AND GASTROINTESTINAL TRACT. CAN CAUSE SEVERE PNEUMONITIS. Explanation of Carcinogenicity:THE COMPONENTS OF THIS PRODUCT HAVE NOT SHOWN ANY EVIDENCE OF BEING CARCINOGENIC. Effects of Overexposure:OVEREXPOSURE MAY LEAD TO RESPIRATORY IRRITATION, NAUSEA, FATIGUE, DIZZINESS, HEADACHES, UNCONSCIOUSNESS, DERMATITIS AND EYE IRRITATION. MATERIAL IS CORROSIVE AND WILL BURN

EXPOSED TISSUE. INGESTION MAY RESULT IN ASTHMA-LIKE REACTIONS (WHEEZING, CO UGHING AND SHORTNESS OF BREATH). Medical Cond Aggravated by Exposure:PERSONS WITH A SKIN DISORDER, EYE DISORDERS, OR IMPARED RESPIRATORY FUNCTION SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION.

EYE : IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: DRINK WATER/MILK TO DILUTE. DO NOT INDUCE VOMITING. NOTHING BY MOUTH IF UNCONSCIOUS.CALL DR.

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL AS APPROPRIATE FOR SURROUNDINGS.

Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT

WHEN FIGHTING CHEMICAL FIRE. USE WATER

SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

Spill Release Procedures:CONTAIN SPILL AND VACUUM RECOVER TO A SEPTIC TANK TRUCK. DO NOT ALLOW RUNOFF TO A SEWER UNLESS MATERIAL IS DILUTED AND NEUTRALIZED WITH DILUTE ACID SOLUTION. Neutralizing Agent:5% ACETIC ACI D (VINEGAR)

Handling and Storage Precautions:STORE IN A COOL, DRY, VENTILATED WORK
AREA. KEEP CONTAINERS CLOSED WHEN NOT IN USE. PLACE STORAGE TANKS
IN A DIKED CONTAINMENT AREA.
Other Precautions:SPILLAGE CAN BE SLIPPERY.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:NOT NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR FOR HANDLING MIST IF PROLONGED CONTACT WITH M ATERIAL. Ventilation: ADEQUATE ROOM VENTILATION SUFFICIENT TO MEET TLV. Protective Gloves: NEOPRENE OR RUBBER GLOVES Eye Protection: NO CONTACTS. USE CHEMICAL SAFETY GOGGLES Other Protective Equipment: EYE WASH. CHEMICAL APRON IS RECOMMENDED. FULL RUBBER BOOTS RECOMMENDED. DO NOT WEAR THIN RUBBER COVERS OVER LEATHER SHOE Work Hygienic Practices: DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT. WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA. Supplemental Safety and H ealth CORROSIVE LIQUID - AVOID CONTACT. CONTACT LENSES SHOULD NOT BE WORN WHEN DEALING WITH THIS PRODUCT. KEEP EYE WASH AND QUICK DRENCH SHOWER FACILITIES AVAILABLE WHEN WORKING WITHN THIS MATERIAL.

HCC:B1 Boiling Pt:B.P. Text:2408F,1320C Melt/Freeze Pt:M.P/F.P Text:680F,360C Vapor Pres:1 @ 1326F Spec Gravity:2.04 Solubility in Water:APPRECIABLE Appearance and Odor:WHITE, DELIQUESCENT SOLID. NO ODOR.

 Stability Indicator/Materials to Avoid:YES
WATER,ACIDS,FLAMMABLE LIQUIDS, ORGANIC HALOGEN COMPOUNDS (ESPECIALLY TRICHLOROETHYLENE), NITRO COMPOUNDS, AL,ZN,SN.
Stability Condition to Avoid:MOISTURE
Hazardous Decomposition Products:LIBERATES FLAMMABLE HYDROGEN GAS ON CONTACT WITH ACTIVE METALS SUCH AS ZN,AL,SN.

Waste Disposal Methods:WASTE DILUTED AND NEUTRALIZED LIQUI D COULD BE

FLUSHED TO A WASTE WATER TREATMENT SYSTEM VIA THE SEWER OR GIVEN TO A LICENSED DISPOSAL CONTRACTOR. CONFORM TO ALL APPLICABLE REGULATIONS. UNDILUTED MATER IAL IS A RCRA HAZARDOUS WASTE (CODE = D002).

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurat

e and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.