

SCM CORP/GLIDDEN COATING & RESIN DIV -- SPRED SPRAY ENAMEL-FLAT WHITE 1204 --
8010-00-724-7000

===== Product Identification =====

Product ID:SPRED SPRAY ENAMEL-FLAT WHITE 1204

MSDS Date:01/29/1986

FSC:8010

NIIN:00-724-7000

MSDS Number: BJNXB

=== Responsible Party ===

Company Name:SCM CORP/GLIDDEN COATING & RESIN DIV

Address:925 EUCLID AVE

City:CLEVELAND

State:OH

ZIP:44115

Country:US

Info Phone Num

:216-826-5566

Emergency Phone Num:216-826-5566

CAGE:LO857

=== Contractor Identification ===

Company Name:GLIDDEN CO MEMBER OF ICI WORLD PAINTS

Address:925 EUCLID AVE

Box:15049

City:CLEVELAND

State:OH

ZIP:44115

Country:US

Phone:216-344-8000

CAGE:72818

Company Name:SCM CORP/GLIDDEN COATING & RESIN DIV

Address:925 EUCLID AVE

Box:City:CLEVELAND

State:OH

ZIP:44115

Country:US

Phone:216-826-5566

CAGE:LO857

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL K

ETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10%

Other REC Limits:LEL 1.8

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 10%

Other REC Limits:NOT SPECIFIED

OSHA PEL:500 PPM/C,1000; Z2

ACGIH TLV:50 PPM, A2; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fracti

on by Wt: 10%

Other REC Limits:500 PPM/LEL 1.0

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5%

Other REC Limits:LEL 1.2

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 5%

Other REC Limits:LEL .9

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 5%

Ot

her REC Limits:LEL 1.4
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 12.5%
Other REC Limits:LEL 2.3
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE (PROPELLANT)
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 12.5%
Other REC Limits:LEL 1.8
ACGIH TLV:1000 PPM

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES I
ngestion:YES
Health Hazards Acute and Chronic:IRRITATION OF EYES, SKIN, RESPIRATORY
TRACT. PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.
Effects of Overexposure:DIZZINESS, LIGHTHEADEDNESS, NAUSEA, ANESTHETIC
EFFECT OR NARCOSIS.
Medical Cond Aggravated by Exposure:REPORTS HAVE ASSOCIATED REPEATED
AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT
BRAIN AND NERVOUS SYSTEM DAMAGE.

===== First Aid Measures =====

First Aid:INHALATIO
N: MOVE PERSON TO WELL VENTILATED AREA. ADMINISTER
OXYGEN OR ARTIFICIAL RESPIRATION IF NECESSARY. SKIN: FLUSH FROM
SKIN WITH WATER, WASH THOROUGHLY WITH SOAP AND WATER. EYE: FLUSH
IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MIN.
INGESTION AND AS NEEDED: GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:20.0F,-6.7C
Lower Limits:.9
Extinguishing Media:DRY CHEMICAL OR FOAM.
Fire Fighting Procedures:WATER

MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:VAPORS IGNITE. VAPORS HEAVIER THAN AIR/TRAVEL TO IGNITE SOURCES VIA GROUND. CLOSED CONTAINERS EXPLODE WITH EXTREME HEAT. DECOMPOSE=IRRITANT/TOXIC GASES EMITTED.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA WITH EXPLOSION-PROOF EQUIPMENT. COLLECT SMALL SPILLS WITH ABSORBENT MATERIALS. USE NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80F. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

Other Precautions:DO NOT TAKE INTERNALLY. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE WITH OSHA STANDARD 29 CFR 1910.134 AS NEEDED.

Ventilation:PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT VAPOR BUILD-UP. USE EXPLOSION-PROOF, NON-SPARKING EQUIPMENT.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:EYE WASH, SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING OR SMOKING. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS.

Supplemental Safety and Health

KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.

===== Physical/Chemical Properties =====

Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

Disclaimer (

provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.