

CONCORDE BATTERY CORP -- LEAD/ACID BATTERY, DRY CHARGED -- 6140-00-406-2633

=====  
Product Identification  
=====

Product ID: LEAD/ACID BATTERY, DRY CHARGED

MSDS Date: 02/20/1991

FSC: 6140

NIIN: 00-406-2633

MSDS Number: BJPDR

=== Responsible Party ===

Company Name: CONCORDE BATTERY CORP

Address: 2009 SAN BERNARDINO RD

City: WEST COVINA

State: CA

ZIP: 91790-1006

Country: US

Info Phone Num: 213-962-4006

Emergency

Phone Num: 213-962-4006

Preparer's Name: DGSC-SSH

CAGE: 63017

=== Contractor Identification ===

Company Name: CONCORDE BATTERY CORP

Address: 2009 SAN BERNARDINO RD

Box: City: WEST COVINA

State: CA

ZIP: 91790-1006

Country: US

Phone: 800-255-3924/818-813-1234

CAGE: 63017

=====  
Composition/Information on Ingredients  
=====

Ingred Name: LEAD OXIDE

CAS: 1317-36-8

RTECS #: OG1750000

Fraction by Wt: 49%

Other REC Limits: NONE SPECIFIED

Ingred Name: LEAD SULFATE (SARA III)

CAS: 7446-14-2

RTECS #: OG43

75000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:SEE 1910.1025  
ACGIH TLV:0.15 MG PB/M3; 9192  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Fraction by Wt: 45%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 MG/M3;DUST 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:PLASTIC BATTERY CASE  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50  
LC50 Mixture:ORAL RAT LD50 IS NOT KNOWN  
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO  
Health Hazards Acute and Chronic:PRODUCT CONTAINS LEAD. IT MUST BE FILLED WITH SULFURIC ACID BEFORE USE. SULFURIC ACID IS A CORROSIVE CAUSING BURNS TO BODY TISSUES. LEAD IS TOXIC AND SOME LEAD COMPOUNDS ARE LISTED AS CARCINOGENIC. CONTACT WITH THE LEAD IS HIGHLY UNLIKELY. CONTACT WITH THE ACID MAY OCCUR AT FILLING OR IF THE CASE IS BROKEN OR SPILLED  
Explanation of Carcinogenicity:LEAD COMPOUNDS ARE LISTED AS CARCINOGENIC IN ANIMALS AND POSSILBY IN HUMANS.  
Effects of Overexposure:CONTACT WITH SULFURIC ACID IS THE MOST LIKELY EXPOSURE, PRODUCING IRRITATION OR BURNS TO THE BODY TISSUE CONTACTED.  
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:FIRST AID IS GIVEN FOR SULFURIC ACID CONTACT. EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN.

SKIN:WASH WITH SOAP & WATER.

REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE.

INHALED:REMOVE TO FRESH AIR. INGESTED:DO NOT INDUCE VOMITING.

GIVE 2 LARGE GLASSES OF MILK OR WATER AND GET IMMEDIATE MEDICAL CARE. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. IF IRRITATION PERSISTS OR IS SEVERE,SEE A DOCTOR.

===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE

Autoignition Temp:Autoignition Temp Text:UNKNON

Extinguishing Media:USE

WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:IF ACID IS SPILLED, NEUTRALIZE. PLACE

REMAINDER IN AN ACID RESISTANT CONTAINER FOR RECYCLE OF THE LEAD.

Neutralizing Agent:SODIUM BICARBONATE OR LIME

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREA. PROTECT FROM PHYSICAL DAMAGE. PROTECT TERMINALS FROM SHORT CIRCUITS.

Other Precautions:READ MANUFACTURERS LITERATURE AND FOLLOW INSTRUCTIONS. DO NOT OVERCHARGE OR SHORT TERMINALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR WILL NOT NORMALLY BE NECESSARY. USE NIOSH/MSHA APPROVED RESPIRATOR FOR ACID DUST/MIST IF EXPOSURE IS ABOVE THE TLV/PEL. SEE 29 CFR 1910.134 FOR REGULATIONS PERTAINING TO RESPIRATOR USE.

Ventilation:NOT NORMALLY REQUIRED. USE LOCAL EXHAUST DURING CHARGING CYCLES TO AVOID AN EXPLOSIVE BUILD UP OF HYDROGEN GAS.

Protective Gloves:NONE (RUBBER IF ACID IS LEAKING)

Eye Protection:SAFETY GLASSES/SPLASH GOGGLES (LIQUID)

Other Protective Equipment:NORMA

L WORK CLOTHING. PROTECT WITH IMPERVIOUS APRON AND/OR BOOTS IF ACID IS LEAKING OR BEING HANDLED.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID ALL CONTACT WITH ACID OR INTERNALS OF THE BATTERY.

Supplemental Safety and Health

NSN COVERS A DRY CHARGED BATTERY WHICH IS SHIPPED WITHOUT THE SULFURIC ACID ELECTROLYTE. USE PROTECTIVE EQUIPMENT WHEN FILLING THE BATTERY PRIOR TO USE. MSDS IS WRITTEN TO COVER CONTACT WITH THE ACID, THE MOST LIKELY HAZARDOUS EXPOSURE.\*MSDS WRITTEN BY DGSC-SSH FROM A PRIOR MSDS FROM CONCORD BATTERY.\*

===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:PLASTIC CASED SOLID, NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG BASES (AFTER ACID FILL)

Stability Condition to Avoid:OVER CHARGING (HYDROGEN GAS IS EVOLVED CREATING AN EXPLOSION HAZARD)

Hazardous Decomposition Products:MAY EMIT LEAD FUMES UNDER FIRE

CONDITIONS, OR HYDROGEN GAS DURING CHARGING(ESPECIALLY OVER CHARGING).

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W ALL FEDERAL, STATE AND LOCAL REGULATIONS. MANUFACTURER SUGGESTS THAT DISPOSAL MAY BE DONE BY FLUSHING NEUTRALIZED ACID TO DRAIN AND SENDING REMAINDER TO LEAD RECLAIMER. DO NOT INCINERATE!!!

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.