

INDEPENDENT ENERGY CO DIV OF INDEPENDENT CORP. -- WATER WHITE KEROSENE --  
9140-01-292-4460

=====  
Product Identification  
=====

Product ID:WATER WHITE KEROSENE

MSDS Date:04/04/1989

FSC:9140

NIIN:01-292-4460

MSDS Number: BJPHR

=== Responsible Party ===

Company Name:INDEPENDENT ENERGY CO DIV OF INDEPENDENT CORP.

Box:957

City:ELYRIA

State:OH

ZIP:44036

Country:US

Info Phone Num:216-327-7100

Emergency P

hone Num:800-366-5303

CAGE:7U271

=== Contractor Identification ===

Company Name:INDEPENDENT ENERGY CO DIV OF INDEPENDENT CORP.

Box:957

City:ELYRIA

State:OH

ZIP:44036

Country:US

Phone:800-366-5303

CAGE:7U271

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM DISTILLATES (NAPHTHA)

CAS:8002-05-9

RTECS #:SE7449000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM(T); 400 PPM

ACGIH TLV:400 PPM

=====  
Hazards Identification  
=====

=====  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: IRRITATION TO EYES, NOSE,  
THROAT, SKIN AND LOSS OF COORDINATION. CHRONIC: MAY PRODUCE SKIN  
TUMORS WITH PROLONGED AND EXCESSIVE CONTACT. WILL CAUSE SKIN DRYING  
AND CRACKING.

Explanation of Carcinogenicity:LIMITED ANIMAL EVIDENCE INDICATES  
PRODUCT MAY BE A CARCINOGENIC RISK CHEMICAL TO MAN.

Effects of Overexposure:OVEREXPOSURE MAY LEAD TO EYE, NOSE, THROAT, AND  
SKIN IRRITATION. MAY CAUSE LOSS OF COORDINATION.

Medical Conditions Aggravated by Exposure:PERSONS WITH A SKIN DISORDERS SUCH  
AS DERMATITIS SHOULD USE CAUTION WHEN HANDLING OR USING THIS  
PRODUCT.

=====  
First Aid Measures

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE MOUTH-TO-MOUTH  
RESUSCITATION IF NOT BREATHING. GIVE OXYGEN IF BREATHING IS  
DIFFICULT. GET MEDICAL ATTENTION. EYES: FLUSH WITH RUNNING WATER  
FOR 15 MINUTES WHILE HOLDING EYELID. GET MEDICAL ATTENTION. SKIN:  
WASH WITH PLENTY OF SOAP & WATER. REMOVE CONTAMINATED CLOTHING. GET  
MEDICAL ADVICE. INGESTED: DO NOT INDUCE VOMITING. GET MEDICAL  
ATTENTION IMMEDIATELY.

=====  
Fire Fighting Measures

Flash Point Method:CC  
Flash Point:100F,38C  
Autoignition Temp:Autoignition Temp Text:410F  
Lower Limits:0.6  
Upper Limits:7.4  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE ON FLAMES, BUT SHOULD  
BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. WEAR SCBA WHEN FIRE  
FIGHTING IN CONFINED SPACE.

Unusual Fire/Explosion Hazard:HIGHLY VOLATILE, VAPORS MAY BE IGNITED BY  
OTHER IGNITION SOURCES.

=====  
Accidental Release Measures

Spill Release Procedures:MINOR: ABSORB MATERIAL WITH CLAY, VERMICULITE,  
OR SIMILAR ABSORBENT MATERIAL. PLACE IN DISPOSAL CONTAINER

CONTAINERS. MAJOR:

DIKE & CONTAIN SPILL. ELIMINATE SOURCES OF IGNITION. SHUT OFF  
LEAKS. REMOVE LIQUID BY VACUUM OR ABSORBENT. USE FOAM TO CONTROL  
VAPORS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL, VENTILATED WORK AREA.  
KEEP CONTAINERS CLOSED WHEN NOT IN USE. COMBUSTIBLE LIQUID; EMPTY  
CONTAINERS CAN CONTAIN HAZARDOUS RESIDUES.

Other Precautions:NONE

=====  
Exposure Controls/Personal Protection  
n  
=====

Respiratory Protection:USE NIOSH/MSHA APPROVED ORGANIC VAPOR RESPIRATOR  
FOR HIGH VAPOR CONCENTRATIONS.

Ventilation:USE IN WELL VENTILATED AREA. USE MECHANICAL VENTILATION IN  
CONFINED SPACES. KEEP AIR CONCENTRATIONS BELOW TLV.

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SPLASH SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER. WEAR BODY  
COVERING WORK CLOTHES TO AVOID PROLONGED OR REPEATED EXPOSURE.

Work

Hygienic Practices:AVOID SKIN CONTACT. WASH THOROUGHLY AFTER USE.  
DO NOT EAT OR SMOKE IN WORK AREA. LAUNDER SOILED CLOTHING BEFORE  
REUSE.

Supplemental Safety and Health  
NONE

=====  
Physical/Chemical Properties  
=====

HCC:F4

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:1.0

Vapor Density:>4

Spec Gravity:0.85

Evaporation Rate & Reference:N/K (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, COLORLESS LIQUID. CHARACTERISTIC KEROSE

NE

ODOR.

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, HALOGENS, STRONG ACIDS, AND STRONG ALKALI.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products:CARBON MONOXIDE AND ASPHYXIANTS.

===== Disposal Considerations =====

Waste Disposal Methods:USER MUST DETERMINE IF THE MATERIAL IS A

HAZARDOUS WASTE. WASTE MAY BE BURNED IN AN APPROVED INCINERATOR OR  
DISPOSED OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND  
FEDERAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person u

tilizing this

document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.