

SIKA CORPORATION -- SIKAFLEX-LA:*ALL COLORS -- 2640-00-922-6917

===== Product Identification =====

Product ID:SIKAFLEX-LA:*ALL COLORS
MSDS Date:03/22/1985
FSC:2640
NIIN:00-922-6917
MSDS Number: BJQGP
=== Responsible Party ===
Company Name:SIKA CORPORATION
Address:875 VALLEY BROOK AVE
City:LYNDHURST
State:NJ
ZIP:07071
Country:US
Info Phone Num:201-933-8800
Emergency Phone Num:800-424-9300, CHEMTRE
C
CAGE:SIKA1
=== Contractor Identification ===
Company Name:ADAMS PSP INC
Address:355 UNIONVILLE RD
Box:City:BUTLER
State:PA
ZIP:16003
Country:US
CAGE:17705
Company Name:SIKA CORPORATION
Address:875 VALLEY BROOK AVE
Box:City:LYNDHURST
State:NJ
ZIP:07071
Country:US
Phone:201-933-8800
CAGE:SIKA1

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
O

SHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CALCIUM OXIDE
CAS:1305-78-8
RTECS #:EW3100000
Fraction by Wt: 1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3
ACGIH TLV:2 MG/M3; 9192

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 6%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 2%
Other
REC Limits:NONE SPECIFIED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRIMARY SKIN IRRITANT. EYE IRRITANT.
NOT TOXIC ORALLY. NOT TOXIC BY INHALATION. NOT TOXIC DERMALLY.
Effects of Overexposure:EYE AND SKIN IRRITATION.
Medical Cond Aggravated by Exposure:PRESENSITIZATION TO PRODUCE
T.

=====
===== First Aid Measures =====

First Aid:SKIN:WASH THOROUGHLY WITH SOAP AND WATER. EYES:FLUSH WITH
COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MIN. OBTAIN MEDICAL
ATTENTION. INHALATION:MOVE TO AN AREA FREE FROM RISK OF FURTHER
EXPOSURE. INGESTION:OBTAIN MEDICAL ATTENTION IMMEDIATELY. DO NOT
INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point:143F,62C
Lower Limits:1.0
Extinguishing Media:FOAM,

DRY CHEMICAL OR CARBON DIOXIDE.

Fire Fighting Procedures:DURING A FIRE, IRRITATING TOXIC GASES AND/OR AEROSOLS FROM THE DECOMPOSITION PRODUCTS MAY BE PRESENT.

Unusual Fire/Explosion Hazard:PERSONNEL ENGAGED IN FIGHTING FIRES MUST BE PROTECTED AGAINST NITROGEN DIOXIDE FUMES AND SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN WITH CLOTH OR ABSORBENT PAPER. IF AREA IS CLOSED, VENTILATE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE TEMPERATURE:32F-122F. IF CLOSED CONTAINER OF MATERIAL IS EXPOSED TO HEAT, PRESSURE CAN BUILD UP. IF MOISTURE ENTERS DRUM, PRESSURE BUILDUP.

Other Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. STORE IN TIGHTLY CLOSED CONTAINER AND PROTECT FROM MOISTURE AND FOREIGN MATERIALS. AT THE MAXIMUM STORAGE TEMPERATURE, NON-HAZARDOUS POLYMERIZATION MAY RESULT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:CHEMICALLY RESISTANT RUBBER OR PLASTIC.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====
=====

HCC:N1

Vapor Density:>AIR

Evaporation Rate & Reference: