

ADAMS PSP INCION -- SIKAFLEX-LA, ALL COLORS -- 2640-00-922-6921

=====  
Product Identification  
=====

Product ID:SIKAFLEX-LA, ALL COLORS

MSDS Date:03/22/1985

FSC:2640

NIIN:00-922-6921

Kit Part:Y

MSDS Number: BJQGR

=== Responsible Party ===

Company Name:ADAMS PSP INCION

Address:355 UNIONVILLE RD

Box:189

City:BUTLER

State:PA

ZIP:16003

Country:US

Emergency Phone Num:412-287-6711

CAGE:MO237

=== Contract

or Identification ===

Company Name:ADAMS PSP INC

Address:355 UNIONVILLE RD

Box:City:BUTLER

State:PA

ZIP:16003

Country:US

CAGE:17705

Company Name:ADAMS PSP INCION

Address:355 UNIONVILLE RD

Box:189

City:BUTLER

State:PA

ZIP:16003

Country:US

CAGE:MO237

Company Name:SIKA CORPORATION

Address:875 VALLEY BROOK AVE

Box:City:LYNDHURST

State:NJ

ZIP:07071

Country:US

Phone:201-933-8800

CAGE:SIKA1

=====  
Composition/Information on Ingredients  
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SA

RA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:CALCIUM OXIDE  
CAS:1305-78-8  
RTECS #:EW3100000  
Fraction by Wt: 1%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:5 MG/M3  
ACGIH TLV:2 MG/M3; 9192

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 6%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TD  
UST; 9293

Ingred Name:CARBON BLACK  
CAS:1333-86-4  
RTECS #:FF5800000  
Fraction by Wt: 2%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PRIMARY SKIN IRRITANT. EYE IRRITANT.  
NOT TOXIC ORALLY. NOT TOXIC BY INHALATION. NOT TOXIC DERMALLY.  
Effects of Overexpo

sure:EYE AND SKIN IRRITATION.

Medical Cond Aggravated by Exposure:PRESENSITIZATION TO PRODUCT.

===== First Aid Measures =====

First Aid:SKIN:WASH THOROUGHLY WITH SOAP AND WATER. EYES:FLUSH WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MIN. OBTAIN MEDICAL ATTENTION. INHALATION:MOVE TO AN AREA FREE FROM RISK OF FURTHER EXPOSURE. INGESTION:OBTAIN MEDICAL ATTENTION IMMEDIATELY. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point:143F,62C

Lower Limits:1.0

Extinguishing Media:FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

Fire Fighting Procedures:DURING A FIRE, IRRITATING TOXIC GASES AND/OR AEROSOLS FROM THE DECOMPOSITION PRODUCTS MAY BE PRESENT.

Unusual Fire/Explosion Hazard:PERSONNEL ENGAGED IN FIGHTING FIRES MUST BE PROTECTED AGAINST NITROGEN DIOXIDE FUMES AND SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN WITH CLOTH OR ABSORBENT PAPER. IF AREA IS CLOSED, VENTILATE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE TEMPERATURE:32F-122F. IF CLOSED CONTAINER OF MATERIAL IS EXPOSED TO HEAT, PRESSURE CAN BUILD UP. IF MOISTURE ENTERS DRUM, PRESSURE BUILDUP.

Other Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. STORE IN TIGHTLY CLOSED CONTAINER AND PROTECT FROM MOISTURE AND FOREIGN MATERIALS. AT THE MAXIMUM STORAGE TEMPERATURE, NON-HAZARDOUS POLYMERIZATION MAY RESULT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:CHEMICALLY RESISTANT RUBBER OR PLASTIC.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supple

mental Safety and Health

THIS NSN (2640-00-922-6921) IS A KIT. THIS BONDING COMPOUND CAN ALSO BE  
PURCHASED SEPARATELY UNDER NSN:2640-00-922-6917.

===== Physical/Chemical Properties =====

HCC:N1

Vapor Density:>AIR

Evaporation Rate & Reference: