

CHESTERTON A W CO MIDDLESEX INDUSTRIAL PK -- 616 HIGH TEMPERATURE MOLY  
LUBRICANT(AEROSOL -- 9150-01-331-6975

=====  
Product Identification  
=====

Product ID:616 HIGH TEMPERATURE MOLY LUBRICANT(AEROSOL

MSDS Date:07/01/1991

FSC:9150

NIIN:01-331-6975

MSDS Number: BJQLB

=== Responsible Party ===

Company Name:CHESTERTON A W CO MIDDLESEX INDUSTRIAL PK

Address:225 FALLON RD

City:STONEHAM

State:MA

ZIP:02180

Country:US

Info Phone Num:617-438-7000

Emergency Phone Num:617-438-7000(DAY)617-438-7013 NIGHT

CAGE:71431

=== Contractor Identification ===

Company Name:CHESTERTON A W CO

Address:225 FALLON RD

Box:City:STONEHAM

State:MA

ZIP:02180-9101

Country:US

Phone:781-438-7000/800-535-5053

CAGE:71431

Company Name:FRISCHKARA JOHN H JR INC

Address:1801 ROSENEATH RD

Box:City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-353-0181

CAGE:0M4T1

=====  
Composition/Information on Ingredients  
=====

=

Ingred Name:STODDARD SOLVENT \*  
CAS:8052-41-3  
RTECS #:WJ8925000  
Fraction by Wt: 5 - 10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM \*  
ACGIH TLV:100 PPM; 9192 \*

Ingred Name:CARBON DIOXIDE \*  
CAS:124-38-9  
RTECS #:FF6400000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:10000PPM/30000STEL \*  
ACGIH TLV:5000PPM/30000STEL;92

Ingred Name:OTHER COMPONENTS (TYPE NOT SPECIFIED)  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Ro

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE- DIRECT CONTACT MAY RESULT IN EYE IRRITATION. INHALATION OF VAPOR CONCENTRATIONS IN EXCESS OF 1000 PPM MAY RESULT IN DIZZINESS, HEADACHE & OTHER CENTRAL NERVOUS SYSTEM EFFECTS. THIS VAPOR CONCENTRATION MAY ALSO IRRITATE THE EYES & RESPIRATORY TRACT. CHRONIC- PROLONGED/REPEATED CONTACT MAY CAUSE SKIN IRRITATION.

Explanation of Carci

nogenicity:DATA PER MSDS

Effects of Overexposure:DIRECT CONTACT MAY RESULT IN EYE IRRITATION.

INHALATION OF VAPOR CONCENTRATIONS IN EXCESS OF 1000 PPM MAY RESULT IN DIZZINESS, HEADACHE & OTHER CENTRAL NERVOUS SYSTEM EFFECTS. THIS VAPOR CONCENTRATION MAY ALSO IRRITATE THE EYES & RESPIRATORY TRACT.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR RESPIRATORY TRACT MAY BE AT INCREASED RISK FRO

## M EXPOSURE.

### ===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN: WASH WITH SOAP & WATER. EYE: FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED: REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED. ORAL: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN IMMEDIATELY.

### ===== Fire Fighting Measures =====

Flash Point:NONE,AEROSOL

Extinguishing Media:CARBON DIOXIDE, FOAM, O  
R DRY CHEMICAL. WATER MAY  
CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

### ===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION. EVACUATE AREA.

C  
ONTAIN SPILL. PICK UP WITH ABSORBENT MATERIAL (E.G. SAWDUST) AND TRANSFER TO A SUITABLE CONTAINER FOR DISPOSAL. KEEP OUT OF SEWERS, STREAMS AND WATERWAY S. FLUSH AWAY FROM IGNITION SOURCES WITHWATER.  
Neutralizing Agent:NOT APPLICABLE.

### ===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-DO NOT STORE IN DIRECT SUNLIGHT OR ABOVE 120F(49C).

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPE

ATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES.

USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. MAY ATTACK SOME RUB BER AND PAINTS.

### ===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. USE NIOSH APPROVED RESPIRATOR AS REQUIRED IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.

Ventilation:GOOD GENERAL VENTILATION IS SUFFICIENT FOR MOST CONDITIONS (10 ROOM VOLUMES PER HOUR).

Protective Gloves:NEOPRENE.

Ey

Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER, WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:B.P. Text:318F,159C

Vapor Density:>1

Spec Gravity:0.96

Evaporation Rate &am

p; Reference: