

LAGUNA CLAY CO -- SODIUM BISULFATE

=====  
MSDS Safety Information  
=====

FSC: 6810  
NIIN: 00-270-9984  
MSDS Date: 03/25/1991  
MSDS Num: BJQQM  
Product ID: SODIUM BISULFATE  
MFN: 01  
Responsible Party  
Cage: 40894  
Name: LAGUNA CLAY CO  
Address: 14400 LOMITAS AVE  
City: LA PUENTE CA 91746  
Info Phone Number: 818-330-0631  
Emergency Phone Number: 818-330-0631  
Preparer's Name: DELISA B. DAVIS  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 40894  
Name: LAGUNA CLAY CO  
Address: 14400 LOMITAS AVE  
City: LA PUENTE CA 91746

=====  
Contractor Summary  
=====

Cage: 40894  
Name:  
LAGUNA CLAY CO  
Address: 14400 LOMITAS AVE  
City: LA PUENTE CA 91746  
Phone: 818-330-0631

=====  
Item Description Information  
=====

Item Manager: S9G  
Item Name: SODIUM BISULFATE, ANHYDROUS, TECHNICAL  
Specification Number: MIL-S-16917  
Type/Grade/Class: I TYPE  
Unit of Issue: DR  
Quantitative Expression: 00000000100LB  
UI Container Qty: 1  
Type of Container: DRUM  
=====

=====

Ingredients

=====

Cas: 7681-38-1  
RTECS #: VZ1860000  
Name: SODIUM BISULFATE  
% Wt: >99  
Other REC Limits: NONE SPECIFIED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: NOT ESTABLISHED

=====

Health Hazards Data

=====

LD50 LC50 Mixture: ORAL LD50 (RAT) IS UNKNOWN  
Route Of Entry Inds - Inhalation: YES  
Skin: YES  
Ingestion: YES  
Carcinogenicity Inds  
- NTP: NO  
IARC: NO  
OSHA: NO  
Effects of Exposure: NONE SPECIFIED BY MANUFACTURER.  
Explanation Of Carcinogenicity: NONE OF THE INGREDIENTS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.  
Signs And Symptoms Of Overexposure: NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.  
Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.  
First Aid: INHALE-REMOVE TO FRESH AIR, GIVE CPR OR OXYGEN IF NEED;EYES/SKIN-FLUSH WITH LARGE AMOUNTS WATER FOR 15 MIN;INGEST-RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====

Handling and Disposal

=====

Spill Release Procedures: WEAR PROTECTIVE EQUIPMENTS. RECOVER MUCH AS POSSIBLE.NEUTRALIZE AREA WITH ALKALINE SOLUTION & WASH/FLUSH WITH LG Q OF WATER.  
Neutralizing Agent: ALKALINE SOLUTIONS  
Waste Disposal Methods: MANUFACTURER SPECIFIED, CAN BE FLUSHED

TO SEWER AFTER

NEUTRALIZATION I/A/W LOCAL, STATE & FEDERAL REGULATIONS.

Handling And Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED AREA.

PROTECT FROM PHYSICAL DAMAGE. AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions: AVOID SKIN CONTACT. DO NOT STORE IN HUMID LOCATION.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Text: NONE

Extingui

shing Media: EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS, USE WATER SPRAY TO COOL NEARBY CONTAINERS.

Unusual Fire/Explosion Hazard: ABOVE 570F, FUMES OF SULFUR DIOXIDE ARE EVOLVED. ELIMINATE BY FORCED DRAFT VENTILATION.

=====  
Control Measures  
=====

Respiratory Protection: WEAR MASK W/INORGANIC-TYPE CANISTER OR DUST MASK

Ventilation: USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves: RUBBER/PLASTIC

Eye Protection: GOGGLES/FACE SHIELD

Other Protective Equipment: FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONG CONTACT.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health: MSDS NOT DATED; SPEC REFERENCE:MIL-S-16917,TYPE

I. \*\*\*\*\*MSDS CREATED FOR LUGANA CLAY. LAGUNA CLAY DOES NOT HAVE A MSDS FOR SODIUM BISULFATE. LAGUNA CLAY IS A DISTRIBUTING COMPANY. MS  
DS CREATED ON 3-  
25-91.\*\*\*\*\*

=====  
Physical/Chemical Properties  
=====

HCC: N1

Solubility in Water: COMPLETE

Appearance and Odor: OFF-WHITE,BEAD LIKE,GRANULAR,DRY MATERIAL

=====  
Reactivity Data  
=====

Stability Indicator: YES

Stability Condition To Avoid: NOT KNOWN

Materials To Avoid: STRONG ALKAL

IS  
Hazardous Decomposition Products: THERMAL DECOMPOSITION  
Hazardous Polymerization Indicator: NO  
Conditions To Avoid Polymerization: NOT KNOWN

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

=====  
Transportation Information  
=====

Responsible Party Cage: 40894  
Tran  
s ID NO: 64601  
Product ID: SODIUM BISULFATE  
MSDS Prepared Date: 03/25/1991  
Review Date: 03/02/1998  
MFN: 1  
Net Unit Weight: 100 LBS  
AF MMAC Code: NR  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: DR  
Container QTY: 1  
Type Of Container: DRUM  
Additional Data: GRANULAR DRY MATERIAL.

=====  
Detail DOT Information  
=====

DOT PSN Code: ZZZ  
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSP

ORTATION

=====  
Detail IMO Information  
=====

IMO PSN Code: ZZZ  
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION  
=====

=====  
Detail IATA Information  
=====

IATA PSN Code: ZZZ  
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
Detail AFI Information  
=====

AFI PSN Code: ZZZ  
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
HAZCOM Label  
=====

Product ID: SODIUM BISULFATE  
Cage: 40894  
Company Name: LAGUNA CLAY CO  
Street: 14400 LOMITAS AVE  
City: LA PUENTE CA  
Zipcode: 91746  
Health Emergency Phone: 818-330-0631  
Label Required IND:  
Y  
Date Of Label Review: 03/25/1991  
Status Code: C  
MFG Label NO: UNK  
Label Date: 03/25/1991  
Origination Code: F  
Eye Protection IND: YES  
Skin Protection IND: YES  
Signal Word: WARNING  
Respiratory Protection IND: YES  
Health Hazard: Moderate  
Contact Hazard: Slight  
Fire Hazard: None  
Reactivity Hazard: None  
Hazard And Precautions: STORE IN COOL, DRY, WELL VENTILATED AREA. PROTECT FROM  
PHYSICAL DAMAGE. AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED  
FIRST AID: INHALE-REMOVE TO FRESH AIR,

GIVE CPR OR OXYGEN IF NEED;EYE  
S/SKIN-FLUSH WITH LARGE AMOUNTS WATER FOR 15 MIN;INGEST-RINSE MOUTH; GET  
MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF  
OVEREXPOSURE.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.