

HULS AMERICA INC -- HYDRAULIC FLUID,FIRE RESISTANT,MIL-H-83282 -- 9150-00-149-7431
===== Product Identification =====

Product ID:HYDRAULIC FLUID,FIRE RESISTANT,MIL-H-83282

MSDS Date:02/10/1989

FSC:9150

NIIN:00-149-7431

MSDS Number: BJR BQ

=== Responsible Party ===

Company Name:HULS AMERICA INC

Address:80 CENTENNIAL AVE

Box:456

City:PISCATAWAY

State:NJ

ZIP:08855-0456

Country:US

Info Phone Num:201-7

63-7173

Emergency Phone Num:201-763-7173

CAGE:63182

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

===== Composition/Information on Ingredients =====

Ingred Name:"NOT HAZARDOUS"

Fraction by Wt: 100%

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO

IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE AND SKIN IRRITATION, NAUSEA, VOMITING, RESPIRATION TRACT IRRITATION.

Effects of Overexposure:SEE "HEALTH HAZARDS"

Medical Cond Aggravated by Exposure:NONE STATED.

=====
===== First Aid Measures =====

First Aid:EYE/SKIN: WASH SKIN WITH SOAP AND WATER, FLUSH EYES WITH WATER FOR 15 MINUTES. CALL A PHYSICIAN; INHALE: REMOVE TO FRESH AIR

AND GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED; INGEST: DO NOT INDUCE VOMITING, CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:410F/210C

Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM OR CARBON DIOXIDE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. AVOID SPREADING LIQUID AND FIRE BY WATER FLOODING.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN

CLOSED CONTAINERS. COOL WITH WATER SPRAY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:COVER WITH AN INERT. ABSORBENT MATERIAL AND REMOVE TO DISPOSAL CONTAINER. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE OIL ABOVE THE MAXIMUM RECOMMENDED OPEATING TEMPERATURE OF 410F. MAY SOFTEN SOME PLASTIC

AND PAINT SURFACES. WIPE UP SPILLS IMMEDIATELY.

Other Precautions:AVOID EYE AND SKIN CONTACT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED, USE APPROPRIATE NIOSH-APPROVED RESPIRATORY PROTECTIVE EQUIPMENT.

Ventilation:USE MECHANICAL VENTILATION WITH LOCAL EXHAUST.

Protective Gloves:RECOMMENDED.

Eye Protection:CHEMICAL GOGGLES.

Other Protective Equipment:EYE WASH FOUNTAIN, SAFETY SHOWER.

Supplemental Safety and Health
MFR'S

MSDS/PRODUCT NO.: 0425600.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:520F/271C

Vapor Pres:NIL

Vapor Density:>1

Spec Gravity: