View NSN Online: https://aerobasegroup.de/nsn/6810-00-234-8366

ALDRICH CHEMICAL CO INC. -- POTASSIUM HYDROXIDE 60369 -- 6810-00-234-8366

============ Product Identification ==============

Product ID:POTASSIUM HYDROXIDE 60369

MSDS Date:04/01/1992

FSC:6810

NIIN:00-234-8366

MSDS Number: BJRCQ === Responsible Party ===

Company Name: ALDRICH CHEMICAL CO INC.

Address:1001 W. ST. PAUL AVE

Box:2060

City:MILWAUKEE

State:WI ZIP:53233 Country:US

Info Phone Num:414-273-3850

Emergency Pho

ne Num:800-231-8327

CAGE:60928

=== Contractor Identification ===

Company Name: ALDRICH CHEMICAL CO INC

Address:1001 WEST ST PAUL AVE

Box:355

City:MILWAUKEE

State:WI ZIP:53233 Country:US

Phone:414-273-3850

CAGE:60928

======= Composition/Information on Ingredients ========

Ingred Name:POTASSIUM HYDROXIDE (SARA III)

CAS:1310-58-3

RTECS #:TT2100000

Other REC Limits: NONE SPECIFIED

OSHA PEL:C, 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

=== Hazards Identification ============
LD50 LC50 Mixture:ORAL LD50 (RAT) IS 273 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: EXTREMELY DESTRUCTIVE TO MUCOUS MEMBRANES. SKIN: HARMFUL IF ABSORBED THROUGH SKIN. INHALATION: MAY BE FATAL AS A RESULT OF SPASM, INFLAMATION AND EDEMA OF THE LARYNX AND BRONCHI.
Explanation of Carcinogenicity:THIS MATERIAL IS NOT KNOWN TO BE CARCINOGENIC.
Effects of Overexposure:BURNING SENSATION, COUGHING, WHEEZING, LARYNGITIS, SHORTNESS OF BREATH, HEADACHE, NAUSEA AND VOMITING. Medical Cond Aggravated by Exposure:PERSONS WITH A SKIN DISORDER, EYE
DISORDERS, OR IMPARED RESPIRATORY FUNCTION SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.
======================================
First Aid:SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO
FRESH AIR & RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION. EYE: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. INGESTION: WASH OUT MOUTH WITH
WATER PROVIDED PERSON IS CONSCIOUS. CALL A PHYSICIAN IMMEDIATELY.
======================================
Flash Point:NONE Extinguishing Media:USE EXTINGUISHING MEDIA APPROPRIATE TO SURROUNDING FIRE CONDITI ONS. DO NOT USE WATER.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES. Unusual Fire/Explosion Hazard:EMITS TOXIC FUMES UNDER FIRE CONDITIONS

======== Accidental Release Measures ===========

Spill Release Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS, RUBBER BOOTS AND HEAVY RUBBER GLOVES. SWEEP UP, PLACE IN A BAG AND HOLD FOR WASTE DISPOSAL. AVOID RAISING DUST. VENTILATE AREA AND

WASH SPILL SITE AFTER MATERI AL PICKUP IS COMPLETE. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:STORE IN A COOL, DRY, VENTILATED PLACE. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. VERY HYGROSCOPIC. USE ONLY IN A CHEMICAL FUME HOOD. Other Precautions:SPILLAGE CAN BE SLIPPERY. MATERIAL ABSORBS MOISTURE AND CARBON DIOXIDE FROM THE AIR.
======= Exposure Controls/P ersonal Protection ==========
Respiratory Protection:NOT NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR FOR HANDLING MIST IF PROLONGED CONTACT WITH MATERIAL. Ventilation:ADEQUATE ROOM VENTILATION SUFFICIENT TO MEET TLV. Protective Gloves:NEOPRENE OR RUBBER GLOVES Eye Protection:CHEMICAL SAFETY GOGGLES Other Protective Equipment:EYE WASH. CHEMICAL APRON IS RECOMMENDED. FULL RUBBER BOOTS RECOMMENDED. DO NOT WEAR THIN RUBBER COVERS OVER LEATHER SHOE Work Hygienic Practices:D O NOT TAKE INTERNALLY. AVOID SKIN CONTACT. WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK AREA. Supplemental Safety and Health CORROSIVE LIQUID - AVOID CONTACT. CONTACT LENSES SHOULD NOT BE WORN WHEN DEALING WITH THIS PRODUCT. KEEP EYE WASH AND QUICK DRENCH SHOWER FACILITIES AVAILABLE WHEN WORKING WITHN THIS MATERIAL. DANGER: UNDER FIRE CONDITIONS MATERIAL WILL MELT AND FLOW. MOLTEN MATERIAL REACTS VIOLENTLY WITH WATER.
========== Physical/Ch emical Properties ====================================
HCC:B1 Melt/Freeze Pt:=361.1C, 682.F Vapor Pres:1 @ 719C Spec Gravity:2.044 Solubility in Water:COMPLETE Appearance and Odor:WHITE PELLETS.
======================================
Stability Indicator/Materials to Avoid:YES

ACIDS, ACID HALIDES, ACID ANHYDRIDES, MAGNESIUM, ALUMINUM, COPPER. Stability Condition to Avoid:EXTREMELY HIGH TEMPERATURES, MOISTURE Hazardous Decomposition Products:NATURE OF DECOMPOSITION PRODUCTS NOT

KNOWN.

======= Disposal Considerations ===========

Waste Disposal Methods:FOR SMALL QUANTITIES: CAUTIOUSLY ADD TO A LARGE STIRRED EXCESS OF WATER. ADJUST THE PH TO NEUTRAL. FLUSH THE AQUEOUS SOLUTION DOWN THE DRAIN WITH PLENTY OF WATER. OBSERVE ALL FEDERAL, STATE AND LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Ame rica in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.