

INCO ALLOYS INTERNATIONAL -- WELDING ELECTRODE 182T -- 3439-00-461-1324

=====
Product Identification
=====

Product ID:WELDING ELECTRODE 182T

MSDS Date:11/01/1989

FSC:3439

NIIN:00-461-1324

MSDS Number: BJRNQ

=== Responsible Party ===

Company Name:INCO ALLOYS INTERNATIONAL

Address:1401 BURRIS ROAD

City:NEWTON

State:NC

ZIP:28658-1754

Country:US

Info Phone Num:704-465-0352

Emergency Phone Num:304-526-

5780

CAGE:28553

=== Contractor Identification ===

Company Name:INCO ALLOYS INTERNATIONAL, INC. DIV INTL NICKEL CO

Address:3200 RIVERSIDE DR

City:HUNTINGTON

State:WV

ZIP:25705

Country:US

Phone:304-526-5100

CAGE:28553

=====
Composition/Information on Ingredients
=====

Ingred Name:THE FOLLOWING INGREDIENTS ARE IN THE "AS SHIPPED" PRODUCT.

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

In

gred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200000
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:IRON
CAS:7439-89-6
RTECS #:NO4565500
OSHA PEL:10MG/M3(Fe*2O*3)DUST
ACGIH TLV:5 MG/M3(Fe*2O*3)FUME

Ingred Name:MANGANESE (SARA III)
CAS:7439-96-5
RTECS #:OO9275000
Other REC Limits:STEL 3 MG/M3 FUME
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:MANGANESE OXIDE
CAS:1317-35-7
RTECS #:OP0895000
Other REC Limits:STEL 3 MG/M3 FU
ME
OSHA PEL:(C),5 MG/M3(MN)
ACGIH TLV:5 MG MN/M3; 9293

Ingred Name:MOLYBDENUM
CAS:7439-98-7
RTECS #:QA4680000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3; 9293

Ingred Name:SODIUM FLUOALUMINATE, LD50:(ORAL)200 MG/KG(RAT)
CAS:15096-52-3
RTECS #:WA9625000
OSHA PEL:2.5 MG/M3 (F)
ACGIH TLV:2 MG/M3 (AL)

Ingred Name:SODIUM SILICATE, LD50:(ORAL)1153 MG/KG(RAT)
CAS:1344-09-8

Ingred Name:NICKEL (SARA III)
CAS:7440-02-0
RTECS #:QR5950000
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3; 9192

Ingred Name:NIOBIUM, TL

V/PEL AS GENERAL WELDING FUME.

CAS:7440-03-1

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

Ingred Name:TITANIUM, METAL. TLV/PEL AS GENERAL WELDING FUME.

CAS:7440-32-6

RTECS #:XR1700000

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

=====
===== Hazards Identification =====

LD50 LC50 Mixture:SEE INGREDIENTS

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of C

arcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:INHAL: CHRONIC EXPOSURE TO WELDING FUMES CAN RESULT IN A NUMBER OF MALADIES RANGING FROM IRRITATION TO FIBROTIC LUNG DISEASE. CERTAIN COMPOUNDS CAN AFFECT THE CNS, SKELETAL SYSTEM, LIVER, AND KIDNEYS .

Explanation of Carcinogenicity:CHROMIUM: CLASS 1 (IARC, NTP); NICKEL: CLASS 1 (IARC), CLASS 2 (NTP)

Effects of Overexposure:EYES: MECHANICAL IRRITATION, CONJUNCTIVITIS.

SKIN: IRRITATION LEADING TO DE

RMATITIS. INHAL: SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH PARTICLES FROM EYEBALLS WITH CLEAN WATER FOR AT LEAST 15 MINUTES. IF IRRIT PERSISTS, GET MD. SKIN: WASH WITH SOAP & WATER TO REMOVE ANY METALLIC PARTICLES. IF A RASH DEVELOPS, GET MD. INHA L: REMOVE FROM EXPOS. IF SEVERE RESP IRRIT PERSISTS, GET MD. EXCESS INHAL OF SOME METAL FUMES CAN

PRDCE AN ACUTE REACTION (METAL FUME FEVER) WITH SYMPTOMS OF CHILLS & FEVER SIMILAR TO (SEE SUPP DATA)

===== Fire Fighting Measures =====

Extinguishing Media:USE MEDIA SUITABLE FOR SURROUNDING FIRE .
Fire Fighting Procedures:NONFLAMMABLE; HOWEVER SPARKS FROM WELDING IN USER OPERATIONS COULD IGNITE FLAMMABLE OR COMBUSTIBLE LIQUIDS, VAPORS AND SOLIDS.
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:VACUUM OR SHOVEL ANY SPILLED MATERIAL INTO A SUITABLE CONTAINER. ALLOY WASTES ARE NORMALLY COLLECTED TO RECOVER METAL VALUES.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT EXPOSE SKIN OR EYES TO HEAT AND RADIATION FROM WELDING OPERATIONS.
Other Precautions:USE SCREENS AS APPROPRIATE TO MINIMIZE UV EXPOSURE WITHIN THE WORK PLACE .

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PROTECTION NECESSARY WHEN EXPOSURE LIMITS ARE EXCEEDED DURING WELDING WITH THESE ELECTRODES. USE NIOSH/MSHA APPROVED AIR-SUPPLIED RESPIRATOR IN CONFINED SPACES.
Ventilation:WELDING:LOCAL EXHST.MAINTAIN EXPOS 1832F
Spec Gravity:4-6
Appearance and Odor:METALLIC SILVER COLORED WIRE WITH A FLUX COATING OR FLUX CORE, ODORLESS

===== Stability and Reactivity Data =====

a =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:(PRODUCED DURING CONSUMPTION) METALS, METAL OXIDES, CHROMATES, FLUORIDES, CARBON MONOXIDE, OZONE, (SEE SUPP DATA)

===== Disposal Considerations =====

Waste Disposal Methods:IF NECESSARY, DISPOSE IN ACCORDANCE WITH FEDERAL, STATE OR LOCAL REGULATIONS.

Disclaimer

(provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.