

INWELD MFG CORP -- COVERED ELECTRODES FOR MMAW -- 3439-01-039-6408

=====
Product Identification
=====

Product ID:COVERED ELECTRODES FOR MMAW

MSDS Date:09/01/1989

FSC:3439

NIIN:01-039-6408

MSDS Number: BJRQQ

=== Responsible Party ===

Company Name:INWELD MFG CORP

Address:1471 JERSEY AVE

Box:6019

City:NEW BRUNSWICK

State:NJ

ZIP:08902

Country:US

Info Phone Num:201-545-3800

Emergency Phone Num:201-545-3800

CAGE:66376

=== Contractor Identification ===

Company Name:INWELD MFG CORP

Address:3962 PORTLAND ST

Box:40

City:COPLAY

State:PA

ZIP:18037-0040

Country:US

Phone:610-261-1900

CAGE:66376

=====
Composition/Information on Ingredients
=====

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Fraction by Wt: 55-70%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3(IRON OXIDE)

ACGIH TLV:5 MG/M3 (IRON OXIDE)

Ingred Name:MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:OO9275000

Fraction

by Wt: 0.5-2.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:SILICON
CAS:7440-21-3
RTECS #:VW0400000
Fraction by Wt: 0.1-1.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 0-3.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MOLYBDENUM
CAS:7439-98
-7
RTECS #:QA4680000
Fraction by Wt: 0-1.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3; 9293

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: 5-12%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:FLUORSPAR
CAS:14542-23-5
Fraction by Wt: 3-10%
Other REC Limits:NONE SPECIFIED
OSHA PEL:2.5 MG/M3 FLUORIDE
ACGIH TLV:2.5 MG/M3 FLUORIDE

Ingred Name:POTASSIUM TITANATE
C

AS:12030-97-6
Fraction by Wt: 0-2%
Other REC Limits:NONE SPECIFIED

Ingred Name:POTASSIUM ALUMINUM SILICATE (FELDSPAR)
CAS:68476-25-5
Fraction by Wt: 0-2%
Other REC Limits:NONE SPECIFIED

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS
FORMS) (SARA III)
CAS:1344-28-1
RTECS #:BD1200000
Fraction by Wt: 0-1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICA, AMORPHOUS, DUST
CAS:112945-52-5
RTECS #:VV7310000
Fraction by
Wt: 0-2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3; 8990

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 0-3%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:POTASSIUM SILICATE
CAS:1312-76-1
Fraction by Wt: 0-3%
Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM SILICATE
CAS:1344-09-8
Fraction by Wt: 0-5%
Other REC Limits:NONE SPECIFIED

Ingred Name:CRYOLITE
CAS:15096-52-3
Fraction by

Wt: 0-2%
Other REC Limits:NONE SPECIFIED

Ingred Name:MAGNESITE
CAS:546-93-0
RTECS #:OM2470000
Fraction by Wt: 0-2%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:POTASSIUM HYDROXIDE (SARA III)
CAS:1310-58-3
RTECS #:TT2100000
Fraction by Wt: 0-0.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes

of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:FUMES AND GASES CAN BE DANGEROUS TO
YOUR HEALTH. ARC RAYS CAN INJURE EYES AND BURN SKIN. ELECTRIC SHOCK
CAN KILL. NOISE CAN DAMAGE HEARING.
Explanation of Carcinogenicity:CHROMIUM IS LISTED UNDER NTP AND IARC.
Effects of Overexposure:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNESS OF
CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE AND THROAT.
CHRO
NIC:EXCESSIVE LEVELS MAY CAUSE BRONQUIAL ASTHMA,LUNG FIBROSIS
AND PNEUMOCONIOSIS.
Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY
OR ALLERGIC CONDITIONS.HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG
SMOKERS.

===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE AND OBTAIN PROMPT MEDICAL ATTENTION. IF
NOT BREATHING,GIVE CPR/OXYGEN. EMPLOY FIRST AID TECHNIQUES
RECOMMENDED BY AMERICAN RED CROSS.

=====

=====
Fire Fighting Measures
=====

Extinguishing Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

Unusual Fire/Explosion Hazard:WELDING ARCS, SPARKS, ETC. MAY IGNITE COMBUSTIBLE MATERIAL.

=====
Accidental Release Measures
=====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN DRY AREA. ELECTRODES EXPOSED TO MOISTURE MAY EXPLODE VIOLENTLY IF USED. DRY MOIST RODS BY BAKING AT 300F FOR TEN HOURS.

Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES.MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES.AVOID ELECTRICAL SHOC

K BY MAINTAINING DRY WORK AREA. WELDING ARC CAN IGNITE COMBUSTIBLES AND FLAMMABLES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.

Ventilation:LOCAL EXHAUST TO KEEP BELOW TLV.

Protective Gloves:WELDER'S GLOVES.

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:SUBSTANTIAL DARK CLOTH,ARM

P

ROTECTOR,APRON,HAT AND SHOULDER PROTECTION. AIR SAMPLING TO DETERMINE CORRECTIVE MEASURES.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKING OR USING SANITARY FACILITIES.

Supplemental Safety and Health

NONE.

=====
Physical/Chemical Properties
=====

HCC:V7

Solubility in Water:INSOLUBLE

Appearance and Odor:WELDING ROD.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

Hazardous De

composition Products:FUMES OF IRON,COMPLEX OXIDES OF
MANGANESE,SILICON,CHROMIUM,MOLYBDENUM,FLUORIDES,CO,CO2,NITROGEN
OXIDES,OZONE.

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT WITH YOUR LOCAL ENVIRONMENTAL
OFFICER.DISPOSE OF FUMES,FLUX OR WELD GRINDING RESIDUE FROM THE
WORK AREA OR FROM FILTERS IN ACCORDANCE WITH FEDERAL,STATE AND
LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compil
ing agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.