

S.L. GILLMAN PAINT CO. -- ALKYD GLOSS ENAMEL 27875 -- 8010-00-286-7838

=====
Product Identification
=====

Product ID:ALKYD GLOSS ENAMEL 27875

MSDS Date:11/01/1988

FSC:8010

NIIN:00-286-7838

MSDS Number: BJXLM

=== Responsible Party ===

Company Name:S.L. GILLMAN PAINT CO.

Address:2250 MORELAND AVENUE, S.E.

City:ATLANTA

State:GA

ZIP:30315

Country:US

Info Phone Num:404-622-1326

Emergency Phone Num:404-

589-4400 POISON CONTROL CENTER

CAGE:OO269

=== Contractor Identification ===

Company Name:GILLMAN PAINT CO.

Address:2250 MORELAND AVE., S.E.

City:ATLANTA

State:GA

ZIP:30315

Country:US

Phone:404-622-1326

CAGE:GILLM

Company Name:S.L. GILLMAN PAINT COMPANY

Address:2250 MORELAND AVENUE, S.E.

City:ATLANTA

Phone:404 622 1326

CAGE:OO269

=====
Composition/Information on Ingredients
=====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: 30-35%

Other R

EC Limits:NONE SPECIFIED
OSHA PEL:300 PPM/400 STEL
ACGIH TLV:300 PPM; 9192

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:SWALLOWING CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.
Effects of Overexposure:EYES:SEVERE IRRITATION,REDNESS,TEARING,BLURRED VISION.SKIN:
MODERATE
IRRIT,DEFATTING,DERMATITIS.BREATHING:NASAL/RESPIRATORY IRRIT,DIZZINESS,WEAKNESS,FATIGUE,NAUSEA,HEADACHE,POSSIBLE UNCONSCIOUSNESS, AN D EVEN ASPHAXIATION.
Medical Cond Aggravated by Exposure:NONE EXPECTED

===== First Aid Measures =====

First Aid:SKIN:WASH W/SOAP AND WATER.REMOVE CONTAMINATED CLOTHES.LAUNDER CLOTHING BEFORE RE-USE.GET MEDICAL AID IF IRRIT PERSISTS.EYES:FLUSH W/LARGE AMOUNTS OF WATER.LIFTING UPPER AND LOWER LI
D OCCASIONALLY.GET MED AID.SWALLOWED:DO NOT INDUCE VOMITING.KEEP PERSON WARM,QUIET.GET MED AID.BREATHED:REMOVE TO FRESH AIR.IF BREATHING DIFFICULT,GIVE OXYGEN.IF BREATHING STOPPED,GIVE CPR.KEEP WARM/QUIET.GET MED AID.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:105F/41C
Lower Limits:1.0
Extinguishing Media:FOAM, CO2, AND DRY CHEMICAL
Fire Fighting Procedures:WEAR SCBA WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND O
R OTHER POSITIVE PRESSURE MODE WHEN FIGHTING FIRES.WATER SPRAY MAY BE INEFFECTIVE.
Unusual Fire/Explosion Hazard:VAPORS TRAVEL ALONG GROUND/MOVED BY VENTILATION/IGNITED BY PILOT LIGHT/OTHER IGNIT SOURCES AT DISTANT FROM MATERIAL.OVEREXPOSURE CAUSE HEALTH HAZARD.MAY EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCE OF IGNIT.SMALL:ABSORB ON PAPER,VERMICULITE, OTHER ABSORB MATERIAL/TRANSFER TO HOOD.LARGE:REMOVE P

PERSON NOT WEARING PROTECT CLOTHES.STOP SPILL AT SOURCE,DIKE TO STOP SPREAD TO SEWERS,STRE AMS/OTHER WATER.IF RUN-OFF, CALL AUHORITY.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORING IN HIGH TEMPERATURE OR NEAR OPEN FLAME. STORE DRUM OUT OF SUN AND AWAY FROM HEAT.
Other Precautions:DO NOT WELD/FLAME CUT EMPTY DRUM.DRUM SHOULD BE GROUNDED/BONDED WHEN POURING.AVOID BREATHING SANDING DUST.KEEP CLOSED/UPRIGHT.DO NOT STORE/USE NEAR HEAT,SPARK.CONTAINERS HAZARDOUS WHEN EMPY,RETAIN RES IDUES(VAPORS,LIQUID/SOLID).

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA RESPIRATORS UNDER SPECIFIED CONDITIONS. ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLIMENTED TO REDUCE EXPOSURE.
Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL VENTILATION) TO PREVENT/AINTAIN EXPOSURE BELOW TLV'S.
Protective Gloves:NITRILE RUBBER, NEOPREN
E
Eye Protection:CHEM SPLASH GOGGLES PER OSHA/SAFE GLASS
Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN CONTACT. WEAR IMPERVIOUS CLOTHING AND BOOTS.
Work Hygienic Practices:AVOID REPEATED OR PROLONGED CONTACT WITH SKIN. WASH HANDS BEFORE EATING OR USING WASHROOM. SMOKE IN SMOKING AREAS ONLY.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:300F,149C
Vapor Density:> THAN AIR
Evaporation
Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:49.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:AVOID HIGH TEMPERATURES, OPEN FLAME AND SPARKS.
Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS SUCH AS CARBON DIOXIDE, CARBON MONOXIDE, AND VARIOUS HYDROCARBONS.

===== Disposal Considerations =====

Waste Disp

osal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assu
me responsibility for the suitability of this information to their
particular situation.