

DEXTER AEROSPACE MATERIAL DIVISION -- EA 956 PART B, PRODUCT CODE:AB9112. --  
8040-01-126-6271

===== Product Identification =====

Product ID:EA 956 PART B, PRODUCT CODE:AB9112.

MSDS Date:08/01/1991

FSC:8040

NIIN:01-126-6271

Kit Part:Y

MSDS Number: BJYBW

=== Responsible Party ===

Company Name:DEXTER AEROSPACE MATERIAL DIVISION

Address:2850 WILLOW PASS ROAD

Box:312

City:PITTSBURG

State:CA

ZIP:94565-

0031

Country:US

Info Phone Num:510-458-8000

Emergency Phone Num:800-424-9300(CHEMTREC)

Preparer's Name:MSDS DEPT

CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

Company Name:RESIN FORMULATORS CO

Address:8500 STELLER DR

Box:City:CALVER CITY

State:CA

ZIP:90232

Country:US

Phone:213-870-9561

CAGE:03355

===== Compositio

n/Information on Ingredients =====

Ingred Name:POLYAMIDE RESIN (PROPRIETARY)

Fraction by Wt: 40-70%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9394

Ingred Name:TRIETHYLENE TETRAMINE

CAS:112-24-3

RTECS #:YE6650000

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLATILE ORGANIC COMPOUNDS

RTECS #:9999999VO

Fraction by Wt:

125F UNLESS CURING SURFACES TO BE BONDED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF LOCAL EXHAUST VENTILATION IS INADEQUATE A RESPIRATOR EQUIPPED WITH ORGANIC VAPOR CARTRIDGES MAY BE APPROPRIATE.

Ventilation:LOCAL EXHAUST VENTILATION AT THE POINT OF USE.

Protective Gloves:BUTYL RUBBER, PVC, NITRILE RUBBER GLOVES

Eye Protection:SAFETY GLASSES W/SIDE SHIELD;CHEM GOGGLE

Other Protective Equipment:AN EYEWASH AND SAFETY SHOWER SHOULD BE NEARBY AND READY FOR USE. LONG-SLEEVED SHIRT AND TROUSERS.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER HANDLING MATERIALS.

Supplemental Safety and Health

VISCOSITY:BROOKFIELD, SPDKL 1. FAILURE TO OBSERVE PRECAUTIONS IN MIXING/HEATING MAY RESULT IN EXCESSIVE HEAT BUILD-UP CAUSING AN EXOTHERM. THE EXOTHERM HAS POTENTIAL FOR RELEASE OF TOXIC GASES. OBEY HAZ WARNINGS & HANDLE EMPTY CONTAINERS AS IF THEY WERE FULL. SEE SAME NSN/CAGE PNIND:E FOR PART A OF 2-PART KIT.

===

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:405F,207C

Vapor Pres:NIL

Vapor Density:>1

Spec Gravity:0.96

pH:UNDEFI

Viscosity:10-30

Solubility in Water:COMPLETE (100%)

Appearance and Odor:LIQUID, AMBER LIQUID WITH AMMONIACAL ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Stability Condition to Avoid:AVOID MIXING PARTS A&B IN BAT

CHES >1LB &

HEATING MIXTURE >125F.

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS &

UNDETERMINED ORGANICS.

===== Disposal Considerations =====

Waste Disposal Methods:MATL AS WASTE IS NOT RCRA HAZ

WASTE.HOWEVER,INCINERATION IN EPA APPROVED WASTE INCINERATOR IS

PREFERRED.CHEM ADDITIONS/PROCESSING/OTHERWISE ALTERING MATL MAY

MAKE WASTE MANAGEMENT INFOR HEREIN INCOMPL

ETE/INACCURATE/INAPPROPRIATE.CONSULT STATE/LOC REG

Disclaimer

(provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.