

DEXTER ADHESIVES AND STRUCTURAL MATERIALS -- EA 9309 NA PART A -- 8040-01-152-8105

=====
Product Identification
=====

Product ID:EA 9309 NA PART A

MSDS Date:09/29/1989

FSC:8040

NIIN:01-152-8105

Kit Part:Y

MSDS Number: BJYBZ

=== Responsible Party ===

Company Name:DEXTER ADHESIVES AND STRUCTURAL MATERIALS

Address:2850 WILLOW PASS ROAD

Box:312

City:PITTSBURG

State:CA

ZIP:94565

Country:US

Info Phone

Num:415-687-4201

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN SYSTEM

Ingred Name:SILICA

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 149C

Extinguishing Media:DRY CHEMICAL OR HALO

N FIRE EXTINGUISHER, WATER
SPRAY, FOAM OR FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN
FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE
LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY
GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP
REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAM
MABILITY
CAUTIONS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL
INSTRUCTIONS. STORE AT ROOM TEMPERATURE (77 DEG. F) FOR 12 MONTHS.
Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:IMPERVIOUS PLASTIC
OR RUBBER.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD-UP WITH
THE RELEASE OF TOXIC GASES. DO NOT HANDLE OR USE UNTIL MSDS HAS
BEEN READ & UNDERSTOOD. CONTAINS EPOXY RESINS.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:DECOMPOSES

V

apor Pres:1

Evaporation Rate & Reference:NIL

Solubility in Water:NIL

Appearance and Odor:PEARLESCENT PASTE WITH PUNGENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND
UNDETERMINED ORGANICS.

Conditions to Avoid Polymerization:MIXING RESIN/CURING AGENT IN BATCHES
GREATER THAN 1 LB. DO NOT HEAT MIXED

ADHESIVE UNLESS CURING
SURFACES TO BE BONDED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accur
ate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.