

FENWAL INC. -- TRU-BOND (R) 214 PART B -- 8040-00-728-2887

=====  
Product Identification  
=====

Product ID:TRU-BOND (R) 214 PART B

MSDS Date:08/01/1988

FSC:8040

NIIN:00-728-2887

Kit Part:Y

MSDS Number: BJYJL

=== Responsible Party ===

Company Name:FENWAL INC.

Address:400 MAIN ST.

City:ASHLAND

State:MA

ZIP:01721

Country:US

Info Phone Num:508-881-2000

Emergency Phone Num:508-881-2000

CAGE:0KDPZ

=== Co

ntractor Identification ===

Company Name:FENWAL INC.

Address:400 MAIN ST

City:ASHLAND

State:MA

ZIP:01721

Country:US

Phone:617-881-2000

CAGE:0KDPZ

Company Name:KIDDE FENWAL INC

Address:400 MAIN ST

Box:City:ASHLAND

State:MA

ZIP:01721-2150

Country:US

Phone:508-881-2000

CAGE:0KDP7

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PHENOL

CAS:108-95-2

RTECS #:SJ3325000

Fraction by Wt: < 2%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:5 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty

:1000 LBS

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: < 30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9192

=====  
===== Hazards Identification =====

Health Hazards Acute and Chronic:THIS MATERIAL IS A D.O.T. CORROSIVE AND MAY CAUSE BURNS TO SKIN AND EYES.

Effects of Overexposure:CAN CAUSE MILD SKIN IRRITATION. MILDLY IRRITATING TO EYES. VAPORS MAY CAUSE IRRITATION TO MUCOUS MEMBRANES OF RESPIRATORY TRACT.

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IMMEDIATELY. INHALATION:REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NECESSARY. SKIN:WASH WITH SOAP & WATER. GET MEDICAL HELP IF IRRITATION PERSISTS. EYES:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP IF IRRITATION PERSISTS. INGESTION:DO NOT INDUCE VOMITING. GIVE MILK OR WATER IF CONSCIOUS.

=====  
===== Fire Fighting Measures =====

===

Flash Point Method:PMCC

Flash Point:168F,76C

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER FOG

Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:TOXIC FUMES ARE EVOLVED WHEN THIS MATERIAL IS IN A FIRE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS AND REMOVE. RESIDUAL CAN BE REMOVED WITH NONFLAMMABLE SOLVENT. INCINERATE IN ACCORDANCE WITH LOCAL POLLUTION REGULATIONS

AND ORDINANCES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED ORGANIC VAPOR RESPIRATOR.  
Ventilation:LOCAL & MECHANICAL EXHAUST.  
Protective Gloves:IMPERVIOUS GLOVES  
Eye Protection:SPLASH-PROOF GOGGLES  
Other Protective Equipment:SAFETY SHOWER AND EYE WASH FACILITIES.  
Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Vapor Density:> 1  
Spec Gravity:1.09  
Evaporation Rate & Reference:  
< 1 (ETHER=1)  
Appearance and Odor:LIGHT AMBER LIQUID, MILD CHARACTERISTIC ODOR

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS, STRONG ACIDS, EPOXY RESINS UNDER UNCONTROLLED  
CONDITIONS.  
Stability Condition to Avoid:STORAGE AT ELEVATED TEMPERATURES OVER LONG  
PERIODS OF TIME.  
Hazardous Decomposition Products:CO, CO2, NOX

=====  
===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN ACCORDANCE WITH LOCAL POLLUTION  
REGULATIONS AND ORDINANCES.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.