View NSN Online: https://aerobasegroup.de/nsn/6830-01-137-7971

NATIONAL REFRIGERANTS, INC. -- NATIONAL REFRIGERANT 500 -- 6830-01-137-7971

Product ID:NATIONAL REFRIGERANT 500

MSDS Date:01/01/1987

FSC:6830

NIIN:01-137-7971

MSDS Number: BJZKW === Responsible Party ===

Company Name: NATIONAL REFRIGERANTS, INC.

Address:11401 ROOSEVELT BLVD.

City:PHILADELPHIA

State:PA ZIP:19154 Country:US

Info Phone Num:609-455-4555/800-424-9300 C

**HEMTREC** 

Emergency Phone Num:609-455-4555/800-424-9300 CHEMTREC

**CAGE:7Y146** 

=== Contractor Identification ===

Company Name: NATIONAL REFRIGERANTS INC

Address:661 KENYON AVE

Box:City:BRIDGETON

State:NJ ZIP:08302 Country:US

Phone:800-262-0012/215-698-6620

CAGE:4J994

Company Name: NATIONAL REFRIGERANTS INC

Address:11401 ROOSEVELT BLVD

Box:City:PHILADELPHIA

State:PA ZIP:19154 Country:US

Phone:215-834-0200

CAGE:7Y146

====== Composition/Information on Ingredients ========

Ingred Name:DICHL

ORODIFLUOROMETHANE (SARA III) CAS:75-71-8 RTECS #:PA8200000 Fraction by Wt: 73.8% Other REC Limits: NONE SPECIFIED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1 Ingred Name: 1,1-DIFLUOROETHANE CAS:75-37-6 RTECS #:KI1410000 Fraction by Wt: 23.2% Other REC Limits: NONE SPECIFIED ============== Hazards Identification ======================= LD50 LC50 Mixture:LC 50 ORAL RAT >800,000 MG/KG (CCL2F2) Routes of Entry: Inhalation:Y ES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION: VAPOR IS HEAVIER THAN AIR AND CAN CAUSE SUFFOCATION BY REDUCING OXYGEN AVAILABLE FOR BREATHING. BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF B REATH, AND MAY LEAD TO NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. SKIN/EYE: IRRITATION AND FROSTBITE. Explanation of Carcinogenicity:DICHLORODIFLUORO METHANE (FREON 12) IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA. Effects of Overexposure: BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, AND MAY LEAD TO NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. LIQUID IS IRRITATING TO S KIN AND EYES, AND MAY CAUSE FROSTBITE. Medical Cond Aggravated by Exposure: PERSONS WITH KNOWN HISTORY OF HEART

Medical Cond Aggravated by Exposure:PERSONS WITH KNOWN HISTORY OF HEART DISEASE OR IRREGULARITIES OF HEARTBEAT SHOULD BE PARTICULARY CAREFUL

TO AVOID OVEREXPOSURE TO THESE VAPORS.

First Aid:INALATION: REMOVE TO FRESH AIR, CALL A PHYSICIAN. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. DO NOT GIVE EPINEPHRINE OR SIMILAR DRUGS. EYE: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. IF FROSTBITE, WARM SKIN SLOWLY. GET MEDICAL ATTENTION.

\_\_\_\_\_\_

Fire Fighting Measures ===========	
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL AS APPROPRIATE FOR SURROUNDINGS.  Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AI FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AF FIRE EXPOSED CONTAINERS WITH WATER SPRAY.  Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCTS AND VAPORS.	REA. COOL
============ Accidental Relea se Measures ===================	
Spill Release Procedures:VENTILATE AREA. KEEP UPWIND, EVACUATE ENC SPACE. DISPERSE GAS WITH FLOOR-LEVEL FORCED AIR VENTILATION WATER SPRAY. DO NOT SMOKE. REMOVE FLAMES, HEATING ELEMENT ENGINES, ETC. Neutralizing Agent:NONE	OR
======================================	=
Handling and Storage Precautions:STORE IN A CLEAN, COOL, DRY AND WELL-VENTILATED AREA OF LOW FIRE RISK. PROTECT CONTAINERS F PHYSICAL DAM AGE AND KEEP TIGHTLY CLOSED.  Other Precautions:AVOID BREATHING VAPOR, LIQUID CONTACT WITH EYES OR CLOTHING. DO NOT DROP, REUSE, OR REFILL CONTAINER. DO NOT NEAR HEAT OR IN DIRECT SUN. KEEP CONTAINERS BELOW 120 F. REAL BEFORE USE.	S, SKIN F STORE
====== Exposure Controls/Personal Protection ========	
Respiratory Protection:NONE REQUIRED FOR ADEQUATELY VENTED WORK SITUATIONS. FOR ACCIDENTAL OR NON-VENTILATED SITUATIONS, USE SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED-AIR RESPIRATOR, APPROVED BY NIOSH. Ventilation:PROVIDE LOCAL AND MECHANICAL EXHAUST WHEN USED.	
Protective Gloves:SYNTHETIC INSULATED RUBBER GLOVE  Eye Protection:CHEMICAL SPLASH GOGGLES	0055
Other Protective Equipment: USE IMPERVIOUS CLOTHING TO PROTECT EXPO	USED

Work Hygienic Practices: DO NOT SMOKE IN AREA WHILE PRODUCT IS IN USE.

AVOID BREATHING OF VAPORS AND CONTACT WITH EYES/SKIN.

SKIN FROM LIQUID CONTACT.

======= Physical/Chemical Prope

Supplemental Safety and Health

rties ==========
HCC:G3 Boiling Pt:B.P. Text:-28F,-33C Vapor Pres:232 @54C Vapor Density:3.7 AIR=1 Spec Gravity:1.16 Evaporation Rate & Description    Evaporation Rate & Description    Solubility in Water: NEGLIGIBLE Appearance and Odor: CLEAR LIQUIFIED GAS; COLORLESS; SLIGHT ETHEREAL ODOR
Percent Volatiles by Volume:100
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, ALKALI OR ALKALINE EARTH METALS, POWDERED AL, Z
N, BE ETC. Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES OF IGNITION
Hazardous Decomposition Products:DECOMPOSED BY HIGH TEMPERATURES (OPEN FLAMES, GLOWING METAL SURFACES, ETC.) FORMING HYDROCHLORIC AND HYDROFLUORIC ACIDS.
======== Disposal Considerations ===========
Waste Disposal Methods:BEST TO RECYCLE OR RECLAIM, IF POSSIBLE. WASTE MATERIAL IS A LAND-BANNED HAZARDOUS WASTE (CODE U075). CONSULT FEDERAL. STATE. OR LOCAL AUTHO

RITIES FOR PROPER DISPOSAL PROCEDURES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of t

