

RESEARCH SOLVENTS & CHEMICALS, INC. -- THINNER, CELLULOSE ACETATE BUTYRATE DOPE --
8010-00-165-5592

===== Product Identification =====

Product ID:THINNER, CELLULOSE ACETATE BUTYRATE DOPE

MSDS Date:02/05/1991

FSC:8010

NIIN:00-165-5592

MSDS Number: BJZSG

=== Responsible Party ===

Company Name:RESEARCH SOLVENTS & CHEMICALS, INC.

Address:402 INDUSTRIAL PARK DRIVE

City:PELHAM

State:AL

ZIP:35124

Country

:US

Info Phone Num:205-663-6350

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:SASSAN MORADIAN

CAGE:RESEA

=== Contractor Identification ===

Company Name:RESEARCH SOLVENTS & CHEMICALS, INC.

Address:402 INDUSTRIAL PARK DRIVE

City:PELHAM

State:AL

ZIP:35124

Country:US

Phone:205-663-6350

CAGE:RESEA

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 99%

Other REC Limits:NONE SPECIFIED

OS

HA PEL:400 PPM
ACGIH TLV:400 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Other REC Limits:NONE SPECIFIED
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)
CAS:123-42-2
RTECS #:SA9100000
Other REC Limits:NONE SPECIFIED
OSHA PEL:50 PPM
ACGIH TLV:50 PPM; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK)
) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====
=====

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO
Effects of Overexposure:EYES:VAPORS IRRITATE EYES, NOSE & THROAT.
SKIN:MAY CAUSE IRRITATION, DEFATTING OF SKIN & DERMATITIS.
INHALATION:HIGH VAPOR CONCENTRATION MAY CAUSE HEADACHE, D
IZZINESS,
NAUSEA, FATIGUE, POSSIBLE UNCONSCIOUSNESS & EVEN ASPHYXIATION WITH
PROLONGED EXPOSURE. INGESTION IS UNLIKELY ROUTE OF EXPOSURE
Medical Cond Aggravated by Exposure:NO DATA

=====
===== First Aid Measures =====
=====

First Aid:EYES:FLUSH WITH CLEAR WATER FOR AT LEAST 15 MINUTES OR UNTIL
IRRITATION SUBSIDES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.
SKIN:REMOVE CONTAMINATED CLOTHING & WASH SKIN THOROUGHLY WITH SOAP
& WATER. LAUNDRY CLOTH

HING BEFORE REUSE. INHALE:REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED APPLY ARTIFICIAL RESPIRATION, ADMINISTER OXYGEN. GET MEDICAL ATTENTION. INGESTION IS UNLIKELY ROUTE OF EXPOSURE.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:30 F/-1 C
Lower Limits:1.86
Upper Limits:10.33
Extinguishing Media:WATER SPRAY, CO2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:HANDLE AS A FLAMMABLE LIQUID
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:SHUT OFF & ELIMINATE ALL IGNITION SOURCES. KEEP PEOPLE AWAY. RECOVER FREE PRODUCT BY MOPPING OR WITH ABSORBENT MATERIAL & PLACE IN CLOSED CONTAINERS FOR DISPOSAL. AVOID CONTAMINATION OF GROUND & SURFACE WATERS.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE CONTAINERS IN A COOL DRY AREA. DO NOT STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDENTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.
Other Precautions:USE ONLY W/ADEQUATE VENT. WARNING! DO NOT CUT, WELD OR RE-USE ANY CONTAINER FOR ANY REASON WHATSOEVER. CONTAINER USED TO TRANSPORT FLAMMABLE/COMBUSTIBLE PRODUCT MAY CONTAIN PRODUCT RESIDUES WHICH COULD PRESENT FIRE, EXPLOSION, HEALTH HAZARD

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE SELF CONTAINED BREATHING APPARATUS ABOVE THE TLV LIMITS
Ventilation:LOCAL EXHAUST IS ADEQUATE
Protective Gloves:RUBBER OR PVA GLOVES SHOULD BE WORN
Eye Protection:CHEMICAL GOGGLES SHOULD BE WORN
Other Protective Equipment:EYE BATH & SAFETY SHOWER
Supplemental Safety and Health
ADVISE EMPLOYEES &/OR CUSTOMERS OF POTENTIAL HAZARD OF EMPTY CONTAINERS.

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling Pt:B.P. Text:171F,77C
Vapor Pres:57 @ 68F
Vapor Density:3.1
Spec Gravity:.8488
Evaporation Rate & Reference:3.9 (N-BU AC=

1)

Solubility in Water:COMPLETELY

Appearance and Odor:CLEAR, YELLOW LIQUID, WITH A MILD ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG ALKALIES

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME & FIRE

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE & OTHER TOXIC GASES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE & FEDERAL REGULATION. DO NOT REUSE EMPTY CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.