

JONES-HAMILTON CO -- SODIUM BISULFATE/CID AA460 -- 7930-00-559-9481

=====
Product Identification
=====

Product ID:SODIUM BISULFATE/CID AA460

MSDS Date:04/07/1986

FSC:7930

NIIN:00-559-9481

MSDS Number: BJZVY

=== Responsible Party ===

Company Name:JONES-HAMILTON CO

Address:ENTERPRISE AT WILLOW

Box:464

City:NEWARK

State:CA

ZIP:94560

Country:US

Info Phone Num:415-797-2471 OR 419-666-9838

Emergency Pho

ne Num:415-797-2471(CHEMTREC 800-424-9300)

CAGE:93594

=== Contractor Identification ===

Company Name:JONES-HAMILTON CO.

Address:8400 ENTERPRISE DRIVE

Box:City:NEWARK

State:CA

ZIP:94560

Country:US

Phone:510-797-2471/510-792-4500

CAGE:93594

=====
Composition/Information on Ingredients
=====

Ingred Name:SODIUM BISULFATE ANHYDROUS GLOBULAR (SODIUM ACID SULFATE,
NITRE CAKE)

CAS:7681-38-1

RTECS #:VZ1860000

Fraction by Wt: 94.5%

Other REC Limits:NONE SPECIFIED

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INCLUDING SIGNIFICANT ROUTES EFFECTS,
SYMPTOMS OF OVER EXPOSURE & MEDICAL CONDITIONS AGGRAVATED BY
EXPOSURE.
Effects of Overexposure:WATERING OF EYES, MILD SKIN BURNS, MILD BURNING
SENSATION MAY OCCUR TO MUCOUS MEMBRANES & UPPER RESPIRATORY TRACT.
INHALATION: IRRITANT. SKIN: MILD TO SEVE
RE IRRITANT. INGESTION:
IRRITANT.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH THOROUGHLY WITH WATER FOR 15 MINUTES, GET PROMPT
MEDICAL ATTENTION. SKIN:FLUSH WITH WATER FOR 15 MINUTES. IF BURNS
OCCUR OBTAIN MEDICAL HELP. INHALE:MOVE TO FRESH AIR LOCATION.
SWALLOW:DRIN K LARGE QUANTITIES OF WATER/MILK, FOLLOW WITH MILK OF
MAGNESIA, BEATEN EGGS OR VEGETABLE OIL. DO NOT INDUCE VOMITING.
CONTACT PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:WATER OR DRY CHEMICAL AS APPROPRIATE FOR
COMBUSTIBLES IN AREA
Fire Fighting Procedures:WHEN WATER USED TO EXTING COMBUSTIBLES/PRODUCT
IS DISSOLVED IN WATER FORMING SULFURIC ACID.USE ACID PROTECTIVE
EQUIP. ELEVATED TEMPS(+570F)IS REACHED, USE SCBA
Unusual Fire/Explosion Hazard:PRODUCT READILY DISSOLVES IN WATER TO
FORM WEAK SULFURIC ACID SOLUTION. NO GASES, TOXIC FUMES ARE EMITTED
FROM REACTION, BUT PRECAUTIONS SHOULD BE FOLLOWED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL:MATERIAL IS A GRANULAR PRODUCT & CAN BE
SWEEPED UP FROM SURFACES. LARGE:PICK UP AS MUCH AS POSSIBLE W/SHOVEL
OR OTHER TOOL. NEUTRALIZE BALANCE OF SPILL W/WEAK ALKALINE SOLUTION
& WASH DOWN TO SEWE R IF FEDERAL, STATE & LOCAL REGULATIONS PERMITS.

=====
===== Handling and Storage =====

Handling and Storage Pr

Precautions: AVOID CONTACT WITH SKIN, EYES OR CLOTHING. DO NOT STORE WHERE EXPOSED TO MOIST CONDITIONS OR NEAR STRONG ALKALIES. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions: WEAR ALL RECOMMENDED PROTECTIVE EQUIPMENT WHEN HANDLING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: NIOSH OR MSA CERTIFIED DUST MASK SHOULD BE WORN WHILE HANDLING PRODUCT TO CONTROL EXPOSURE BELOW NUISANCE DUST LIMITS OF 10 MG/M³

Ventilation: LOCAL EXHAUST
: LOCAL VENTILATION TO A DUST COLLECTOR IS RECOMMENDED.

Protective Gloves: ACID RESISTANT GLOVES: RUBBER OR NEOPRENE

Eye Protection: SAFETY GOGGLES OR FULL FACE SHEILD

Other Protective Equipment: CLOTHES SHOULD COMPLETELY COVER SKIN TO AVOID SKIN CONTACT. COATS, COVERALLS OR APRONS ARE RECOMMENDED.

Work Hygienic Practices: USE COMMON SENSE & CARE AROUND CHEMICALS. NEVER MIX CHEMICALS. CONSULT YOUR SUPERVISOR FOR OTHER PRACTICES.

Supplemental Safety and Health

=====
===== Physical/
Chemical Properties =====

HCC: C1

Melt/Freeze Pt: M.P/F.P Text: 350F, 177C

Solubility in Water: 100%

Appearance and Odor: OFF-WHITE, BEAD LIKE, GRANULAR, DRY MATERIAL

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG ALKALINE MATERIAL SUCH AS CAUSTIC. REACT WITH WATER TO FORM WEAK SULFURIC ACID SOLUTION.

Stability Condition to Avoid: STORE IN DRY AREA TO AVOID MOISTURE CONTACT

Hazardous Decom

position Products: NONE UNLESS HEATED OVER 570F AT WHICH SULFUR DIOXIDE & SULFUR TRIOXIDE ARE FORMED.

=====
===== Disposal Considerations =====

Waste Disposal Methods: COMPLY WITH ALL THE STATE, FEDERAL & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants

this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.