

S C JOHNSON & SON, INC -- CONQ-R-DUST PRESSURIZED, 14750-005 -- 7930-01-054-2097
===== Product Identification =====

Product ID:CONQ-R-DUST PRESSURIZED, 14750-005

MSDS Date:11/19/1984

FSC:7930

NIIN:01-054-2097

MSDS Number: BJZXX

=== Responsible Party ===

Company Name:S C JOHNSON & SON, INC

Address:1520 HOWE ST.

City:RACINE

State:WI

ZIP:53403-5011

Country:US

Info Phone Num:414-631-2777

Emergency Pho

ne Num:414-631-2777

Preparer's Name:GORDON B. BRADSHAW

CAGE:0U826

=== Contractor Identification ===

Company Name:S C JOHNSON & SON INC/PROF WAX DIV

Address:1525 HOWE ST

City:RACINE

State:WI

ZIP:53403

Country:US

Phone:800-725-6737/414-886-1480 INTNL#

CAGE:0U826

Company Name:SC JOHNSON AND SON INC

Address:1525 HOWE ST

Box:City:RACINE

State:WI

ZIP:53403-2236

Country:US

Phone:800-725-6737

CAGE:32204

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SEAL OIL

C

AS:64742-48-8
RTECS #:PY8036500
Fraction by Wt: 75-85%
Other REC Limits:5 MG/M3 (MIST)

Ingred Name:ISOPARAFFINIC HYDROCARBON
Fraction by Wt: 7-12%
Other REC Limits:400-500 PPM (EST)

Ingred Name:N-AMYL ACETATE (SARA III)
CAS:628-63-7
RTECS #:AJ1925000
Fraction by Wt: < 1%
Other REC Limits:100 PPM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTANE/PROPANE
Fraction by Wt: 10-20%
Other REC Limits:1000 PPM (EST)

=====
Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Health Hazards Acute and Chronic:IF TAKEN INTERNALLY, ASPIRATION OF
LIQUID PRODUCT CAN CAUSE CHEMICAL PNEUMONITIS.

=====
First Aid Measures =====

First Aid:IF PRODUCT IS SWALLOWED, DO NOT INDUCE VOMITING. SEEK MEDICAL
AID AT ONCE.

=====
Fire Fighting Measures =====

Flash Point:NR
Extinguishing Media:FOAM, CO2, DRY CHEMIC
AL, WATER FOG.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS &
PROTECTIVE CLOTHES. FIGHT FIRE FROM MAXIMUM DISTANCE OR PROTECTED
AREA. COOL & USE CAUTION AROUND EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:AEROSOL PRODUCT-FIRE EXPOSED CNTNRS MAY
ROCKET/EXPLODE. MISTS/SPRAYS MAY BE FLAMMABLE AT TEMPS BELOW FLASH
PT. VAPORS ACCUMULATE IN CONFINED/POOR VENTED AREAS.

=====
Accidental Release Measures =====

Spill Release Procedures

SES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AEROSOL CAN BY WRAPPING AND PLACING IN TRASH. DO NOT PUNCTURE OR BURN CONTAINER. DISPOSE OF SPILLED RESIDUES AND MULTIPLE UNITS IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.