

MEGUIAR'S INC. -- M10-MEGUIAR'S PROFESSIONAL PLASTIC POLISH -- 7930-01-133-5375

=====
Product Identification
=====

Product ID:M10-MEGUIAR'S PROFESSIONAL PLASTIC POLISH

MSDS Date:04/24/1990

FSC:7930

NIIN:01-133-5375

MSDS Number: BKBGJ

=== Responsible Party ===

Company Name:MEGUIAR'S INC.

Address:17991 MITCHELL SOUTH

City:IRVINE

State:CA

ZIP:92714

Country:US

Info Phone Num:714-752-8000

Emergency Ph

one Num:800-854-8073

CAGE:MEGUI

=== Contractor Identification ===

Company Name:MEGUIAR'S INC.

Address:17991 MITCHELL SOUTH

City:IRVINE

State:CA

ZIP:92714

Country:US

Phone:714-752-8000

CAGE:MEGUI

=====
Composition/Information on Ingredients
=====

Ingred Name:DIATOMACEOUS EARTH

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 6-15%

Other REC Limits:NONE SPECIFIED

Ingred Name:SILICA, CRYSTALLINE - TRIPOLI

CAS:1317-95-9

RTECS #:VV7336000

Fraction by Wt: 6-18%

Other REC Limits:N

ONE SPECIFIED
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:ALIPHATIC HYDROCARBON
CAS:8008-20-6
RTECS #:OA5500000
Fraction by Wt: 12-24%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:1000 PPM

Ingred Name:BLENDDED OIL
Fraction by Wt: 0-7%
Other REC Limits:NONE SPECIFIED

Ingred Name:NAPHTHALENE (SARA III)
CAS:91-20-3
RTECS #:QJ0525000
Fraction by Wt: 5-18%
Other REC Limits:NONE SPECIFIED
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15 STEL; 9192
EPA Rpt Qty:100 LBS
D
OT Rpt Qty:100 LBS

Ingred Name:TRADE SECRET
Fraction by Wt: 0-7%
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR INTENTIONAL EXPOSURE TO
HIGH CONCENTRATIONS MAY CAUSE IRRITATION TO SKIN, DIGESTIVE OR
BREATHING TRACTS.
Effects of Overexposure:MAY CAUSE IRRITATION TO SKIN, DIGESTIV
E OR
BREATHING TRACT.
Medical Cond Aggravated by Exposure:DERMATITUS

=====
===== First Aid Measures =====

First Aid:WASH SKIN WITH SOAP AND WATER. FLUSH EYES WITH CLEAR WATER.
IF INGESTED, DO NOT INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point:200F/93C
Extinguishing Media:DRY CHEMICAL, FOAM, CO2

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN AND AB

SORB. MAY BE CONTAINED IN METAL,
PLASTIC OR GLASS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM EXTREME HEAT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED FOR NORMAL USE.

Ventilation:LOCAL EXHAUST: ADEQUATE

Protective Gloves:FOR SENSITIVE SKIN.

Eye Protection:WHERE SPLASHING OCCURS.

Work Hygienic Practices:NORMAL

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300F,149C

Vapor Pres:3.8

Spec Gravity:.98

Solubility in Water:YES

Appearance and Odor:WHITE TO CREAM, SWEET ODOR

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:CARBON MONOXIDE

=====
===== Disposal Considerations =====

Waste Disposal Methods:SANITARY LANDFILLS FOR ABSORBENT MATERIALS, OR
AS REQUIRED BY LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability

of this information to their particular situation.