

DOW CORNING CORP -- (R) 200 FLUID,5 CST -- 9150-00-754-2600

===== Product Identification =====

Product ID:(R) 200 FLUID,5 CST

MSDS Date:04/16/1990

FSC:9150

NIIN:00-754-2600

MSDS Number: BKCFR

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

Prepare

r's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:ACCUMETRIC INC

Address:350 RING RD

Box:843

City:ELIZABETHTOWN

State:KY

ZIP:42701

Country:US

Phone:502-769-3385

CAGE:58149

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

==

=====  
Composition/Information on Ingredients  
=====

Ingred Name:"NOT HAZARDOUS"  
Fraction by Wt: 100%  
Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-EFFECTS OF OVEREXPOSURE-EYES:MAY  
CAUSE TEMPORARY DISCOMFORT.SKIN:NO KNOWN ADVERSE  
EFFECTS.INHALATION:NO ADVERSE EFFECTS IN SHO  
RT  
EXPOSURE.ORAL:AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS,ETC., D  
URING NORMAL OPERATIONS SHOULD NOT CAUSE INJURY.CHRONIC-NO KNOWN  
ADVERSE EFFECTS.  
Effects of Overexposure:SEE HEALTH HAZARDS SECTION.  
Medical Cond Aggravated by Exposure:THIS PRODUCT,LIKE ANY OTHER  
CHEMICALS,MAY ENHANCE ALLERGIC CONDITION ON CERTAIN PEOPLE.

=====  
First Aid Measures  
=====

First Aid:INHALATION:NO PROBLEM.REMOVE TO FRESH AIR.EYES:IMMEDIATELY  
FLUSH WITH PL  
ENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN.  
SKIN:WASH WITH WATER. INGESTION:NO PROBLEM.

=====  
Fire Fighting Measures  
=====

Flash Point Method:OC  
Flash Point:275F,135C  
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.

=====  
Accidental Re  
lease Measures  
=====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT FOR SALVAGE  
OR PROPER DISPOSAL.  
Neutralizing Agent:NOT APPLICABLE.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED WHEN  
NOT IN USE.  
Other Precautions:DO NOT TAKE INTERNALLY. AVOID CONTACT WITH EYES AND  
SKIN. TRACES OF FORMALDEHYDE AND OTHER THERMAL DECOMPOSITION  
PRODUCTS MAY FORM AT TEMPERATURE >300F I

N AIR.PROVIDE ADEQUATE  
VENTILATION WHEN HANDLING AT ELEVATED TEMPERATURES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:MECHANICAL

Protective Gloves:WASH HANDS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK  
CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND  
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED

CLOTHING OR

FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres: