

CHEMRAY COATINGS -- 37038 WALKWAY COMPOUND, NON-SLIP BLACK-QUART
5610-00-142-6525

=====
Product Identification
=====

Product ID: 37038 WALKWAY COMPOUND, NON-SLIP BLACK-QUART

MSDS Date: 04/04/1989

FSC: 5610

NIIN: 00-142-6525

MSDS Number: BKHFF

==== Responsible Party ====

Company Name: CHEMRAY COATINGS

Address: 209 N MICHIGAN AVE

City: KENILWORTH

State: NJ

ZIP: 07033

Country: US

Info Phone Num: 201-245-1111

Em

ergency Phone Num: 201-245-1111

Preparer's Name: FRED ARMSTRONG

CAGE: OBRN9

==== Contractor Identification ====

Company Name: CHEMRAY COATING CORP

Address: 209 N MICHIGAN AVE

Box: City: KENILWORTH

State: NJ

ZIP: 07033

Country: US

Phone: 201-245-1111

CAGE: 33832

Company Name: CHEMRAY COATINGS CORP.

Address: 209 N. MICHIGAN AVE.

Box: NA

City: KENILWORTH

State: NJ

ZIP: 07033

Country: US

Phone: 800-924-9300

CAGE: OBRN9

=====
Composition/Information on Ingredients
=====

Ingred Name: LIGHT ALIPHATIC NAPHT

HA, VM & P NAPHTHA, LACOLENE *93/1*

CAS:64742-89-8

Fraction by Wt: 32%

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:LEAD, INORGANIC LEAD (SUSPECTED HUMAN CARCINOGEN BY IARC,
NTP & ACGIH)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 0.2%

OSHA PEL:0.05 MG/CUM

ACGIH TLV:0.15 MG/CUM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:COBALT

CAS:7440-48-4

RTECS #:GF8750000

Fraction by Wt: 0.02%

Other REC Limits:0.05 PPM

OSHA PEL:0.05 MG/CUM

ACGIH TLV:0.05 MG/CUM

Ingred Name:VOL ORGANIC CMPD: 3.

22 LBS/GAL OR 387 G/L

RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:SKIN, EYE & RESPIRATORY TRACT

IRRITANT. PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE POSSIBLE.

Explanation of Carcinogenicity:SEE INGREDIENTS

Effects of Overexposure:INHALATION: HEADACHE & DIZZINESS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER.

INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE VOMITING.

OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:44F

Lower Limits:1%

Upper Limits:6%

Extinguishing Media:CO2, FOAM, WATER FOG, DRY CHEMICAL

Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR

ENCLOSED AREAS. COOL CO

CONTAINERS WITH WATER SPRAY. IF LEAK OR SPILL
IGNITES, USE WATER SPRAY TO DISPERSE VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. ADD ABSORBENT
(SAND, EARTH, SAWDUST) TO SPILL. VENTILATE AREA. OPEN WINDOW &
DOORS. IF LARGE SPILL KEEP PRODUCT FROM ENTERING SEWERS &
WATERCOURSES BY DIKING. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED.

===== Handling and Storage =====

H

Handling and Storage Precautions: AVOID BREATHING VAPOR OR FUMES. USE
ONLY WITH ADEQUATE VENTILATION. KEEP CONTAINER CLOSED WHEN NOT IN USE.
Other Precautions: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING &
INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR
RESPIRATORY IN CONFINED AREA.

Ventilation: LOCAL EXHAUST-FACE VELOCITY 60 FPM SPECIAL. USE
EXP

IMPERMEABLE PROOF EQUIPMENT.

Protective Gloves: CHEMICAL RESISTANT

Eye Protection: SPLASH GOGGLES, FACE SHIELD

Other Protective Equipment: CHEMICAL RESISTANT APRON OR CLOTHING.

Work Hygienic Practices: REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE.
WASH HANDS THOROUGHLY AFTER USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 242-282F

Melt/Freeze Pt: M.P/F.P Text: