

CHEMRAY COATING CORP -- 37038 WALKWAY COMPOUND, NON-SLIP BLACK-GALLON --
5610-00-641-0427

===== Product Identification =====

Product ID: 37038 WALKWAY COMPOUND, NON-SLIP BLACK-GALLON

MSDS Date: 04/04/1989

FSC: 5610

NIIN: 00-641-0427

MSDS Number: BKHQF

=== Responsible Party ===

Company Name: CHEMRAY COATING CORP

Address: 209 N MICHIGAN AVE

City: KENILWORTH

State: NJ

ZIP: 07033

Country: US

Info Phone Num: 201-2

45-1111

Emergency Phone Num: 201-245-1111

Preparer's Name: FRED ARMSTRONG

CAGE: 33832

=== Contractor Identification ===

Company Name: CHEMRAY COATING CORP

Address: 209 N MICHIGAN AVE

Box: City: KENILWORTH

State: NJ

ZIP: 07033

Country: US

Phone: 201-245-1111

CAGE: 33832

===== Composition/Information on Ingredients =====

Ingred Name: LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE *93/1*

CAS: 64742-89-8

Fraction by Wt: 32%

OSHA PEL: 300 PPM

ACGIH TLV: 300 PPM

Ingred Name: LEAD, INORGANIC LEA

D (SUSPECTED HUMAN CARCINOGEN BY IARC,
NTP & ACGIH)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 0.2%

OSHA PEL:0.05 MG/CUM

ACGIH TLV:0.15 MG/CUM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:COBALT

CAS:7440-48-4

RTECS #:GF8750000

Fraction by Wt: 0.02%

Other REC Limits:0.05 PPM

OSHA PEL:0.1 MG/M3;AS CO

ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name:VOL ORGANIC CMPD: 3.22 LBS/GAL OR 387 GM/L

RTECS #:9999999VO

=====
===== Hazards Identification =====

Routes of Ent

ry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic:SKIN, EYE & RESPIRATORY TRACT

IRRITANT. PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE POSSIBLE.

Explanation of Carcinogenicity:SEE INGREDIENTS

Effects of Overexposure:INHALATION: HEADACHE & DIZZINESS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER.

INHALATION: REMOVE TO FR

ESH AIR. INGESTION: DON'T INDUCE VOMITING.

OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:44F

Lower Limits:1%

Upper Limits:6%

Extinguishing Media:CO2, FOAM, WATER FOG, DRY CHEMICAL

Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPMENT FOR

ENCLOSED AREAS. COOL CONTAINERS W/WATER SPRAY. IF LEAK OR SP ILL

IGNITES, USE WATER SPRAY TO DISPERSE VAPORS.

=====
===== Accidental R

Release Measures =====

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENTILATE AREA. OPEN WINDOW & DOORS. IF LARGE SPILL KEEP PRODUCT FROM ENTERING SEWERS & WATERCOURSES BY DIKING. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED.

===== Handling and Storage =====

Handling and Storage Precautions: AVOID BREATHING VAPOR OR FUMES. USE ONLY W/ADEQUATE VENTILATION. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATORY IN CONFINED AREA.

Ventilation: LOCAL EXHAUST-FACE VELOCITY 60FPM SPECIAL. USE EXPLOSION-PROOF EQUIPMENT.

Protective Gloves: CHEMICAL RESISTANT

Eye Protection: SPLASH GOGGLES, FACE SHIELD

Other Protective Eq

uipment: CHEMICAL RESISTANT APRON OR CLOTHING.

Work Hygienic Practices: REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS THOROUGHLY AFTER USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt: B.P. Text: 242-282F

Melt/Freeze Pt: M.P/F.P Text: