

SAF-T-LOK CHEMICAL CORPORATION -- PRIMER T -- 8030-00-082-2508

===== Product Identification =====

Product ID:PRIMER T

MSDS Date:01/02/1991

FSC:8030

NIIN:00-082-2508

MSDS Number: BKJFF

=== Responsible Party ===

Company Name:SAF-T-LOK CHEMICAL CORPORATION

Address:300 EISENHOWER LANE NORTH

City:LOMBARD

State:IL

ZIP:60148

Country:US

Info Phone Num:708-971-2001

Emergency Phone Num:708-971-2001

CAGE:SA

FTL

=== Contractor Identification ===

Company Name:SAF-T-LOK CHEMICAL CORPORATION

Address:300 EISENHOWER LANE NORTH

City:LOMBARD

State:IL

ZIP:60148

Country:US

Phone:708-971-2001

CAGE:SAFTL

===== Composition/Information on Ingredients =====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 91%

Other REC Limits:NONE SPECIFIED

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:100

0 LBS

Ozone Depleting Chemical:1

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION.

Effects of Overexposure:INHALATION: DIZZINESS, WEAKNESS, NAUSEA, HEADACHE, POSSIBLY UNCONSCIOUSNESS. CONTACT WITH EYES: CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING, BLURRED VISION. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE IRRITATION & DERMATITIS.

INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA & VOMITING.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR, IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION & GET MEDICAL ATTENTION. DO NOT GIVE STIMULANTS. EYE CONTACT: FLUSH WITH WATER, SEE PHYSICIAN.

INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN. SKIN CONTACT: WASH WITH SOAP AND WATER.

=====
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:>212F,>100C

Extinguishing Media:CO2, FOAM, DRY CHEMICALS.

Fire Fighting Procedures:WATER MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL UNTIL FIRE IS OUT. USE AIR SUPPLIED MASK AND PROCEDURE FOR CHEMICAL FIRES.

Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON CONTAINER, BECAUSE PRODUCT CAN IGNITE. ON BURNING, PRODUCT GIVES OFF HYDROGEN CHLORIDE & TRACES OF PHOSGENE AND CHLORINE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQUATE VENTILATION. SOAK UP WITH SAND, CLAY, EARTH OR OTHER ABSORBENT MATERIAL AND SHOVEL INTO CONTAINER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE IN POORLY VENTILATED OR CONFINED SPACES. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. STORE IN A COOL PLACE AWAY FROM HEAT & FLAME.

=====
===== Exposure

Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED, AN APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED.

Ventilation:USE LOCAL EXHAUST & MECHANICAL IF NEEDED.

Protective Gloves:POLYETHYLENE OR POLYVINYL ALCOHOL.

Eye Protection:SAFETY GLASSES OR FACE SHIELD.

Other Protective Equipment:EYE WASH FOUNTAIN.

Supplemental Safety and Health

AVOID PROLONGED BREATHING OF VAPORS OR CONTACT WITH EYES.

===== Physical/Chemical Properties =====

H

CC:T4

Boiling Pt:B.P. Text:165F,74C

Vapor Pres:100 @ 68 F

Vapor Density:4.5

Spec Gravity:>1

Evaporation Rate & Reference:>