

TACC INTERNATIONAL CORP. -- NEOPRENE SOLVENTBORNE ADHESIVE -- 8040-00-221-3811

=====
Product Identification
=====

Product ID:NEOPRENE SOLVENTBORNE ADHESIVE

MSDS Date:07/01/1989

FSC:8040

NIIN:00-221-3811

MSDS Number: BKJHC

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

Info Phone Num:617-878-70

15

Emergency Phone Num:800-424-9300 CHEMTREC

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 37-58%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 L

B

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 16-25%
Other REC Limits:STEL-1000 PPM
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 9-15%
Other REC Limits:STEL-300 PPM
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 2-5%
Other REC Limits:STEL-150 PPM
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Health Hazards Acute and Chronic:INHALATION: ACUTE SIGNS OF
OVEREXPOSURE COULD BE HEADACHE, DIZZINESS, NAUSEA, UPPER
RESPIRATORY DRYNESS OR IRRITATION, DROWSINESS, MENTAL DEPRESSION OR
NARCOSIS, DIFFICULTY IN BREATHING. CHRONIC EFFECTS OF OVEREXPOSURE
TO SOLVENT VAPORS COULD LEAD TO PERMANENT EFFECTS TO THE NERVOUS
SYSTEM, BODY ORGANS OR BRAIN. USE *
Effects of Overexposure:*WITH ADEQUATE VENTILATION. EYES: IRRITATION.
INGESTION: MAY BE HARMFUL OR FATAL IF SWALLOWED. SKIN: REMOVAL OF
SKIN OILS, IRRITATION, DERMATITIS, EVEN SENSITIZATION WITH
OVEREXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION: GET FRESH AIR. EYES: FLUS

H WITH WATER FOR AT

LEAST 15 MINUTES, IF NECESSARY, CALL A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. INGESTION: CALL POISON CENTER IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:1

Solubility in Water:NIL

Appearance and Odor:NEUTRAL, TYPICAL ODOR

Percent Volatiles by Volume:63

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES.

Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY.

Hazardous Decomposition Products:CO AND CO2.

===== Disposal Considerations =====

Waste Disposal Methods:LIQUID MATERIAL IS DESIGNATED AS HAZARDOUS WASTE UNTIL ALL SOLVENTS AND VAPORS HAVE EVAPORATED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.