

J C ENTERPRISES INC -- ENTERORISE 1000,LUBRICATING OIL,WATCH. -- 9150-00-270-0063

=====
Product Identification
=====

Product ID:ENTERORISE 1000,LUBRICATING OIL,WATCH.

MSDS Date:05/01/1991

FSC:9150

NIIN:00-270-0063

MSDS Number: BKJHR

=== Responsible Party ===

Company Name:J C ENTERPRISES INC

Address:724 WESTCLIFF RD

Box:7345

City:WILMINGTON

State:DE

ZIP:19803-1712

Country:US

Info Phone Num:302-478

-8326

Emergency Phone Num:302-478-8326

Preparer's Name:V.C.W.

CAGE:2S598

=== Contractor Identification ===

Company Name:J C ENTERPRISES INC

Address:724 WESTCLIFF RD

Box:7345

City:WILMINGTON

State:DE

ZIP:19803-1712

Country:US

Phone:302-478-8326

CAGE:2S598

=====
Composition/Information on Ingredients
=====

Ingred Name:"NOT HAZARDOUS"

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhal

ation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE/CHRONIC-EYES/SKIN:NOT
ESTABLISHED.INHALATION:LOW HAZARD.INGESTION:EXPECTED LOW.
Effects of Overexposure:SEE HEALTH HAZARDS SECTION.
Medical Cond Aggravated by Exposure:NOT DETERMINED

=====
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF NEEDED.INHALATION/INGESTION:NONE
SHOULD BE NEEDED.EYES:IMMEDIATELY FLUSH WITH
WATER FOR 15
MINUTES.SKIN:FLUSH WITH WATER.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:392F,200C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Meas
ures =====

Spill Release Procedures:ABSORB WITH INERT ABSORBENT MATERIAL SUCH AS
VERMICULITE AND PLACE IN IMPERVIOUS CONTAINER.
Neutralizing Agent:NOT APPLICABLE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,WELL VENTILATED AREA
AWAY FROM OXIDIZING AGENTS.
Other Precautions:DO NOT BREATHE MIST.AVOID PROLONGED OR REPEATED
BREATHING OF VAPOR.AVOID CONTACT WITH EYES AND SKIN. WASH HANDS
BEFORE E
ATING OR DRINKING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:VENTILATE AS NEEDED TO COMPLY WITH EXPOSURE LIMIT.
Protective Gloves:STANDARD CHEMICAL OPERATION
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYE WASH STATION.
Work Hygienic Practices:WASH HANDS AFTER HANDLING PRODUCT.
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:752F,400C

Vapor Pres:1.5

Vapor Density:1.06

Spec Gravity:1.0

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NONE

Appearance and Odor:COLORLESS TO YELLOW LIQUID-SLIGHT WOOD ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:DIRECT FLAME

Hazardous Decomposition Products:CARBON DIOXIDE AND WATER

===== Disposal Considerations =====

Waste Dis

posal Methods:DISPOSE BY INCINERATION OR CONTRACT WITH

LICENSED CHEMICAL WASTE DISPOSAL AGENCY.DISCHARGE OR TREATMENT MAY
BE SUBJECT TO FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for i

ts use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.