View NSN Online: https://aerobasegroup.de/nsn/9390-00-290-5089

ACGIH TLV:0.05

--DICALITE 341,375,689,2500,4200,6-10,SP-5,(CONTD IN SUPPLEME) GREFCO INC 9390-00-290-5089 Product ID:DICALITE 341,375,689,2500,4200,6-10,SP-5,(CONTD IN SUPPLEME) MSDS Date:03/13/1992 FSC:9390 NIIN:00-290-5089 MSDS Number: BKJJD === Responsible Party === Company Name: GREFCO INC Address:3435 W LOMITA BLVD City:TORRANCE State:CA ZIP:90509 Country:US Info Phone Num:310-517-0700/310-517-0766 Emergency Phone Num:310-517-0700/310-517-0773 Preparer's Name:W.N. PAVLAKOVICH CAGE:52293 === Contractor Identification === **Company Name: GREFCO INC** Address:3435 W LOMITA BLVD Box:City:TORRANCE State:CA ZIP:90509 Country:US Phone:213-517-0700/213-517-0773 CAGE:52293 Company Name: MAYS CHEMICAL CO, INC (317-842-822) CAGE:MAYSC Ingred Name: FLUX-CALCINED DIATOMACEOUS EARTH CONTAINS CRYSTALLINE SI LICA (CONTAINS INGRED 2 & 3) CAS:68855-54-9 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED Ingred Name: SILICA, CRYSTALLINE - QUARTZ ------UP TO 5% CAS:14808-60-7 RTECS #: VV7330000 Fraction by Wt: SEE #1% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 RDUST; Z-3 ACGIH TLV:0.1 MG/M3 RDUST;9394 Ingred Name: SILICA, CRYSTALLINE - CRISTOBALITE------UP TO 70% CAS:14464-46-1 RTECS #:VV7325000 Fraction by Wt: SEE #1% Other REC Limits:NONE RECOMMENDED **OSHA PEL:SEE TABLE Z-3**

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chronic:PRODUCT CONTAINS CRYSTALLIINE SILICA. LONG TERM INHAL OF CRYSTALLINE SILICA DUSTS MAY CUASE LUNG DISEASE (SILICOSIS). ACUTE:TRANSITORY UPPER RESPIRATORY IRRITANT. CHRONIC:LONG TERM INHAL OF UDST LEVEL S IN EXCESS OF PEL MAY CAUSE

LUNG DISEASE (SILICOSIS) . INGEST:NOT HAZARDOUS. EYE:TEMPORARY IRRIT

&/OR INFLAMMATION.

Explanation of Carcinogenicity:PER MSDS:IARC HAS CLASSIFIED CRYSTALLINE SILICA AS PROBABLE HUMAN CARCINOGEN (GROUP 2A); OSHA/NTP HAS NOT.

Effects of Overexposure:INHLA:COUGHING, IRRITATION OF NOSE & THROAT; CONGESTION MAY OCCUR UPON OVEREXPOSURE. TEMPORARY EYE IRRITATION &/OR INFLAMMATION.

Medical Cond Aggravated by Exposure:PRE-EXISTING UPPER RESPIRATORY & LUNG DISEASE (SUCH AS BRONCHITIS, EMPHYSEMA, ASTHMA, OR O THERS).

TARGET ORGANS:LUNGS.

First Aid:INHAL:REMOVE FROM DUSTY AREA. DRINK WATER TO CLEAR THROAT. BLOW NOSE TO EVACUATE DUST. EYES:DO NOT RUB EYES. FLUSH W/COPIOUS AMOUNTS OF WATER TO REMOVE ANY DUST PARTICLES. CONSULT A PHYSICIAN IF IRRIT ATION PERSISTS. SKIN/INGEST:NOT APPLICABLE.

Flash Point:NON-FLAMMABLE Extinguishing Media:PER MSDS N/A HOWEVER USE APPROPRIATE EXTINGUISHING MEDIA FOR SURROUNDING FIRE AND MATERIALS. Fire Fighting Procedures:NONE. Unusual Fire/Explosion Hazard:NONE.

Spill Release Procedures: VACUUM CLEAN OR WET SWEEP. AVOID DUSTING. USE A DUST SUPPRESSANT WHEN SWEEPING. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions: ALWAYS SEGREGAT

E MATLS BY MAJOR HAZ CLASS.STORE IN DRY PLACE.REPAIR ALL BROKEN BAGS IMMED.AVOID CREATING DUST.COMPLY W/ALL FED/STATE/LOC REGS. Other Precautions: GREFCO CURRENTLY EVALUATING CONCLUSIONS REACHED BY IARC THRU STUDIES SPONSORED BY INTERNATIONAL DIATOMITE PRODUCERS ASSOC(IDPA) & CONDUCTED BY UNIV OF WASHINGTON SCHOOL OF PUBLIC HEALTH.INSURE PROPER RESP PROT FOR REPAIR/MAINT CONTAMIN EQPM **Respiratory Protection** :USE NIOSH APPROVED RESPIRATORS TO PROTECT AGAINST SILICOSIS PRODUCING DUSTS. INSURE PROPER RESPIRATORY PROTECTION FOR REPAIR/MAINTENANCE OF CONTAMINATED EQPMT. Ventilation: USE ADEQUATE EXHAUST VENTI &/OR DUST COLLECTION TO KEEP DUST LEVELS BELOW PEL. Protective Gloves: SAF EYEWEAR TO PROT FROM DUST.NORM N/R. Eye Protection: GLOVE TO PROT OVERLY-SENS SKIN.NORM N/R. Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: MAINTAIN GOOD HOUSEKEEPING PRACTICE. Su pplemental Safety and Health ID:SPECIAL SPEEDFLOW, SPEEDEX, SPEEDPLUS, D.C. SPEEDPLUIS, SWIMMING POOL BRADE. HCC:N1 Spec Gravity:2.35 Solubility in Water:SLIGHT Appearance and Odor: WHITE TO OFF WHITE POWDER, ODORLESS. Stability Indicator/Materials to Avoid:YES HYDROFLUORIC ACID. Stability Condition to Avoid:NONE IN DESIGNED USE. AVOID CONTACT W/HYDROFLUO RIC ACID. Hazardous Decomposition Products: REACTS WITH HYDROFLUORIC ACID TO FORM TOXIC SILICON TETRAFLUORIDE GAS. Waste Disposal Methods:NOT CONSIDERED AS HAZARDOUS WASTES BY RCRA (40CFR PART 261). PLACE WASTE & SPILLAGE IN CLOSED CONTIANERS. DISPOSE OF IN APPROVED LANDFILL. RQ:N/A.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the De

partment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.