

DEXTER ADHESIVES & STRUCTURAL MATERIALS DIVISION -- EA 9330 PART A -- 8040-01-137-8418
===== Product Identification =====

Product ID:EA 9330 PART A
MSDS Date:09/29/1989
FSC:8040
NIIN:01-137-8418
Kit Part:Y
MSDS Number: BKJVJ
=== Responsible Party ===
Company Name:DEXTER ADHESIVES & STRUCTURAL MATERIALS DIVISION
Address:2850 WILLOW PASS ROAD
Box:312
City:PITTSBURG
State:CA
ZIP:94565
Country:US
Inf
o Phone Num:415-687-4201
Emergency Phone Num:415-687-4201 (CHEMTREC)800-424-9300
Preparer's Name:SUZANNE FRANZ
CAGE:33564

=== Contractor Identification ===
Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address:2850 WILLOW PASS ROAD
Box:312
City:BAY POINT
State:CA
ZIP:94565-3299
Country:US
Phone:202-483-7616
CAGE:33564

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN SYSTEM
Other REC Limits:NONE SPECIFIED

Ingred Name:SILICA
CAS:112945-52

-5

RTECS #:VV7310000

Fraction by Wt: < 05%

Other REC Limits:NONE SPECIFIED

OSHA PEL:20 MPPCF

ACGIH TLV:0.1 MG/M3

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS FORMS) (SARA III)

CAS:1344-28-1

RTECS #:BD1200000

Fraction by Wt: 3.84%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:VOC 300

Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER SPRAY, FOAM OR FOG.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASSES MAY BE LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

===== Handling and Storage =====

==

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS. STORE AT ROOM TEMPERATURE (77 DEG F) FOR 12 MONTHS.

Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER.

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:AS NEEDED T

O PROTECT SKIN AND CLOTHING.

Supplemental Safety and Health

*TO BE BONDED. FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD-UP WITH THE RELEASE OF TOXIC GASSES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:DECOMPOSES

Vapor Pres: 1

Evaporation Rate & Reference:NIL

Solubility in Water:NIL

Appearance and Odor:PEARLESCENT PASTE WITH PUNGENT ODOR

===== Stability and Reactivity Data =====

Stability Indicato

r/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND UNDETERMINED ORGANICS.

Conditions to Avoid Polymerization:AVOID MIXING RESIN AND CURING AGENT IN BATCHES >1 LB TOTAL.DO NOT HEAT MIXED ADHESIVE ABOVE 75F UNLESS CURING SURFACES*

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.