

EXXON COMPANY, USA, A DIV OF EXXON CORP. -- #205 CYLINDER STOCK -- 9150-00-223-4133  
===== Product Identification =====

Product ID:#205 CYLINDER STOCK

MSDS Date:09/10/1987

FSC:9150

NIIN:00-223-4133

MSDS Number: BKKCJ

=== Responsible Party ===

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info Phone Num:713-656-5949

FAX: 713-656-3631

Emergency Phone Num:713-656-3424/2443 (MEDICAL)

CAGE:DO850

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 FAX: 713-656-3631

CAGE:DO850

Company Name:VINELAND WAX SPECIALTIES INC WAX PROCESSING

Address:S RAIL

ROAD BLVD  
Box:City:MINOTOLA  
State:NJ  
ZIP:08341  
Country:US  
Phone:609-697-3941 (OUT OF BUSINESS)  
CAGE:63400

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC  
CAS:64742-54-7  
RTECS #:PY8035500  
Fraction by Wt: 100%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5 G/KG OF BODY WEIGT  
Routes of Entry:  
Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:HIGH VAPOR LEVELS MAY CAUSE EYE  
IRRITATION. THE LIQUID IS SLIGHTLY IRRITATING TO THE SKIN.  
PROLONGED OR REPEATED CONTACT CAN RESULT IN DEFATTING AND DRYING  
WHICH MAY RESULT IN SKIN IRRITATION AND DERM ATITIS. INHALATION OF  
VAPORS MAY BE IRRITATING TO NOSE & LUNGS. INGESTION MAY CAUSE  
VOMITING  
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO ING  
REDIENTS AT  
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT  
CARCINOGENS.  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:PREEXISTING EYE, SKIN AND  
RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS  
PRODUCT.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING  
EYELIDS OPEN. GET MEDICAL ATTENTION IMMEDIATELY. SKIN: WASH WITH  
SOAP

AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. GIVE MOUTH-TO-MOUTH RESUSCITATION IF NOT BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. KEEP HEAD BELOW HIPS IF VOMITING OCCURS. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:575F,302C  
Autoignition Temp:Autoignition Temp Text:>500F  
Lower Limits:0.9  
Upper Limits:7.0  
Extinguishing  
Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.  
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION. WEAR APPROPRIATE RESPIRATOR & PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK IF SAFE TO DO SO. DIKE TO CONTAIN. REMOVE WITH VACUUM OR PUMP TO STORAGE/SALVAGE VESSELS. ABSORB RESIDUE WITH INERT MATERIAL. WATER FLUSH AREA.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP LIQUID/VAPOR AWAY FROM HEAT, SPARKS & FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION. IGNITED VAPORS MAY EXPLODE.  
Other Precautions:"EMPTY" CONTAINERS CAN CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, DRILL, GRIND, WELD OR PERFORM SIMILAR OPERATIONS ON OR NEAR CONTAINERS. STATIC ELECTRICITY MAY ACCUMULATE AND CREATE A FIRE HAZARD. GROUND CONTAINERS, FIXED & TRANSFER EQUIPMENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID PROLONGED OR REPEATED BREATHING OF VAPORS. IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS, USE A NIOSH/MSHA APPROVED RESPIRATOR.

EITHER AN AIR-SUPPLIED OR AIR-PURIFYING  
RESPIRATOR WITH ORGANIC VAPOR CARTRIDGES IS RECOMMENDED.  
Ventilation:USE EXPLOSION-PROOF LOCAL AND/OR MECHANICAL VENTILATION.  
AVOID OPEN ELECTRICAL SOURCES NEAR PRODUCT VAPOR AREAS.  
Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL  
Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD  
Other Protective Equipment:INDUSTRIAL WORK CLOTHING TO MINIMIZE  
CONTACT. RUBBER APRON AD BOOTS AS REQUIRED. EYE BATH AND SAFETY  
SHOWER RECOMMENDED

Work Hygienic Practices:WASH THOROUGHLY AFTER USING PRODUCT AND BEFORE  
EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.

Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:556F,291C  
Vapor Pres:5  
Spec Gravity:0.87  
pH:7  
Evaporation Rate & Reference: