

EXXON CO USA, A DIV OF EXXON CORP. -- UNIVOLT 60 -- 9160-00-926-2124

=====
Product Identification
=====

Product ID:UNIVOLT 60

MSDS Date:10/24/1988

FSC:9160

NIIN:00-926-2124

MSDS Number: BKLKV

=== Responsible Party ===

Company Name:EXXON CO USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info Phone Num:713-870-6000

Emergency Phone Num:713-870-

6000, 713-656-3424

CAGE:29700

=== Contractor Identification ===

Company Name:EXXON CHEMICAL CO USA SALES OFFICE

Address:1333 W LOOP S

Box:3272

City:HOUSTON

State:TX

ZIP:77253

Country:US

Phone:281-870-6000/6884

CAGE:4H542

Company Name:EXXON COMPANY U.S.A.

Address:Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIG

HT

NAPHTHENIC

CAS:64742-53-6

RTECS #:PY8036000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 OIL MIST

ACGIH TLV:5 MG/M3 (OIL MIST)

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-INGESTION:NO ILL EFFECTS

EXPECTED. INHALATION OF MIST MAY CAUSE IRRITATION. MINUTE AMOUNTS
ASPIRATED INTO LUNGS MAY

CAUSE PULMONARY INJURY. EYE: IRRITATION.

SKIN: NOT NORMALLY EXPECTED TO CAUSE ILL EFFECTS.

CHRONIC-PROLONGED/REPEATEDSKIN CONTACT MAY CAUSE IRRITATION,
DERMATITIS.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS
LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:MILD EYE & SKIN IRRITATION.

Medical Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VO

MITING. GET MEDICAL ATTENTION.

SKIN: FLUSH WITH SOAP & WATER. REMOVE AND LAUNDER CONTAMINATED
CLOTHING. EYE: FLUSH WITH PLENTY OF WATER FOR ATLEAST 15 MINUTES.
GET MEDICAL A TTENTION. INHALATION: REMOVE TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:293F,145C

Autoignition Temp:Autoignition Temp Text:>500F

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:WEAR

FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL. PROTECT FROM IGNITION. ABSORB
WITH SAND OR INERT MATERIAL. SWEEP OR SCOOP UP AND TRANSFER TO
DISPOSAL DRUM

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SPARKS AND OPEN FLAMES.
Other Precautions:DO NOT GET IN EYES, OR ON CLOTHING. KEEP AWAY FROM
SPARKS AND OPEN FLAMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.
Ventilation:USE WITH ADEQUATE VENTILATION.
Protective Gloves:NEOPRENE/BUTYL RUBBER/POLYETHYLENE
Eye Protection:FACE SH
IELD
Other Protective Equipment:NONE
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:460F,238C
Melt/Freeze Pt:M.P/F.P Text:-50F,-46C
Vapor Pres:5
Spec Gravity:0.88
pH:NEUTRL
Viscosity:410 SSU
Evaporation Rate & Reference: