View NSN Online: https://aerobasegroup.com/nsn/8040-01-163-3481

Product ID:EA 9309.3 NA PART B MSDS Date:02/14/1991 FSC:8040 NIIN:01-163-3481 Kit Part:Y MSDS Number: BKLMD === Responsible Party === Company Name: DEXTER HYSOL AEROSPACE INC DIV OF EXTER CORP Address:2850 WILLOW PASS ROAD Box:312 City:PITTSBURG State:CA ZIP:94565-3237 Country :US Info Phone Num:510-458-8000 Emergency Phone Num:510-458-8000 Preparer's Name:SUZANNE FRANZ CAGE:33564 === Contractor Identification === **Company Name: DEXTER CORPORATION ADHESIVE & COATING SYSTEMS** Address:2850 WILLOW PASS ROAD Box:312 **City:BAY POINT** State:CA ZIP:94565-3299 Country:US Phone:202-483-7616 CAGE:33564

Ingred Name:ALKYLAMINES Other REC Limits:NONE SPECIFIED

======= Hazards Identification =======

_____ Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:MATERIAL MAY BE CORROSIVE TO SKIN AND EYES. HIGH CONCENTRATION OF VAPORS CAN CAUSE SEVERE IRRITATION OF EYES AND RESPIRATORY TRACT. LIQUID CAUSES SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED. PROLON GED AND REPEATED CONTACT MAY CAUSE SENSITIZATION WHICH WILL RESULT IN ALLERGIC REACTIONS. Effects of Overexposure: POSSIBLE BU RNS TO EYES AND SKIN; IRRITATION AND POSSIBLE SENSITIZATION TO SKIN. VAPORS MAY BE IRRITATING TO UPPER RESPIRATORY TRACT. First Aid:FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WATER. WASH SKIN THOUROUGHLY WITH SOAP AND WATER, RUBBING ALCOHOL OR HAND CLEANER. DO NOT USE SOLVENTS. REMOVE SOILED CLOTHING AND WASH BEFORE REUSE. IF IRRIT ATION PERSIST, SEE PHYSICIAN. ================== Fire Fighting Measures _____ Flash Point Method:TOC Flash Point:>300F,>149C Extinguishing Media: DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER SPRAY, FOAM OR FOG. Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS. Unusual Fire/Explosion Hazard: DENSE SMOKE AND TOXIC GASES MAY BE LIBERATED. Spill Release Procedures: WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLAS SES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS. Handling and Storage Precautions: KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTION. FOLLOW RECOMMENDED CURING SCHEDULE. MAY BE STORED AT ROOM TEMPERATURE (77F) FOR 12 MONTHS. Other Precautions:*SURFACES TO BE BONDED. FAILURE TO OBSERVE CAUTIONS

MAY RESULT IN EXCESSIVE HEAT BUILD-UP

WITH THE RELEASE OF TOXIC GASES.

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION. Ventilation:LOCAL EXHAUST RECOMMENDED. Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER. Eye Protection:SAFETY GLASSES OR GOGGLES. Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING. Supplemental Safety and Health KEY1:C2.

HCC:B2 Boiling Pt: B.P. Text:N. A. Vapor Pres:NA Vapor Density:8.45 Spec Gravity:1.02 Evaporation Rate & amp; Reference:NIL Solubility in Water:NA Appearance and Odor:TRANSPARENT BLUE LIQUID WITH AMMONIACAL ODOR Percent Volatiles by Volume:NA

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.
Stability Condition to Avoid:NA
Hazardous Decomposition Products:CO, NO2, ALDEHYDES, ACIDS AND
UNDETERMI
NED ORGANICS.
Conditions to Avoid Polymerization:AVOID MIX RESIN/CURING AGENT IN
BATCHES GREATER THAN 1 LB TOTAL. DO NOT HEAT MIXED ADHESIVE ABOVE 100F UNLESS CURING *

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department o f Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.