

EASTMAN KODAK CO. -- 177 9123 EKTAMATIC S-30 STABILIZER -- 6750-00-912-0455
===== Product Identification =====

Product ID:177 9123 EKTAMATIC S-30 STABILIZER

MSDS Date:01/17/1991

FSC:6750

NIIN:00-912-0455

MSDS Number: BKMYH

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:71

6-722-5151 (72-1)

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 60 - 65%

Other REC Limits:NONE SPECIFIED

Ingred Name:AMMONIUM THIOCYANATE (SARA III)

CAS:1762-95-4

RTECS #:XK7875000

Fr

action by Wt: 20 - 25%
Other REC Limits:NONE SPECIFIED
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACETIC ACID (SARA III)
CAS:64-19-7
RTECS #:AF1225000
Fraction by Wt: 1 - 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM ACETATE
CAS:126-96-5
RTECS #:AJ4375000
Fraction by Wt: 1 - 5%
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes

of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-INHALATION/SKIN:LOW HAZARD FOR
RECOMMENDED HANDLING.EYES:MAY BE IRRITATING.INGESTION:EXPECTED TO
BE A LOW INGESTION HAZARD.CHRONIC-NOT GIVEN.
Explanation of Carcinogenicity:THIS PRODUCT CONTAINS NO INGREDIENT
LISTED AS CARCINOGEN BY IARC,NTP, OR OSHA.
Effects of Overexposure:SEE HEALTH HAZARDS SECTION.
Medical Cond Aggravated by Exposure:NONE SP
ECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS OCCUR.EYE/SKIN:IMMEDIATELY
FLUSH WITH WATER FOR AT LEAST 15 MINUTES.INHALATION:REMOVE TO FRESH
AIR.INGESTION:IF CONSCIOUS, DRINK 1-2 GLASSES OF WATER.SEEK MEDICAL
CAR E.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:WATER SPRAY; DRY CHEMICAL; CARBON DIOXIDE
Fire Fighting Procedures:USE

SELF-CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH MATERIAL TO SEWER WITH LARGE AMOUNT OF
WATER.

Neutralizing Agent:NOT GIVEN.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-KEEP CONTAINER TIGHTLY CLOSED

AND AWAY FROM OXIDIZING AGENTS & ACIDS.

Other Precautions:AVOID BREATHING VAPOR. AVOID CONTACT WITH
EYES,SKIN,OR CLOTHING. WASH THOROUGHLY AFTER HANDLING.USE
VENTILATION THAT IS ADEQUATE TO KEEP EMPLOYEE EXPOSURE TO AIRBORNE
CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATORS ARE NOT NEEDED FOR NORMAL USE.A
NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH A DUST/MIST

FILTER OR A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR WHERE
AIRBORNE CONCENTRATIONS > TLV.

Ventilation:GOOD GENERAL VENTILATION (10 ROOM VOLUMES PER HOUR) SHOULD
BE SUFFICIENT.

Protective Gloves:LATEX OR COTTON

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER.IMPERVIOUS
CLOTHING SUCH AS BOOTS,APRON,WHOLE BODY SUIT MADE FROM NEOPRENE.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

FORMUL

A CHANGED. SEE P/N A SAME NSN.

===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.09

pH:4.5

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, COLORLESS TO PALE PINK SOLUTION; SLIGHT ODOR

Percent Volatiles by Volume:75

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS

Stability Conditio

n to Avoid:HIGH TEMPERATURES AND FLAMES

Hazardous Decomposition Products:COMBUSTION WILL PRODUCE CARBON DIOXIDE AND PROBABLY CARBON MONOXIDE. AMMONIA AND OXIDES OF NITROGEN MAY ALSO BE PRESENT.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE, AND LOCAL REGULATIONS.THIS CHEMICAL IS EXPECTED TO HAVE A LOW BIOLOGICAL OXYGEN DEMAND,AND IT IS EXPECTED TO CAUSE LITTLE OXYGEN DEPLETION IN AQUATIC SYSTEMS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.