

GOLDEN WEST REFINING COMPANY -- NO 2 DIESEL FUEL -- 9140-00-286-5294

=====
Product Identification
=====

Product ID:NO 2 DIESEL FUEL

MSDS Date:09/29/1989

FSC:9140

NIIN:00-286-5294

MSDS Number: BKNTR

=== Responsible Party ===

Company Name:GOLDEN WEST REFINING COMPANY

Address:13538 EAST FOSTER ROAD

City:SANTA FE SPRINGS

State:CA

ZIP:90670

Country:US

Info Phone Num:213-921-3581/CHEMTREC 800-424-9300

Emergency Phone Num:213-921-3581/LA POISON 213-664-2121

Preparer's Name:D.C. MARKIE

CAGE:41982

=== Contractor Identification ===

Company Name:GOLDEN WEST REFINING COMPANY

Address:13538 EAST FOSTER ROAD

Box:City:SANTA FE SPRINGS

State:CA

ZIP:90670

Country:US

Phone:213-921-3581/LA POISON 213-664-2121

CAGE:41982

=====
Composition/Information on Ingredients
=====

Ingred Name:GAS OILS, STRAIGHT RUN (INTERMEDIATE)

CAS:64741-43-1

Other REC Limits:100 PPM

=====
Haza

Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and

Chronic:ACUTE-EYE:VAPORS->IRRITATION;LIQUID->BURNING,TEARING &
REDNESS.SKIN:IRRITATION.PROLONGED/REPEATED CONTACT MAY CAUSE

BURNING,REDNESS,DERMATITIS & SKIN

DAMAGE.INHALATION:MIST/VAPOR->IRRITATION OF NOSE,T

HROAT,RESPIRATORY TRACT & CNS

DEPRESSION(HEADACHE,NAUSEA,DIZZINESS).INGESTION:SEE

INHA

LATION.CHRONIC-SKIN CANCER(ANIMAL)

Explanation of Carcinogenicity:LONG-TERM SKIN APPLICATION OF SIMILARLY & PROCESSED PETROLEUM DISTILLATES HAVE BEEN SHOWN TO CAUSE SKIN CANCER IN ANIMAL

Effects of Overexposure:THIS MATERIAL IS AN ASPIRATION HAZARD,A SKIN IRRITANT AND MAY BE A SKIN CANCER HAZARD BASED ON TESTS WITH LABORATORY ANIMALS. PRIMARY EXPOSURE ROUTE IS SKIN CONTACT. INHALATION IF VAPORS OR MISTS ARE GENERATED.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN, LIVER, KIDNEY AND RESPIRATORY CONDITIONS.

=====
===== First Aid Measures =====

First Aid:GET MEDICAL CARE.INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED.EYE/SKIN:FLUSH WITH WATER.WASH SKIN WITH SOAP & WATER.INGESTION:DO NOT INDUCE VOMITING.IF CONSCIOUS,DRINK MILK/WATER.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:125F,52C

Autoignition Temp:Autoignition Temp Text:494F

Lower Limi

ts:0.5

Upper Limits:5.0

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.USE WATER TO DISPERSE VAPORS,TO FLUSH UNIGNITED & PROTECT PERSONNEL

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:CARBON DIOXIDE, CARBON MONOXIDE AND WATER VAPOR.VAPORS MAY TRAVEL TO IGNITION SOURCE AND FLASH BACK.

=====
===== Accidental Release Measures =====

Spill Release Procedures:PICK UP SMALL SPILLS/RESIDUE WITH INERT ABSORBENT.FOR LARGE SPILLS,WEAR PROTECTIVE EQUIPMENT.REMOVE ALL IGNITION SOURCES.DIKE & CONTAIN SPILLS.DON'T ALLOW SPILLS TO ENTER SEWERS,STREAMS ETC.PROVIDE EX PLOSION-PROOF VENTILATION.PICK UP SPILLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORAGE-STORE IN COOL,DRY WELL-VENTILATED A

REA IN CLOSED CONTAINER AWAY FROM HEAT,IGNITION
SOURCES & OXIDIZERS.

Other Precautions:ELECTRICALLY BOND & GROUND CONTAINERS WHEN
TRANSFERRING MATERIAL.EMPTY CONTAINERS RETAIN MATERIAL RESIDUE
AND,IF HEATED,MAY GENERATE VAPORS WHICH CAN IGNITE &
EXPLODE.COMPLETLY DRAIN & COMMERCIALLY CLEAN BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN SITUATION WHERE VAPOR CONCENTRATIONS MAY
EXCEED THE RECOMMENDED EXPOSURE LIMITS,

A NIOSH-APPROVED ORGANIC

VAPOR CARTRIDGE RESPIRATOR SHOULD BE WORN. USE SELF-CONTAINED
SUPPLIED-AIR RESPIRATOR FOR EMERGENCIES.

Ventilation:GENERAL DILUTION OR MECHANICAL VENTILATION/EXPLOSION-PROOF
LOCAL EXHAUST

Protective Gloves:NEOPRENE, NITRILE, OR POLYVINYL ALCOHOL

Eye Protection:USE CHEMICAL SAFETY GOGGLES & FACESHIELD

Other Protective Equipment:EYE WASH STATION.BARRIER CREAMS SPECIFIC FOR
PETROLEUM-BASED MATERIALS MAY BE USED WHEN GLOVES ARE IMPRACTICAL.

Work Hygienic

Practices:DO NOT TAKE INTERNALLY. AVOID SKIN CONTACT.

WASH SKIN AFTER USING PRODUCT. DO NOT EAT, DRINK OR SMOKE IN WORK
AREA.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:350F,177C

Vapor Pres:LOW

Vapor Density:> 1

Spec Gravity:0.85 - 0.90

Viscosity:33 - 40 SSU

Evaporation Rate & Reference: