

BAKER SEALANTS AND COATINGS CO -- PAINT OIL EXTERIOR CONCRETE -- 8010-00-598-5154

=====
Product Identification
=====

Product ID:PAINT OIL EXTERIOR CONCRETE
MSDS Date:11/13/1990
FSC:8010
NIIN:00-598-5154
MSDS Number: BKPJD
=== Responsible Party ===
Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:B
City:JERSEY CITY
State:NJ
ZIP:07304
Country:US
Info Phone Num:201-333-6986
Emer
gency Phone Num:201-333-6986
Preparer's Name:CHARLES FRIEDMAN
CAGE:34094
=== Contractor Identification ===
Company Name:BAKER SEALANTS AND COATINGS CO
Address:234 SUYDAM AVE
Box:City:JERSEY CITY
State:NJ
ZIP:07304-3306
Country:US
Phone:201-333-6986
CAGE:34094

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt: 26.0%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TL

V:10 MG/M3 TDUST; 9192

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 26.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:RAW LINSEED OIL

CAS:8001-26-1

RTECS #:OI9690000

Fraction by Wt: 12.0%

Other REC Limits:NONE SPECIFIED

Ingred Name:CARBON BLACK

CAS:7440-44-0

RTECS #:FF5250000

Fraction by Wt: 4.0%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:M

INERAL SPIRITS

Other REC Limits:NONE SPECIFIED

ACGIH TLV:500 TLV

Ingred Name:VOC: 192

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: CAN CAUSE IRRITATION. SKIN: CAN

CAUSE DEFATTING. INHALATION: CAN RESULT IN HEADACHE AND DIZZINESS.

INGESTION: CAN CAUSE NAUSEA.

=====

=====
First Aid Measures
=====

First Aid: EYES: FLUSH WITH COOL RUNNING WATER FOR 15 MINS. SEE A PHYSICIAN! SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: PROVIDE FRESH AIR AND REST. INGESTION: DO NOT INDUCE VOMITING. DRINK ONE OR TWO GLASSES OF WATER TO DILUTE.

=====
Fire Fighting Measures
=====

Flash Point Method: TCC

Flash Point: 110F, 43C

Lower Limits: 0.8

Upper Limits: 5.0

Extinguishing Media: CO₂, DRY CHEMICAL FOAM.

Fire Fighting Procedures: FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF SMOKE OR VAPORS. DO NOT USE WATER.

Unusual Fire/Explosion Hazard: ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAMES. VAPORS FROM EXPLOSIVE MIXTURE BETWEEN UPPER AND LOWER EXPLOSIVE UNITS.

=====
Accidental Release Measures
=====

Spill Release Procedures: VENTILATE AREA. REMOVE ALL SOURCES OF IGNITION. PICK UP SPILL IMMEDIATELY WITH INERT ABSORBENT(S) AND NONSPARKING TOOLS. SAFELY DISPOSE OF SATURATED ABSORBENT(S) BY IMMERSING IN WATER. WEAR PROTECTIVE EQUIPMENT DURING CLEAN-UP.

=====
Handling and Storage
=====

Handling and Storage Precautions: KEEP CONTAINERS TIGHTLY CLOSED. KEEP CONTAINERS AWAY FROM ANY SOURCE OF IGNITION.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: ORGANIC CARTRIDGE MASK OR AIR PACK IF VENTILATION IS INADEQUATE.

Ventilation: LOCAL: IS RECOMMENDED. MECHANICAL: WITH APPROVED CLASS D EXPLOSION-PROOF MOTOR AND SWITCHES.

Protective Gloves: NEOPRENE RUBBER GLOVES.

Eye Protection: CHEMICAL SAFETY GOGGLES.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC: F4

Boiling Pt: B.P. Text: 300F, 149C

Vapor Pres: 3.1 MM HG

Vapor Density: 3.9

Spec Gravity: 1.46

Viscosity: 89-104

Evaporation Rate & Reference: 0.12 (BUAC = 1)

Solubility in Water: INSOL

UBLE

Appearance and Odor:BLACK COLOR, PETROLEUM

Percent Volatiles by Volume:25.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:STRONG ACIDS OR BASES, OXIDIZING AGENTS
AND SELECTED AMINES.

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL METHODS MUST COMPLY WITH ALL STATE,
LOCAL AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.