

HULS AMERICA INC -- MIL-L-46000C -- 9150-00-753-4686

=====
Product Identification
=====

Product ID:MIL-L-46000C
MSDS Date:09/27/1990
FSC:9150
NIIN:00-753-4686
MSDS Number: BKSSX
=== Responsible Party ===
Company Name:HULS AMERICA INC
Address:80 CENTENNIAL AVE
Box:456
City:PISCATAWAY
State:NJ
ZIP:08855-0456
Country:US
Info Phone Num:201-980-6800
Emergency Phone Num:201-980-6800, 201-763-7173
Prepa
rer's Name:P.A. PARKER
CAGE:63182
=== Contractor Identification ===
Company Name:HULS AMERICA INC
Address:TURNER PLACE
Box:365
City:PISCATAWAY
State:NJ
ZIP:08855
Country:US
Phone:201-763-7173
CAGE:63182

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENTS
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

Ingred Name:BIS (2-ETHYLHEXYL) SEBACATE
CAS:122-62-3
RTECS #:VS1000000
Fraction by Wt: 89%
Other REC Limits:NONE SPECIFIED
OSHA PEL:

NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:VOLATILE ORGANIC COMPOUND 0.375 LBS/GAL
RTECS #:9999999VO
Fraction by Wt: 450F,>232C

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER FOG
Fire Fighting Procedures:BURNING WILL PRODUCE TOXIC FUMES. WEAR SCBA
AND FULL TURN-OUT GEAR TO FIGHT FIRE. AVOID SPREADING LIQUID AND
FIRE BY WATER FLOODING.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN
CLOSED CONTAINERS. COOL WITH WATER SPRAY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA, COVER WITH INERT, ABSORBENT
MATERIAL AND REMOVE TO DISPOSAL CONTAINER. OBEY ALL RELEVANT
FEDERAL, STATE AND LOCAL LAWS. DLA-HMIS: IF SPILL ENTERS
WATERWAY/SEWER, CALL NATIONAL RESPONSE CENTER AT 800-424-8802.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE OIL ABOVE THE
MAXIMUM
RECOMMENDED OPERATING TEMPERATURE, OF 270F. MAY SOFTEN SOME
PLASTICS OR PAINTS. WIPE UP SPILLS IMMEDIATELY.
Other Precautions:AVOID SKIN & EYE CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED, USE APPROPRIATE NIOSH APPROVED
RESPIRATORY PROTECTIVE EQUIPMENT.
Ventilation:LOCAL OR MECHANICAL EXHAUST RECOMMENDED
Protective Gloves:IMPERMEABLE GLOVES TO MINIMIZE CONTACT
Eye Protection:CHEMICAL SPLASH GOGGLES/FACE
SHIELD
Other Protective Equipment:EYE WASH FOUNTAIN, SAFETY SHOWER. WASH
CONTAMINATED CLOTHING BEFORE REUSE.
Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>660F,>349C
Melt/Freeze Pt:M.P/F.P Text:340F,171C
Spec Gravity: