

SPORLAN VALVE COMPANY -- RCW48 CATCH ALL BRAND -- 4130-00-136-9191

=====  
Product Identification  
=====

Product ID:RCW48 CATCH ALL BRAND

MSDS Date:11/24/1985

FSC:4130

NIIN:00-136-9191

MSDS Number: BKYGZ

=== Responsible Party ===

Company Name:SPORLAN VALVE COMPANY

Address:7525 SUSSEX AVENUE

City:ST. LOUIS

State:MO

ZIP:63143

Info Phone Num:(314) 647-2775

Emergency Phone Num:(314) 647-2775

Preparer's N

ame:JOHN E. HOFFMAN

CAGE:78462

=== Contractor Identification ===

Company Name:SPORLAN VALVE COMPANY

Address:7525 SUSSEX AVE.

Box:City:ST LOUIS

State:MO

ZIP:63143

Phone:314-647-2775

CAGE:78462

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS  
FORMS) (SARA III)

CAS:1344-28-1

RTECS #:BD1200000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SODIUM ALUMINOSILICATE

CAS:1344-00-9

Ingred N

ame:ALUMINUM PHOSPHATE, MONOAMMONIUM PHOSPHATE

CAS:7784-30-7

RTECS #:TB6450000

ACGIH TLV:2 MG/CUM

Ingred Name:KAOLIN

CAS:1332-58-7

RTECS #:GF1670500

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:2 MG/M3 TDUST; 9293

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION/SKIN/EYES/INGESTION: LOW  
RISK OF IRRITABILITY.

Explanation of Carci  
nogenicity:NONE  
Effects of Overexposure:INHALATION/SKIN/EYES/INGESTION: LOW RISK OF  
IRRITABILITY.

=====  
===== Fire Fighting Measures =====

Flash Point:NON-FLAMMABLE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH SMALL AMOUNTS W/WATER, MOP UP OR SWEEP  
UP, & DISPOSE OF IN THE SAME MANNER AS CONVENTIONAL PAPER TRASH.

=====  
===== Handling and Storage =====

Handling and Storage P  
recautions:NO PRECAUTIONS ARE NECESSARY FOR  
STORING. STORE IN NORMAL CONDITIONS. CORE WILL PICK UP WATER BY  
ADSORPTION PROCESS/WILL GET WARM DURING WATER PICKUP.  
Other Precautions:TO OPEN THE METAL CAN CONTAINING THE PRODUCT, THE  
TEAR STRIP ON THE SIDE OF THE CAN SHOULD BE OPENED CAUTIOUSLY USING  
PLIERS TO AVOID BEING CUT BY THE SHARP METAL EDGE OF THE TEAR  
STRIP.

=====  
===== Exposure Controls/Personal Protection =====

Other Protective Equipment:AS NECESSARY  
Sup

plemental Safety and Health

PRODUCT TO REMOVE CONTAMINANTS FROM CIRCULATING REFRIGERANT ON REFRIGERATION/AIR CONDITIONING SYSTEMS/UTILIZE SOLID FILTER CORE MOLDED FROM DESICCANT GRANULES. IF MOLDED BLOCK IS CRUSHED, IT IS POSSIBLE THE RESULTING POWDER TO BE CONSIDERED A NUISANCE DUST IF >10 MG/CUM. 8% VOL AT 1700F.

===== Physical/Chemical Properties =====

Spec Gravity:1.1 G/ML  
Solubility in Water:INSOLUBLE  
Appearance and Odor:CORE IS ABRASIVE SOLID MATERIAL/ODORLESS, COMPOSED OF WHITE/BUFF/BLACK GRAINS.  
Percent Volatiles by Volume:0%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE HANDLED ACCORDING TO LOCAL LAWS. HOWEVER, SPILLED MATERIAL NEED NOT BE CONSIDERED A HAZARDOUS WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.